

Package ‘LMest’

October 8, 2026

Title Generalized Latent Markov Models

Description Latent Markov models for longitudinal continuous and categorical data. See Bartolucci, Pandolfi, Pennoni (2017)<[doi:10.18637/jss.v081.i04](https://doi.org/10.18637/jss.v081.i04)>.

Version 4.0.0

Date 2026-10-04

Author Francesco Bartolucci [aut, cre],
Silvia Pandolfi [aut],
Fulvia Pennoni [aut],
Luca Brusa [ctb],
Alessio Farcomeni [ctb],
Alessio Serafini [ctb]

Maintainer Francesco Bartolucci <francesco.bartolucci@unipg.it>

Depends R (>= 3.5.0)

Imports MASS, MultiLCIRT, stats, mvtnorm, Formula(>= 1.2-3), mix,
utils, graphics, diagram(>= 1.6.4), mclust(>= 5.4.6),
scatterplot3d(>= 0.3-41), grDevices

Suggests knitr, rmarkdown, bookdown

VignetteBuilder knitr

NeedsCompilation yes

Repository CRAN

LazyLoad yes

Encoding UTF-8

ByteCompile true

License GPL (>= 2)

Date/Publication 2026-10-08 16:10:02 UTC

Contents

LMest-package	3
bootstrap	5

bootstrap_lm_basic	7
bootstrap_lm_basic_cont	8
bootstrap_lm_cov_latent	9
bootstrap_lm_cov_latent_cont	11
data_criminal_sim	12
data_drug	13
data_employment_sim	14
data_heart_sim	15
data_long_cont	16
data_market_sim	16
data_SRHS_long	17
decoding	18
design_matrices	20
draw	21
draw_lm_basic	26
draw_lm_basic_cont	27
draw_lm_cov_latent	28
draw_lm_cov_latent_cont	29
draw_lm_mixed	31
est_lm_basic	32
est_lm_basic_cont	34
est_LM_cat_multinom	36
est_lm_cov_latent	40
est_lm_cov_latent_cont	42
est_lm_cov_manifest	44
est_lm_mixed	47
est_mc_basic	48
est_mc_cov	50
LMbasic-class	52
LMbasiccont-class	53
lmest	54
lmestCont	60
lmestData	64
lmestDecoding	66
lmestFormula	68
lmestMc	71
lmestMixed	74
lmestSearch	76
LMlatent-class	79
LMlatentcont-class	81
LMmanifest-class	82
LMmanifestcont-class	83
LMmixed-class	85
long2matrices	86
long2wide	87
matrices2long	88
MCbasic-class	89
McCov-class	90

mc_multinom	91
NLSYlong	94
plot	95
print	97
PSIDlong	98
RLMSdat	99
RLMSlong	100
se	101
search.model.LM	103
summary	105
summary.lmestData	106

Index	108
--------------	------------

LMest-package	<i>Overview of the Package LMest</i>
---------------	--------------------------------------

Description

The package LMest is a framework for specifying and fitting Latent (or Hidden) Markov (LM) models for the analysis of longitudinal continuous and categorical data. Covariates are also included in the model specification through suitable parameterizations.

Details

Different LM models are estimated using specific functions that require data in long format. Responses are mainly categorical; functions for continuous responses are identified by Cont. For continuous responses, a (multivariate) Gaussian distribution conditional on the latent process is assumed. The functions are as follows:

lmest Function to estimate LM models for categorical responses generating the following classes:

- **LMbasic-class** for the basic LM model without covariates.
- **LMmanifest-class** for the LM model with covariates in the measurement submodel.
- **LMlatent-class** for the LM model with covariates in the latent model.

lmestCont Function to estimate LM models for continuous outcomes generating the following classes:

- **LMbasiccont-class** for the basic LM model for continuous responses without covariates.
- **LMlatentcont-class** for the LM model for continuous responses with covariates in the latent model.

lmestMixed Function to estimate Mixed LM models for categorical responses with discrete random effects in the latent model generating the following class:

- **LMmixed-class** for the mixed LM model.

lmestMc Function to estimate Markov Chain models for categorical responses generating the following classes:

- **MCbasic-class** for the Markov Chain (MC) model without covariates.

- `McCov-class` for the MC model with covariates.

Maximum likelihood estimation of model parameters is performed through the Expectation-Maximization algorithm, which is implemented by relying on Fortran routines.

Model selection is provided by `lmest` and `lmestCont` functions. In addition, function `lmestSearch` allows us to deal with both model selection and multimodality of the likelihood function. Two main criteria are provided to select the number of latent states: the Akaike Information Criterion and the Bayesian Information Criterion.

Prediction of the latent states is performed using the function `lmestDecoding`, which implements local and global decoding (the Viterbi algorithm) based on the output of the `lmest`, `lmestCont`, and `lmestMixed` functions.

The package allows us to deal with missing responses, including drop-out and non-monotonic missingness, under the missing-at-random assumption.

Standard errors for the parameter estimates are obtained by the function `se` through exact computation of the information matrix or by reliable numerical approximations of this matrix.

The `print` method shows some convergence information, and the `summary` method shows the estimation results.

The package also provides some real and simulated data sets that are listed using the function `data(package = "LMest")`.

Author(s)

Francesco Bartolucci [aut,cre], Silvia Pandolfi [aut], Fulvia Pennoni [aut], Alessio Farcomeni [ctb], and Alessio Serafini [ctb]

Maintainer: Francesco Bartolucci <francesco.bartolucci@unipg.it>

References

- Pennoni, F., Pandolfi, S. and Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.
- Bartolucci, F., Pandolfi, S. and Pennoni, F. (2017). LMest: An R Package for Latent Markov Models for Longitudinal Categorical Data, *Journal of Statistical Software*, **81**, 1-38, doi:10.18637/jss.v081.i04.
- Bartolucci, F., Farcomeni, A., and Pennoni, F. (2014). Latent Markov models: A review of a general framework for the analysis of longitudinal data with covariates (with discussion). *TEST*, **23**, 433-465.
- Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013). *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

See Also

`lmest`, `lmestCont`, `lmestMc`, `lmestMixed`, `LMmixed-class`, `LMbasic-class`, `LMbasiccont-class`, `LMlatent-class`, `LMlatentcont-class`, `LMmanifest-class`

bootstrap	<i>Parametric bootstrap</i>
-----------	-----------------------------

Description

Function that performs parametric bootstrap resampling to compute standard errors for the parameter estimates.

Usage

```
bootstrap(est, ...)
## S3 method for class 'LMbasic'
bootstrap(est, B = 100, seed = NULL, ...)
## S3 method for class 'LMbasiccont'
bootstrap(est, B=100, seed = NULL, ...)
## S3 method for class 'LMlatent'
bootstrap(est, B = 100, seed = NULL, ...)
## S3 method for class 'LMlatentcont'
bootstrap(est, B = 100, seed = NULL, ...)
```

Arguments

<code>est</code>	an object obtained from a call to <code>lmest</code> and <code>lmestCont</code>
<code>B</code>	number of bootstrap samples
<code>seed</code>	an integer specifying the state of the random number generator
<code>...</code>	further arguments

Value

Average of bootstrap estimates and standard errors for the model parameters in `est` object.

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

Examples

```
## Not run:

# LM model for categorical responses with covariates on the latent model

data("data_SRHS_long")
SRHS <- data_SRHS_long[1:2400,]

# Categories rescaled to vary from 0 ("poor") to 4 ("excellent")

SRHS$srhs <- 5 - SRHS$srhs
```

```

out1 <- lmest(responsesFormula = srhs ~ NULL,
              index = c("id", "t"),
              data = SRHS,
              k = 3,
              tol = 1e-8,
              start = 1,
              modBasic = 1,
              out_se = TRUE,
              seed = 123)

boot1 <- bootstrap(out1)

out2 <- lmest(responsesFormula = srhs ~ NULL,
              latentFormula = ~
                I(gender - 1) +
                I( 0 + (race == 2) + (race == 3)) +
                I(0 + (education == 4)) +
                I(0 + (education == 5)) +
                I(age - 50) + I((age-50)^2/100),
              index = c("id", "t"),
              data = SRHS,
              k = 2,
              paramLatent = "multilogit",
              start = 0)

boot2 <- bootstrap(out2)

# LM model for continuous responses without covariates

data(data_long_cont)

out3 <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 3,
                  modBasic = 1,
                  tol = 10^-5)

boot3 <- bootstrap(out3)

# LM model for continuous responses with covariates

out4 <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                  latentFormula = ~ X1 + X2,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 3,
                  output = TRUE)

boot4 <- bootstrap(out4)

## End(Not run)

```

bootstrap_lm_basic	<i>Parametric bootstrap for the basic LM model</i>
--------------------	--

Description

Function that performs bootstrap parametric resampling to compute standard errors for the parameter estimates.

The function is no longer maintained. Please look at [bootstrap](#) function.

Usage

```
bootstrap_lm_basic(piv, Pi, Psi, n, B = 100, start = 0, mod = 0, tol = 10^-6)
```

Arguments

piv	initial probability vector
Pi	probability transition matrices (k x k x TT)
Psi	matrix of conditional response probabilities (mb x k x r)
n	sample size
B	number of bootstrap samples
start	type of starting values (0 = deterministic, 1 = random)
mod	model on the transition probabilities (0 for time-heter., 1 for time-homog., from 2 to (TT-1) partial homog. of that order)
tol	tolerance level for convergence

Value

mPsi	average of bootstrap estimates of the conditional response probabilities
mpiv	average of bootstrap estimates of the initial probability vector
mPi	average of bootstrap estimates of the transition probability matrices
sePsi	standard errors for the conditional response probabilities
sepiv	standard errors for the initial probability vector
sePi	standard errors for the transition probability matrices

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
## Not run:
# Example of drug consumption data
# load data
data(data_drug)
data_drug <- as.matrix(data_drug)
S <- data_drug[,1:5]-1
yv <- data_drug[,6]
n <- sum(yv)
# fit of the Basic LM model
k <- 3
out1 <- est_lm_basic(S, yv, k, mod = 1, out_se = TRUE)
out2 <- bootstrap_lm_basic(out1$piv, out1$Pi, out1$Psi, n, mod = 1, B = 1000)

## End(Not run)
```

bootstrap_lm_basic_cont

Parametric bootstrap for the basic LM model for continuous outcomes

Description

Function that performs bootstrap parametric resampling to compute standard errors for the parameter estimates.

The function is no longer maintained. Please look at [bootstrap](#) function.

Usage

```
bootstrap_lm_basic_cont(piv, Pi, Mu, Si, n, B = 100, start = 0, mod = 0, tol = 10^-6)
```

Arguments

piv	initial probability vector
Pi	probability transition matrices ($k \times k \times TT$)
Mu	matrix of conditional means for the response variables ($r \times k$)
Si	var-cov matrix common to all states ($r \times r$)
n	sample size
B	number of bootstrap samples
start	type of starting values (0 = deterministic, 1 = random)
mod	model on the transition probabilities (0 for time-heter., 1 for time-homog., from 2 to $(TT-1)$ partial homog. of that order)
tol	tolerance level for convergence

Value

mMu	average of bootstrap estimates of the conditional means of the response variables
mSi	average of bootstrap estimates of the var-cov matrix
mpiv	average of bootstrap estimates of the initial probability vector
mPi	average of bootstrap estimates of the transition probability matrices
seMu	standard errors for the conditional means of the response variables
seSi	standard errors for the var-cov matrix
sepiv	standard errors for the initial probability vector
sePi	standard errors for the transition probability matrices

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
## Not run:
# Example based on multivariate longitudinal continuous data

data(data_long_cont)
res <- long2matrices(data_long_cont$id, X = cbind(data_long_cont$X1, data_long_cont$X2),
  Y = cbind(data_long_cont$Y1, data_long_cont$Y2, data_long_cont$Y3))
Y <- res$YY
n <- dim(Y)[1]

# fit of the Basic LM model for continuous outcomes
k <- 3
out1 <- est_lm_basic_cont(Y, k, mod = 1)
out2 <- bootstrap_lm_basic_cont(out1$piv, out1$Pi, out1$Mu, out1$Si, n, mod = 1, B = 1000)

## End(Not run)
```

bootstrap_lm_cov_latent

Parametric bootstrap for LM models with individual covariates in the latent model

Description

Function that performs bootstrap parametric resampling to compute standard errors for the parameter estimates.

The function is no longer maintained. Please look at [bootstrap](#) function.

Usage

```
bootstrap_lm_cov_latent(X1, X2, param = "multilogit", Psi, Be, Ga, B = 100,
  fort = TRUE)
```

Arguments

X1	matrix of covariates affecting the initial probabilities (n x nc1)
X2	array of covariates affecting the transition probabilities (n x TT-1 x nc2)
param	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
Psi	array of conditional response probabilities (mb x k x r)
Be	parameters affecting the logit for the initial probabilities
Ga	parameters affecting the logit for the transition probabilities
B	number of bootstrap samples
fort	to use fortran routine when possible (FALSE for not use fortran)

Value

mPsi	average of bootstrap estimates of the conditional response probabilities
mBe	average of bootstrap estimates of the parameters affecting the logit for the initial probabilities
mGa	average of bootstrap estimates of the parameters affecting the logit for the transition probabilities
sePsi	standard errors for the conditional response probabilities
seBe	standard errors for the parameters in Be
seGa	standard errors for the parameters in Ga

Author(s)

Francesco Bartolucci, Silvia Pandolfi - University of Perugia (IT)

Examples

```
## Not run:
# Example based on self-rated health status (SRHS) data
# load SRHS data
data(data_SRHS_long)
dataSRHS <- data_SRHS_long

TT <- 8
head(dataSRHS)
res <- long2matrices(dataSRHS$id, X = cbind(dataSRHS$gender-1,
  dataSRHS$race == 2 | dataSRHS$race == 3, dataSRHS$education == 4,
  dataSRHS$education == 5, dataSRHS$age-50, (dataSRHS$age-50)^2/100),
  Y = dataSRHS$srhs)
```

```

# matrix of responses (with ordered categories from 0 to 4)
S <- 5-res$YY

# matrix of covariates (for the first and the following occasions)
# columns are: gender,race,educational level (2 columns),age,age^2)
X1 <- res$XX[,1,]
X2 <- res$XX[,2:TT,]

# estimate the model
out1 <- est_lm_cov_latent(S, X1, X2, k = 2, output = TRUE, out_se = TRUE)

out2 <- bootstrap_lm_cov_latent(X1, X2, Psi = out1$Psi, Be = out1$Be, Ga = out1$Ga, B = 1000)

## End(Not run)

```

bootstrap_lm_cov_latent_cont

Parametric bootstrap for LM models for continuous outcomes with individual covariates in the latent model

Description

Function that performs bootstrap parametric resampling to compute standard errors for the parameter estimates.

The function is no longer maintained. Please look at [bootstrap](#) function.

Usage

```
bootstrap_lm_cov_latent_cont(X1, X2, param = "multilogit", Mu, Si, Be, Ga, B = 100)
```

Arguments

X1	matrix of covariates affecting the initial probabilities (n x nc1)
X2	array of covariates affecting the transition probabilities (n x TT-1 x nc2)
param	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
Mu	matrix of conditional means for the response variables (r x k)
Si	var-cov matrix common to all states (r x r)
Be	parameters affecting the logit for the initial probabilities
Ga	parameters affecting the logit for the transition probabilities
B	number of bootstrap samples

Value

mMu	average of bootstrap estimates of the conditional means for the response variables
mSi	average of bootstrap estimates of the var-cov matrix
mBe	average of bootstrap estimates of the parameters affecting the logit for the initial probabilities
mGa	average of bootstrap estimates of the parameters affecting the logit for the transition probabilities
seMu	standard errors for the conditional means
seSi	standard errors for the var-cov matrix
seBe	standard errors for the parameters in Be
seGa	standard errors for the parameters in Ga

Author(s)

Francesco Bartolucci, Silvia Pandolfi - University of Perugia (IT)

Examples

```
## Not run:
# Example based on multivariate longitudinal continuous data

data(data_long_cont)
TT <- 5
res <- long2matrices(data_long_cont$id, X = cbind(data_long_cont$X1, data_long_cont$X2),
                     Y = cbind(data_long_cont$Y1, data_long_cont$Y2, data_long_cont$Y3))
Y <- res$YY
X1 <- res$XX[,1,]
X2 <- res$XX[,2:TT,]

# estimate the model
est <- est_lm_cov_latent_cont(Y, X1, X2, k = 3, output = TRUE)
out <- bootstrap_lm_cov_latent_cont(X1, X2, Mu = est$Mu, Si = est$Si,
                                   Be = est$Be, Ga = est$Ga, B = 1000)

## End(Not run)
```

data_criminal_sim

Criminal dataset

Description

Simulated dataset about crimes committed by a cohort of subjects.

Usage

```
data(data_criminal_sim)
```

Format

A data frame with 60000 observations on the following 13 variables.

```
id  subject id
sex  gender of the subject
time occasion of observation
y1  crime of type 1 (violence against the person)
y2  crime of type 2 (sexual offences)
y3  crime of type 3 (burglary)
y4  crime of type 4 (robbery)
y5  crime of type 5 (theft and handling stolen goods)
y6  crime of type 6 (fraud and forgery)
y7  crime of type 7 (criminal damage)
y8  crime of type 8 (drug offences)
y9  crime of type 9 (motoring offences)
y10 crime of type 10 (other offences)
```

References

Bartolucci, F., Pennoni, F. and Francis, B. (2007), A latent Markov model for detecting patterns of criminal activity, *Journal of the Royal Statistical Society, series A*, **170**, pp. 115-132.

Examples

```
data(data_criminal_sim)
```

data_drug	<i>Dataset about marijuana consumption</i>
-----------	--

Description

Longitudinal dataset derived from the National Youth Survey about marijuana consumption measured by ordinal variables with 3 categories with increasing levels of consumption (1 "never in the past year", 2 "no more than once in a month in the past year", 3 "more than once a month in the past year").

Usage

```
data(data_drug)
```

Format

A data frame with 51 observations on the following 6 variables.

- V1 reported drug use at the 1st occasion
- V2 reported drug use at the 2nd occasion
- V3 reported drug use at the 3rd occasion
- V4 reported drug use at the 4th occasion
- V5 reported drug use at the 5th occasion
- V6 frequency of the response configuration

Source

Elliot, D. S., Huizinga, D. and Menard, S. (1989) *Multiple Problem Youth: Delinquency, Substance Use, and Mental Health Problems*. New York: Springer.

References

Bartolucci, F. (2006) Likelihood inference for a class of latent Markov models under linear hypotheses on the transition probabilities. *Journal of the Royal Statistical Society, series B*, **68**, 155-178.

Examples

```
data(data_drug)
```

data_employment_sim	<i>Employment dataset</i>
---------------------	---------------------------

Description

Simulated dataset related to a survey on the employment status of a cohort of graduates.

Usage

```
data(data_employment_sim)
```

Format

A data frame with 585 observations on the following variables:

- id subject id.
- time occasion of observation.
- emp 0 if unemployed, 1 if employed.
- area 1 if graduated in the South area, 2 if graduated in the North area.
- grade 1 if grade at graduation is low, 2 if it is medium, 3 if it is high.
- edu 1 if parents hold a university degree, 0 if not.

References

Pennoni, F., Pandolfi, S. and Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.

Examples

```
data(data_employment_sim)
```

data_heart_sim	<i>Health dataset</i>
----------------	-----------------------

Description

Simulated longitudinal dataset coming from a medical study to assess the health state progression of patients after a certain treatment.

Usage

```
data(data_heart_sim)
```

Format

A data frame referred to 125 units observed at 6 time occasions on the following variables:

```
id subject id
time occasion of observation
sap systolic arterial pressure in mmHg
dap diastolic arterial pressure in mmHg
hr heart rate in bpm
fluid fluid administration in ml/kg/h
gender 1 for male, 2 for female patients
age age in years
```

References

Pennoni, F., Pandolfi, S. and Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.

Examples

```
data(data_heart_sim)
```

data_long_cont	<i>Multivariate Longitudinal Continuous (Gaussian) Data</i>
----------------	---

Description

Simulated multivariate longitudinal continuous dataset assuming that there are 500 subjects in the study whose data are collected at 5 equally-spaced time points.

Usage

```
data(data_long_cont)
```

Format

A data frame with 2500 observations on the following 7 variables.

id subject id.

time occasion of observation.

Y1 a numeric vector for the first longitudinal response.

Y2 a numeric vector for the second longitudinal response.

Y3 a numeric vector for the third longitudinal response.

X1 a numeric vector for the first covariate.

X2 a numeric vector for the second covariate.

Examples

```
data(data_long_cont)
```

data_market_sim	<i>Marketing dataset</i>
-----------------	--------------------------

Description

Simulated dataset related to customers of four different brands along with the prices of each transaction.

Usage

```
data(data_market_sim)
```

Format

A data frame with 200 observations on the following variables:

id subject id.

time occasion of observation.

brand 0 if the customer has purchased the product from brand A, 1 if brand B, 2 if brand C, 3 if brand D.

price 0 if the price of the transaction is in the range [0.1, 10], 1 if it is in (10, 30], 2 if it is in (30, 60], 3 if it is in (60, 100], 4 if it is in (100, 500] (in thousands of Euros).

age age of the customer in years

income income declared by the customer at the time of the first purchase (in thousands of Euros).

References

Pennoni, F., Pandolfi and S. Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.

Examples

```
data(data_market_sim)
```

data_SRHS_long	<i>Self-reported health status dataset</i>
----------------	--

Description

Dataset about self-reported health status derived from the Health and Retirement Study conducted by the University of Michigan.

Usage

```
data(data_SRHS_long)
```

Format

A data frame with 56592 observations on the following 6 variables.

t occasion of observation

id subject id

gender sex of the subject coded as 1 for "male", 2 for "female"

race race coded as 1 for "white", 2 for "black", 3 for "others"

education educational level coded as 1 for "high school", 2 for "general educational diploma", 3 for "high school graduate", 4 for "some college", 5 for "college and above"

age age at the different time occasions

srhs self-reported health status at the different time occasions coded as 1 for "excellent", 2 for "very good", 3 for "good", 4 for "fair", 5 for "poor"

References

Bartolucci, F., Bacci, S. and Pennoni, F. (2014) Longitudinal analysis of the self-reported health status by mixture latent autoregressive models, *Journal of the Royal Statistical Society - series C*, **63**, pp. 267-288

Examples

```
data(data_SRHS_long)
```

decoding

Perform local and global decoding

Description

Function that performs local and global decoding (Viterbi) from the output of `est_lm_basic`, `est_lm_cov_latent`, `est_lm_cov_manifest`, and `est_lm_mixed`.

The function is no longer maintained. Please look at [lmestDecoding](#) function

Usage

```
decoding(est, Y, X1 = NULL, X2 = NULL, fort = TRUE)
```

Arguments

<code>est</code>	output from <code>est_lm_basic</code> , <code>est_lm_cov_latent</code> , <code>est_lm_cov_manifest</code> , or <code>est_lm_mixed</code>
<code>Y</code>	single vector or matrix of responses
<code>X1</code>	matrix of covariates on the initial probabilities (<code>est_lm_cov_latent</code>) or on the responses (<code>est_lm_cov_manifest</code>)
<code>X2</code>	array of covariates on the transition probabilities
<code>fort</code>	to use Fortran routines

Value

<code>U1</code>	matrix of local decoded states corresponding to each row of <code>Y</code>
<code>Ug</code>	matrix of global decoded states corresponding to each row of <code>Y</code>

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

References

- Viterbi A. (1967) Error Bounds for Convolutional Codes and an Asymptotically Optimum Decoding Algorithm. *IEEE Transactions on Information Theory*, **13**, 260-269.
- Juan B., Rabiner L. (1991) Hidden Markov Models for Speech Recognition. *Technometrics*, **33**, 251-272.

Examples

```
## Not run:
# example for the output from est_lm_basic

data(data_drug)
data_drug <- as.matrix(data_drug)
S <- data_drug[,1:5]-1
yv <- data_drug[,6]
n <- sum(yv)

# fit the Basic LM model

k <- 3
est <- est_lm_basic(S, yv, k, mod = 1)

# decoding for a single sequence

out1 <- decoding(est, S[1,])

# decoding for all sequences

out2 <- decoding(est, S)

# example for the output from est_lm_cov_latent with difflogit parametrization
data(data_SRHS_long)
dataSRHS <- data_SRHS_long[1:1600,]

TT <- 8
head(dataSRHS)
res <- long2matrices(dataSRHS$id, X = cbind(dataSRHS$gender-1,
dataSRHS$race == 2 | dataSRHS$race == 3, dataSRHS$education == 4,
dataSRHS$education == 5, dataSRHS$age-50, (dataSRHS$age-50)^2/100),
Y= dataSRHS$srhs)

# matrix of responses (with ordered categories from 0 to 4)
S <- 5-res$YY

# matrix of covariates (for the first and the following occasions)
# columns are: gender,race,educational level (2 columns),age,age^2
X1 <- res$XX[,1,]
X2 <- res$XX[,2:TT,]

# estimate the model
```

```

est <- est_lm_cov_latent(S, X1, X2, k = 2, output = TRUE, param = "difflogit")
# decoding for a single sequence
out1 <- decoding(est, S[1,,], X1[1,,], X2[1,,])
# decoding for all sequences
out2 <- decoding(est, S, X1, X2)

## End(Not run)

```

design_matrices	<i>Build design matrices for mc_multinom</i>
-----------------	--

Description

Function that builds the contrast and design matrices required by `mc_multinom` to parameterize, through multinomial logits, the initial and the transition probabilities of a Markov chain model.

Usage

```
design_matrices(k, nc, baseline, model_int, model_cov)
```

Arguments

k	Number of response categories (or observed states) in the Markov chain, coded as 1, ..., k. Note that the structures "dist1", "dist2", "dist3", "two" and "diff" (see model_int) rely on the distance or on the direction between categories, and are therefore meaningful only when the categories are ordered; the remaining structures do not require any ordering
nc	Number of covariates affecting the transition probabilities, excluding the intercept. Set nc = 0 when no transition covariates are included
baseline	Character string specifying the reference category in the multinomial logit parameterization. With "initial", category (1) is the reference category for both initial and transition probabilities. With "central", category (1) remains the reference category for the initial probabilities, whereas the current state is the reference category for each row of the transition matrix
model_int	Character string specifying the constraint structure for the intercepts of the transition logits. Possible values are: "all" unconstrained transition-specific intercepts, one for each of the $k(k-1)$ transitions "const" one common intercept for all transitions "dist1" one parameter for each signed distance $v - u$ between the destination category v and the origin category u ($2(k-1)$ parameters) "dist2" one parameter for each absolute distance $ v - u $, shared by the two directions ($k-1$ parameters) "dist3" as "dist2", but the parameter enters with a positive sign for upward transitions and with a negative sign for downward ones ($k-1$ parameters) "two" separate parameters for upward and downward transitions

	"symm" one parameter for each pair of categories, shared by the two directions ($k(k - 1)/2$ parameters)
	"rsymm" as "symm", but the parameter enters with opposite signs in the two directions
	"diff" effects expressed as differences between destination- and origin-specific parameters, with the parameter of the first category set to zero ($k - 1$ parameters)
model_cov	Character string specifying the constraint structure for the regression coefficients of the transition covariates. The admissible values and their interpretation are the same as for model_int. This argument is used only when nc > 0

Value

G	Contrast matrix used to parameterize the initial probabilities in the mc_multinom function
Z	Design matrix mapping the reduced parameter vector to the transition-logit parameters under the selected intercept and covariate constraints
GG	Array of contrast matrices used to parameterize the transition probabilities for each origin state
Z1	Design matrix defining the constraint structure for the intercepts of the transition logits
Z2	Design matrix defining the constraint structure for the covariate effects on the transition logits. This component is returned only when nc > 0

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), Luca Brusa and Fulvia Pennoni, University of Milano-Bicocca (IT)

References

Bartolucci, F., Pandolfi, S., and Pennoni, F. (2026). Parsimonious parametrizations of transition matrices of Markov chain and hidden Markov models, *Annals of Operations Research*, 363, 233–266.

draw	<i>Draw simulated sample from a Generalized Latent Markov Model</i>
------	---

Description

Draw a sample for LMest objects of classes: LMbasic, LMbasiccont, LMlatent, LMlatentcont, and LMmixed

Usage

```
## S3 method for class 'LMbasic'
draw(est, n = NULL, TT = NULL, format = c("long", "matrices"), seed = NULL, ...)
## S3 method for class 'LMlatent'
draw(est, n = NULL, TT = NULL, data, index, format = c("long", "matrices"),
      fort = TRUE, seed = NULL, ...)
## S3 method for class 'LMbasiccont'
draw(est, n = NULL, TT = NULL, format = c("long", "matrices"), seed = NULL, ...)
## S3 method for class 'LMlatentcont'
draw(est, n = NULL, TT = NULL, data, index, format = c("long", "matrices"),
      fort = TRUE, seed = NULL, ...)
## S3 method for class 'LMmixed'
draw(est, n = NULL, TT = NULL, format = c("long", "matrices"), seed = NULL, ...)
```

Arguments

est	object of class LMbasic (LMbasic-class), LMlatent (LMlatent-class), class LMbasiccont (LMbasiccont-class), LMlatentcont (LMlatentcont-class), or LMmixed (LMmixed-class)
n	sample size
format	character string indicating the format of final responses matrix
seed	an integer value with the random number generator state
data	a data frame in long format, with rows corresponding to observations and columns corresponding to covariates, a column corresponding to time occasions and a column containing the unit identifier when est is of class LMlatent or LMlatentcont
index	a character vector with two elements indicating the name of the "id" column as first element and the "time" column as second element when est is of class LMlatent or LMlatentcont
fort	to use fortran routine when possible (FALSE for not use fortran) when est is of class LMlatent or LMlatentcont
TT	number of time occasions when est is of class LMmixed
...	further arguments

Value

Y	matrix of response configurations unit by unit when est is of class LMbasic or LMmixed; array of continuous outcomes (n x TT x r) when est is of class LMbasiccont or LMlatentcont
S	matrix of distinct response configurations when est is of class LMbasic or LMmixed
yv	corresponding vector of frequencies when est is of class LMbasic or LMmixed
piv	vector of initial probabilities of the latent Markov chain when est is of class LMbasic
Pi	set of transition probabilities matrices (k x k x TT) when est is of class LMbasic
Psi	array of conditional response probabilities (mb x k x r) when est is of class LMbasic

n	sample size
TT	number of time occasions
est	object of class LMbasic, LMlatent, LMbasiccont, LMlatentcont, or LMmixed
U	matrix containing the sequence of latent states (n x TT) when est is of class LMlatent or LMlatentcont
Be	parameters affecting the logit for the initial probabilities when est is of class LMlatent or LMlatentcont
Ga	parameters affecting the logit for the transition probabilities when est is of class LMlatent or LMlatentcont
data	a data frame in long format, with rows corresponding to observations and columns corresponding to variables, a column corresponding to time occasions and a column containing the unit identifier when est is of class LMlatent or LMlatentcont
Mu	array of conditional means for the response variables (r x k) when est is of class LMlatentcont
Si	var-cov matrix common to all states (r x r) when est is of class LMlatentcont
latentFormula	a symbolic description of the model to be fitted. A detailed description is given in lmestCont

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni

Examples

```
## Not run:
# draw a sample for 1000 units and only one response variable when est is of class LMbasic
n <- 1000
TT <- 6
k <- 2
r <- 1 #number of response variables
mb <- 3 #maximum number of response categories

piv <- c(0.7,0.3)
Pi <- matrix(c(0.9,0.1,0.1,0.9), k, k)
Pi <- array(Pi, c(k, k, TT))
Pi[, ,1] <- 0
Psi <- matrix(c(0.7,0.2,0.1,0.5,0.4,0.1), mb, k)
Psi <- array(Psi, c(mb, k, r))
est = list(piv=piv, Pi=Pi, Psi=Psi, n=n, TT=TT)
class(est) = "LMbasic"

out <- draw(est)

data("data_SRHS_long")
SRHS <- data_SRHS_long[1:2400,]

SRHS$srhs <- 5 - SRHS$srhs
```

```

est <- lmest(responsesFormula = srhs ~ NULL,
             index = c("id","t"),
             data = SRHS,
             k = 3)

out1 <- draw(est = est, format = "matrices", seed = 4321, n = 100)

# draw a sample for 7074 units and only one response variable when est is of class LMlatent
data(data_SRHS_long)

data_SRHS_long$srhs <- 5 - data_SRHS_long$srhs
n <- length(unique(data_SRHS_long$id))
TT <- max(data_SRHS_long$t)

est <- lmest(responsesFormula = srhs ~ NULL,
             latentFormula = ~
             I(gender - 1) +
             I( 0 + (race == 2) + (race == 3)) +
             I(0 + (education == 4)) +
             I(0 + (education == 5)) +
             I(age - 50) + I((age-50)^2/100),
             index = c("id","t"),
             data = data_SRHS_long,
             k = 2,
             paramLatent = "multilogit",
             start = 0)

out <- draw(est = est, data = data_SRHS_long, index = c("id","t"),
            format = "matrices",seed = 4321)

est1 = list(Psi = est$Psi, Be = est$Be, Ga = est$Ga,
            paramLatent = "multilogit",n=n,TT=TT)

attributes(est1)$latentFormula = ~
             I(gender - 1) +
             I( 0 + (race == 2) + (race == 3)) +
             I(0 + (education == 4)) +
             I(0 + (education == 5)) +
             I(age - 50) + I((age-50)^2/100)
class(est1) = "LMlatent"

out1 <- draw(est = est1, data = data_SRHS_long, index = c("id","t"),
            format = "matrices",
            seed = 4321)

# draw a sample for 1000 units and 3 response variable when est is of class LMbasiccont
n <- 1000
TT <- 5
k <- 2
r <- 3 #number of response variables

piv <- c(0.7,0.3)

```

```

Pi <- matrix(c(0.9,0.1,0.1,0.9), k, k)
Pi <- array(Pi, c(k, k, TT))
Pi[, ,1] <- 0
Mu <- matrix(c(-2,-2,0,0,2,2), r, k)
Si <- diag(r)
est = list(piv=piv,Pi=Pi,Mu=Mu,Si=Si,n=n,TT=TT)
class(est) = "LMbasiccont"

out <- draw(est)

data(data_long_cont)

est <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                 index = c("id", "time"),
                 data = data_long_cont,
                 k = 3,
                 modBasic = 1,
                 tol = 10^-5)

out2 <- draw(est = est, n = 100, format = "long", seed = 4321)

# draw a sample for 1000 units and 3 response variable when est is of class LMlatentcont
data(data_long_cont)

est <- lmestCont(responsesFormula = Y1 + Y2 + Y3~ NULL,
                 latentFormula = ~ X1 + X2,
                 index = c("id", "time"),
                 data = data_long_cont,
                 k = 3)
out <- draw(est = est, data = data_long_cont, index = c("id", "time"), format = "matrices",
           seed = 4321)

est1 <- list(Mu = est$Mu,Si = est$Si,Be = est$Be,Ga = est$Ga,paramLatent="multilogit",n=est$n,
            TT=est$TT)
attributes(est1)$latentFormula = ~ X1 + X2
class(est1) = "LMlatentcont"
out1 <- draw(est = est1, data = data_long_cont,
            index = c("id", "time"),
            fort=TRUE, seed = 4321, format = "matrices")

## End(Not run)

# draw a sample for 1000 units and only one response variable and 5 time occasions
# when est is of class LMmixed
k1 <- 2
k2 <- 3
la <- rep(1/k1, k1)
Piv <- matrix(1/k2, k2, k1)
Pi <- array(0, c(k2, k2, k1))
Pi[, ,1] <- diag(k2)
Pi[, ,2] <- 1/k2
Psi <- cbind(c(0.6,0.3,0.1), c(0.1,0.3,0.6), c(0.3,0.6,0.1))
est <- list(la=la, Piv=Piv, Pi=Pi, Psi=Psi, n=1000,TT=5)

```

```

class(est) = "LMmixed"

out <- draw(est = est)

## Not run:
# Example based on criminal data when est if of class LMmixed
data(data_criminal_sim)
data_criminal_sim = data.frame(data_criminal_sim)

# Estimate mixed LM model for females
responsesFormula <- lmestFormula(data = data_criminal_sim,
                                response = "y")$responsesFormula
est <- lmestMixed(responsesFormula = responsesFormula,
                 index = c("id", "time"),
                 k1 = 2,
                 k2 = 2,
                 data = data_criminal_sim[data_criminal_sim$sex == 2,])

out <- draw(est = est, n = 100, TT = 6, seed = 4321)

## End(Not run)

```

draw_lm_basic

Draw samples from the basic LM model

Description

Function that draws samples from the basic LM model with specific parameters.

The function is no longer maintained. Please look at [draw.LMbasic](#) function.

Usage

```
draw_lm_basic(piv, Pi, Psi, n)
```

Arguments

piv	vector of initial probabilities of the latent Markov chain
Pi	set of transition probabilities matrices ($k \times k \times TT$)
Psi	array of conditional response probabilities ($mb \times k \times r$)
n	sample size

Value

Y	matrix of response configurations unit by unit
S	matrix of distinct response configurations
yv	corresponding vector of frequencies

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
## Not run:
# draw a sample for 1000 units and only one response variable
n <- 1000
TT <- 6
k <- 2
r <- 1 #number of response variables
mb <- 3 #maximum number of response categories

piv <- c(0.7, 0.3)
Pi <- matrix(c(0.9,0.1,0.1,0.9), k, k)
Pi <- array(Pi, c(k, k, TT))
Pi[, ,1] <- 0
Psi <- matrix(c(0.7,0.2,0.1,0.5,0.4,0.1), mb, k)
Psi <- array(Psi, c(mb, k, r))
out <- draw_lm_basic(piv, Pi, Psi, n = 1000)

## End(Not run)
```

draw_lm_basic_cont

Draw samples from the basic LM model for continuous outcomes

Description

Function that draws samples from the basic LM model for continuous outcomes with specific parameters.

The function is no longer maintained. Please look at [draw.LMbasiccont](#) function.

Usage

```
draw_lm_basic_cont(piv, Pi, Mu, Si, n)
```

Arguments

piv	vector of initial probabilities of the latent Markov chain
Pi	set of transition probabilities matrices ($k \times k \times TT$)
Mu	matrix of conditional means for the response variables ($r \times k$)
Si	var-cov matrix common to all states ($r \times r$)
n	sample size

Value

Y	array of continuous outcomes ($n \times TT \times r$)
---	---

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
## Not run:

# draw a sample for 1000 units and 3 response variable
n <- 1000
TT <- 5
k <- 2
r <- 3 #number of response variables

piv <- c(0.7,0.3)
Pi <- matrix(c(0.9,0.1,0.1,0.9), k, k)
Pi <- array(Pi, c(k, k, TT))
Pi[, ,1] <- 0
Mu <- matrix(c(-2,-2,0,0,2,2), r, k)
Si <- diag(r)
out <- draw_lm_basic_cont(piv, Pi, Mu, Si, n)

## End(Not run)
```

draw_lm_cov_latent	<i>Draw samples from LM model with covariaates in the latent model</i>
--------------------	--

Description

Function that draws samples from the LM model with individual covariates with specific parameters.

The function is no longer maintained. Please look at [draw.LMlatent](#) function.

Usage

```
draw_lm_cov_latent(X1, X2, param = "multilogit", Psi, Be, Ga, fort = TRUE)
```

Arguments

X1	desing matrix for the covariates on the initial probabilities (n x nc1)
X2	desing matrix for the covariates on the transition probabilities (n x TT-1 x nc2)
param	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
Psi	array of conditional response probabilities (mb x k x r)
Be	parameters affecting the logit for the initial probabilities
Ga	parametes affecting the logit for the transition probabilities
fort	to use fortran routine when possible (FALSE for not use fortran)

Value

Y matrix of response configurations unit by unit ($n \times TT \times r$)

U matrix containing the sequence of latent states ($n \times TT$)

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
## Not run:

# draw a sample for 1000 units, 10 response variable and 2 covariates
n <- 1000
TT <- 5
k <- 2
nc <- 2 #number of covariates
r <- 10 #number of response variables
mb <- 2 #maximum number of response categories
fort <- TRUE

Psi <- matrix(c(0.9,0.1,0.1,0.9), mb, k)
Psi <- array(Psi, c(mb, k, r))
Ga <- matrix(c(-log(0.9/0.1),0.5,1), (nc+1)*(k-1), k)
Be <- array(c(0,0.5,1), (nc+1)*(k-1))
#Simulate covariates
X1 <- matrix(0, n, nc)
for(j in 1:nc) X1[,j] <- rnorm(n)
X2 <- array(0,c(n, TT-1, nc))
for (t in 1:(TT-1)) for(j in 1:nc){
  if(t==1){
    X2[,t,j] <- 0.5*X1[,j] + rnorm(n)
  }else{
    X2[,t,j] <- 0.5 *X2[,t-1,j] + rnorm(n)
  }
}

out <- draw_lm_cov_latent(X1, X2, Psi = Psi, Be = Be, Ga = Ga, fort = fort)

## End(Not run)
```

draw_lm_cov_latent_cont

Draw samples from LM model for continuous outcomes with covariates in the latent model

Description

Function that draws samples from the LM model for continuous outcomes with individual covariates with specific parameters.

The function is no longer maintained. Please look at [draw.LMlatentcont](#) function.

Usage

```
draw_lm_cov_latent_cont(X1, X2, param = "multilogit", Mu, Si, Be, Ga, fort = TRUE)
```

Arguments

X1	designing matrix for the covariates on the initial probabilities (n x nc1)
X2	designing matrix for the covariates on the transition probabilities (n x TT-1 x nc2)
param	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
Mu	array of conditional means for the response variables (r x k)
Si	var-cov matrix common to all states (r x r)
Be	parameters affecting the logit for the initial probabilities
Ga	parameters affecting the logit for the transition probabilities
fort	to use fortran routine when possible (FALSE for not use fortran)

Value

Y	array of continuous outcomes (n x TT x r)
U	matrix containing the sequence of latent states (n x TT)

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
## Not run:
# draw a sample for 1000 units, 10 response variable and 2 covariates
n <- 1000
TT <- 5
k <- 2
nc <- 2 #number of covariates
r <- 3 #number of response variables
fort <- TRUE

Mu <- matrix(c(-2,-2,0,0,2,2), r, k)
Si <- diag(r)
Ga <- matrix(c(-log(0.9/0.1),0.5,1), (nc+1)*(k-1), k)
Be <- array(c(0,0.5,1), (nc+1)*(k-1))
```

```

#Simulate covariates
X1 <- matrix(0, n, nc)
for(j in 1:nc) X1[,j] <- rnorm(n)
X2 <- array(0, c(n,TT-1,nc))
for (t in 1:(TT-1)) for(j in 1:nc){
  if(t==1){
    X2[,t,j] <- 0.5*X1[,j] + rnorm(n)
  }else{
    X2[,t,j] <- 0.5*X2[,t-1,j] + rnorm(n)
  }
}

out <- draw_lm_cov_latent_cont(X1, X2, param = "multilogit", Mu, Si, Be, Ga, fort = fort)

## End(Not run)

```

draw_lm_mixed	<i>Draws samples from the mixed LM model</i>
---------------	--

Description

Function that draws samples from the mixed LM model with specific parameters.

The function is no longer maintained. Please look at [draw.LMmixed](#) function.

Usage

```
draw_lm_mixed(la, Piv, Pi, Psi, n, TT)
```

Arguments

la	vector of mass probabilities for the first latent variable
Piv	matrix of initial probabilities of the latent Markov chain ($k_2 \times k_1$)
Pi	set of transition matrices ($k_2 \times k_2 \times k_1$)
Psi	array of conditional response probabilities ($m_b \times k_2 \times r$)
n	sample size
TT	number of time occasions

Value

Y	matrix of response configurations unit by unit
S	matrix of distinct response configurations
yv	corresponding vector of frequencies

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
## Not run:
# draw a sample for 1000 units and only one response variable and 5 time occasions
k1 <- 2
k2 <- 3
la <- rep(1/k1,k1)
Piv <- matrix(1/k2,k2,k1)
Pi <- array(0,c(k2,k2,k1))
Pi[, ,1] <- diag(k2)
Pi[, ,2] <- 1/k2
Psi <- cbind(c(0.6,0.3,0.1),c(0.1,0.3,0.6),c(0.3,0.6,0.1))
out <- draw_lm_mixed(la,Piv,Pi,Psi,n=1000,TT=5)

## End(Not run)
```

est_lm_basic

Estimate basic LM model

Description

Main function for estimating the basic LM model.

The function is no longer maintained. Please look at [lmest](#) function.

Usage

```
est_lm_basic(S, yv, k, start = 0, mod = 0, tol = 10^-8, maxit = 1000,
             out_se = FALSE, piv = NULL, Pi = NULL, Psi = NULL)
```

Arguments

S	array of available configurations (n x TT x r) with categories starting from 0 (use NA for missing responses)
yv	vector of frequencies of the available configurations
k	number of latent states
start	type of starting values (0 = deterministic, 1 = random, 2 = initial values in input)
mod	model on the transition probabilities (0 for time-heter., 1 for time-homog., from 2 to (TT-1) partial homog. of that order)
tol	tolerance level for convergence
maxit	maximum number of iterations of the algorithm
out_se	to compute the information matrix and standard errors
piv	initial value of the initial probability vector (if start=2)
Pi	initial value of the transition probability matrices (k x k x TT) (if start=2)
Psi	initial value of the conditional response probabilities (mb x k x r) (if start=2)

Value

lk	maximum log-likelihood
piv	estimate of initial probability vector
Pi	estimate of transition probability matrices
Psi	estimate of conditional response probabilities
np	number of free parameters
aic	value of AIC for model selection
bic	value of BIC for model selection
lkv	log-likelihood trace at every step
V	array containing the posterior distribution of the latent states for each response configuration and time occasion
sepiv	standard errors for the initial probabilities
sePi	standard errors for the transition probabilities
sePsi	standard errors for the conditional response probabilities
call	command used to call the function

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

References

Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
## Not run:
# Example of drug consumption data

# load data
data(data_drug)
data_drug <- as.matrix(data_drug)
S <- data_drug[,1:5]-1
yv <- data_drug[,6]

# fit of the Basic LM model
k <- 3
out <- est_lm_basic(S, yv, k, mod = 1)
summary(out)

# Example based on criminal data

# load criminal data
data(data_criminal_sim)
out <- long2wide(data_criminal_sim, "id" , "time" , "sex",
```

```

c("y1","y2","y3","y4","y5","y6","y7","y8","y9","y10"),aggr = T, full = 999)
XX <- out$XX
YY <- out$YY
freq <- out$freq

# fit basic LM model with increasing number of states to select the most suitable
Res0 <- vector("list", 7)
for(k in 1:7){
  Res0[[k]] <- est_lm_basic(YY, freq, k, mod = 1, tol = 10^-4)
  save(list <- ls(), file = "example_criminal_temp.RData")
}
out1 <- Res0[[6]]

## End(Not run)

```

est_lm_basic_cont

Estimate basic LM model for continuous outcomes

Description

Main function for estimating the basic LM model for continuous outcomes.

The function is no longer maintained. Please look at [lmestCont](#) function.

Usage

```

est_lm_basic_cont(Y, k, start = 0, mod = 0, tol = 10^-8, maxit = 1000,
  out_se = FALSE, piv = NULL, Pi = NULL, Mu = NULL, Si = NULL)

```

Arguments

Y	array of continuous outcomes (n x TT x r)
k	number of latent states
start	type of starting values (0 = deterministic, 1 = random, 2 = initial values in input)
mod	model on the transition probabilities (0 for time-heter., 1 for time-homog., from 2 to (TT-1) partial homog. of that order)
tol	tolerance level for convergence
maxit	maximum number of iterations of the algorithm
out_se	to compute the information matrix and standard errors
piv	initial value of the initial probability vector (if start=2)
Pi	initial value of the transition probability matrices (k x k x TT) (if start=2)
Mu	initial value of the conditional means (r x k) (if start=2)
Si	initial value of the var-cov matrix common to all states (r x r) (if start=2)

Value

lk	maximum log-likelihood
piv	estimate of initial probability vector
Pi	estimate of transition probability matrices
Mu	estimate of conditional means of the response variables
Si	estimate of var-cov matrix common to all states
np	number of free parameters
aic	value of AIC for model selection
bic	value of BIC for model selection
lkv	log-likelihood trace at every step
V	array containing the posterior distribution of the latent states for each units and time occasion
call	command used to call the function

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

References

Penloni, F., Pandolfi, S. Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.

Bartolucci, F., Farcomeni, A. and Penloni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC, Boca Raton.

Examples

```
## Not run:
# Example based on multivariate longitudinal continuous data

data(data_long_cont)
res <- long2matrices(data_long_cont$id, X=cbind(data_long_cont$X1, data_long_cont$X2),
  Y=cbind(data_long_cont$Y1, data_long_cont$Y2, data_long_cont$Y3))
Y <- res$YY

# fit of the Basic LM model for continuous outcomes
k <- 3
out <- est_lm_basic_cont(Y, k, mod = 1, tol = 10^-5)
summary(out)

## End(Not run)
```

est_LM_cat_multinom *Estimation of Constrained Hidden Markov Models*

Description

Function that estimates a hidden Markov model to a univariate categorical longitudinal response. The observed response is generated by an unobserved first-order Markov chain with k latent states. Conditional on the latent state, responses are independent over time. Covariates may affect both the initial latent-state probabilities and the transition probabilities, and linear equality constraints may be imposed separately on transition intercepts and covariate effects.

Usage

```
est_LM_cat_multinom(resp_name, formula, k, data, reltol = 10^-10,
  rand.start = FALSE,
  nstart = 1, baseline = c("initial", "central"),
  model_int = c("all", "const", "dist1", "dist2",
    "dist3", "two", "symm", "rsymm", "diff"),
  model_cov = c("all", "const", "dist1", "dist2", "dist3",
    "two", "symm", "rsymm", "diff"),
  formula_init = NULL,
  par.init = list(la = NULL, psi = NULL, Pr = NULL),
  output = FALSE, fort = TRUE)
```

Arguments

resp_name	Character string giving the name of the observed response variable in data. The response must be numeric and coded with consecutive integer categories 1, ..., c , where c is the number of response categories, with no missing categories.
formula	A one-sided formula specifying the covariates in the transition model, for example <code>~ gender + race + education + age_c</code> . An intercept should be included. If <code>formula_init</code> is NULL, the same covariates are used for the initial latent-state probabilities.
k	Positive integer giving the number of latent states. A one-state model is allowed; in that case only the response probabilities and fit criteria are estimated, and the arguments <code>formula</code> , <code>formula_init</code> , <code>baseline</code> , <code>model_int</code> and <code>model_cov</code> have no effect.
data	Data frame in long format. The first column is used as the subject identifier and the second as the measurement occasion, irrespective of their names. Subject identifiers must be consecutive integers, records must be ordered by subject and occasion, and occasions for each subject must be consecutive and start at 1. Individual trajectories may have different lengths. Rows with missing values in the response or model variables should be removed before fitting.

reltol	Positive numeric value giving the relative log-likelihood tolerance used to stop the EM algorithm. Iteration stops when the relative increment in log-likelihood is no greater than reltol.
rand.start	Logical value controlling initialization when nstart = 1. If FALSE, the initial latent allocation is obtained by k-means clustering of the response. If TRUE, a random latent allocation is used. Components supplied in par.init override the corresponding internally generated starting values.
nstart	Positive integer giving the number of fits from different starting values. If greater than 1, the first fit uses the k-means initialization and the remaining fits use random initial allocations; the fit with the largest log-likelihood is returned.
baseline	Character string specifying the reference category in the multinomial logit parameterization for the transition probabilities. With "initial", the transition towards the first state is used as the reference category for each row of the transition matrix. With "central", the self-transition is used as the reference category for each row of the transition matrix.
model_int	Character string specifying the equality-constraint structure for the transition-logit intercepts. Available choices are "all", "const", "dist1", "dist2", "dist3", "two", "symm", "rsymm", and "diff". See Details and design_matrices .
model_cov	Character string specifying the equality-constraint structure for the transition-logit regression coefficients. The available choices are the same as for model_int. See Details and design_matrices .
formula_init	Optional one-sided formula specifying the covariates for the initial latent-state probabilities. Only measurements at occasion 1 are used. If NULL, formula is also used for this submodel. Use ~ 1 for an intercept-only initial-probability model.
par.init	Named list of optional starting values. Component 1a contains the coefficients for the initial-probability logits; psi contains the reduced parameter vector for the constrained transition logits; and Pr is a k by c matrix of conditional response probabilities. Any component may be left NULL to use an internally generated starting value.
output	Logical value. If TRUE, the fitted subject-specific initial probabilities Piv and transition probabilities PI are returned in addition to the main estimation results.
fort	Logical value selecting the numerical implementation. If TRUE, the compiled Fortran routines are used and must be available and loaded. If FALSE, the corresponding R routines are used.

Details

Let U denote the latent state for subject i at occasion t . The measurement model is $P(Y = y \mid U = u)$, represented by the returned matrix Pr. The arguments model_int and model_cov apply the same family of constraint structures to different parameter blocks: model_int acts on the transition intercepts, whereas model_cov acts componentwise on the transition covariate coefficients. The two structures can be selected independently. With baseline = "central", let a_{uv} denote a transition parameter from origin state u to destination state v , with $v \neq u$. The available structures are:

"all" No equality constraints: every transition has its own parameter.

- "const" A common parameter is used for all off-diagonal transitions. For `model_cov`, each covariate therefore has one common effect across all transitions.
- "dist1" Parameters are grouped by signed displacement $v - u$. Transitions with the same direction and the same size of movement share a parameter.
- "dist2" Parameters are grouped by absolute displacement $|v - u|$; movements of the same size share a parameter in both directions.
- "dist3" Parameters depend on $|v - u|$, with opposite signs for upward and downward movements of the same size.
- "two" Two parameters are used: one for transitions with $v > u$ and one for transitions with $v < u$, irrespective of movement size.
- "symm" Opposite transitions share a parameter, so that $a_{uv} = a_{vu}$.
- "rsymm" Opposite transitions have parameters with reversed signs, so that $a_{uv} = -a_{vu}$.
- "diff" Transition parameters are differences between destination- and origin-state parameters, $a_{uv} = a_v - a_u$, with the state-1 parameter fixed at zero for identifiability.

The distance-based structures "dist1", "dist2", "dist3", and "two" are intended for substantively ordered latent states. In particular, `model_cov = "all"` is the unconstrained transition-covariate model, `model_cov = "dist1"` pools effects by signed displacement, and `model_cov = "const"` imposes one effect per covariate across all transitions. The argument `model_int` operates analogously on the transition intercepts.

When `nstart > 1`, the returned object is the solution with the largest log-likelihood and component `lkv` records the log-likelihood obtained in each fit.

Value

An object of class "LM_cat_multinom" containing:

- `Pr` A k by c matrix of estimated conditional response probabilities, with latent states in rows and observed categories in columns.
- `lk` The maximized observed-data log-likelihood.
- `np` The number of free model parameters.
- `aic` The Akaike information criterion.
- `bic` The Bayesian information criterion, using the number of subjects as the sample size.
- `call` The matched call used to fit the model.

For $k > 1$, the object also contains:

- `1a` Estimated regression coefficients for the initial latent-state probabilities.
- `psi` Estimated reduced parameter vector for the constrained transition logits.
- `eta` Expanded transition-logit parameter vector obtained by applying the design matrix constraints to `psi`.
- `W` Array of posterior latent-state probabilities produced by the final E-step, with dimensions n by k by TT , where n is the number of subjects.
- `CL` Matrix of modal posterior latent-state classifications by subject and occasion, with dimensions n by TT .

If output = TRUE and $k > 1$, it additionally contains:

Piv Matrix of subject-specific fitted initial probabilities, with dimensions n by k .

PI Array of subject- and occasion-specific fitted transition probabilities, with dimensions k by k by n by TT , where TT is the maximum number of occasions.

If $nstart > 1$, component **lkv** contains the log-likelihood from each attempted start.

Author(s)

Francesco Bartolucci and Silvia Pandolfi, University of Perugia (Italy); Luca Brusa and Fulvia Pennoni, University of Milano-Bicocca (Italy).

References

Bartolucci, F., Pandolfi, S., and Pennoni, F. (2026). Parsimonious parametrizations of transition matrices of Markov chain and hidden Markov models. *Annals of Operations Research*, **363**, 233–266.

See Also

[design_matrices](#)

Examples

```
## Not run:

# Load and prepare data

data("data_SRHS_long")
srhs <- data_SRHS_long[,c(2,1,3:7)]

# 1 = poor, ..., 5 = excellent
srhs$srhs1 <- 6L - as.integer(srhs$srhs)
srhs$gender <- factor(srhs$gender)
srhs$race <- factor(srhs$race)
srhs$education <- factor(srhs$education)
srhs$age_c <- srhs$age - mean(srhs$age)
srhs$id <- as.integer(factor(srhs$id))
srhs <- srhs[order(srhs$id, srhs$t), ]

# Reduce the sample size for fast example
set.seed(123)

all_ids <- unique(srhs$id)
n_example <- min(1000L, length(all_ids))
example_ids <- sample(all_ids, size = n_example, replace = FALSE)
srhs_example <- srhs[srhs$id %in% example_ids, , drop = FALSE]

# Consecutive identifiers required by the estimation function
srhs_example$id <- match(srhs_example$id, example_ids)
srhs_example <- srhs_example[order(srhs_example$id, srhs_example$t), ]
```

```
# Estimate a HM-ALL-COV: benchmark without constraints on covariate effects

hm_all <- est_LM_cat_multinom("srhs1", ~ gender + race + education + age_c,
                             k = 3, data = srhs_example, baseline = "central",
                             model_cov = "all", model_int = "all",
                             output = TRUE, fort = TRUE)

print(hm_all)
summary(hm_all)

# Model with a common covariate effect across transitions
hm_const <- est_LM_cat_multinom("srhs1", ~ gender + race + education + age_c,
                                k = 3, data = srhs_example, baseline = "central",
                                model_cov = "const", model_int = "all",
                                output = TRUE, fort = TRUE)

print(hm_const)
summary(hm_const)

## End(Not run)
```

est_lm_cov_latent	<i>Estimate LM model with covariates in the latent model</i>
-------------------	--

Description

Main function for estimating the LM model with covariates in the latent model.

The function is no longer maintained. Please look at [lmest](#) function.

Usage

```
est_lm_cov_latent(S, X1=NULL, X2=NULL, yv = rep(1,nrow(S)), k, start = 0, tol = 10^-8,
                  maxit = 1000, param = "multilogit", Psi, Be, Ga, fort = TRUE,
                  output = FALSE, out_se = FALSE, fixPsi = FALSE)
```

Arguments

S	array of available configurations (n x TT x r) with categories starting from 0 (use NA for missing responses)
X1	matrix of covariates affecting the initial probabilities (n x nc1)
X2	array of covariates affecting the transition probabilities (n x TT-1 x nc2)
yv	vector of frequencies of the available configurations
k	number of latent states
start	type of starting values (0 = deterministic, 1 = random, 2 = initial values in input)
tol	tolerance level for checking convergence of the algorithm
maxit	maximum number of iterations of the algorithm

param	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
Psi	initial value of the array of the conditional response probabilities (mb x k x r)
Be	initial value of the parameters affecting the logit for the initial probabilities (if start=2)
Ga	initial value of the parameters affecting the logit for the transition probabilities (if start=2)
fort	to use fortran routine when possible (FALSE for not use fortran)
output	to return additional output (V,PI,Piv,UI)
out_se	to compute the information matrix and standard errors
fixPsi	TRUE if Psi is given in input and is not updated anymore

Value

lk	maximum log-likelihood
Be	estimated array of the parameters affecting the logit for the initial probabilities
Ga	estimated array of the parameters affecting the logit for the transition probabilities
Piv	estimate of initial probability matrix
PI	estimate of transition probability matrices
Psi	estimate of conditional response probabilities
np	number of free parameters
aic	value of AIC for model selection
bic	value of BIC for model selection
lkv	log-likelihood trace at every step
V	array containing the posterior distribution of the latent states for each response configuration and time occasion
UI	matrix containing the predicted sequence of latent states by the local decoding method
sePsi	standard errors for the conditional response matrix
seBe	standard errors for Be
seGa	standard errors for Ga
call	command used to call the function

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia, <http://www.stat.unipg.it/bartolucci>

References

Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
## Not run:
# Example based on self-rated health status (SRHS) data
# load SRHS data
data(data_SRHS_long)
dataSRHS = data_SRHS_long

TT <- 8
head(dataSRHS)
res <- long2matrices(dataSRHS$id, X = cbind(dataSRHS$gender-1,
dataSRHS$race == 2 | dataSRHS$race == 3, dataSRHS$education == 4,
dataSRHS$education == 5, dataSRHS$age-50, (dataSRHS$age-50)^2/100),
Y = dataSRHS$srhs)

# matrix of responses (with ordered categories from 0 to 4)
S <- 5-res$YY
n <- dim(S)[1]

# matrix of covariates (for the first and the following occasions)
# columns are: gender,race,educational level (2 columns),age,age^2)
X1 <- res$XX[,1,]
X2 <- res$XX[,2:TT,]

# estimate the model
est2f <- est_lm_cov_latent(S, X1, X2, k = 2, output = TRUE, out_se = TRUE)
summary(est2f)

# average transition probability matrix
PI <- round(apply(est2f$PI[,,,2:TT], c(1,2), mean), 4)

# Transition probability matrix for white females with high educational level
ind1 <- X1[,1] == 1 & X1[,2] == 0 & X1[,4] == 1)
PI1 <- round(apply(est2f$PI[,,,ind1,2:TT], c(1,2), mean), 4)

# Transition probability matrix for non-white male, low educational level
ind2 <- (X1[,1] == 0 & X1[,2] == 1 & X1[,3] == 0 & X1[,4] == 0)
PI2 <- round(apply(est2f$PI[,,,ind2,2:TT], c(1,2), mean), 4)

## End(Not run)
```

est_lm_cov_latent_cont

Estimate LM model for continuous outcomes with covariates in the latent model

Description

Main function for estimating the LM model for continuous outcomes with covariates in the latent model.

The function is no longer maintained. Please look at [lmestCont](#) function.

Usage

```
est_lm_cov_latent_cont(Y, X1 = NULL, X2 = NULL, yv = rep(1,nrow(Y)), k, start = 0,
  tol = 10^-8, maxit = 1000, param = "multilogit",
  Mu = NULL, Si = NULL, Be = NULL, Ga = NULL,
  output = FALSE, out_se = FALSE)
```

Arguments

Y	array of continuous outcomes (n x TT x r)
X1	matrix of covariates affecting the initial probabilities (n x nc1)
X2	array of covariates affecting the transition probabilities (n x TT-1 x nc2)
yv	vector of frequencies of the available configurations
k	number of latent states
start	type of starting values (0 = deterministic, 1 = random, 2 = initial values in input)
tol	tolerance level for checking convergence of the algorithm
maxit	maximum number of iterations of the algorithm
param	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
Mu	initial value of the conditional means (r x k) (if start=2)
Si	initial value of the var-cov matrix common to all states (r x r) (if start=2)
Be	initial value of the parameters affecting the logit for the initial probabilities (if start=2)
Ga	initial value of the parameters affecting the logit for the transition probabilities (if start=2)
output	to return additional output (V,PI,Piv,UI)
out_se	to compute the information matrix and standard errors

Value

lk	maximum log-likelihood
Be	estimated array of the parameters affecting the logit for the initial probabilities
Ga	estimated array of the parameters affecting the logit for the transition probabilities
Mu	estimate of conditional means of the response variables
Si	estimate of var-cov matrix common to all states
np	number of free parameters
aic	value of AIC for model selection
bic	value of BIC for model selection
lkv	log-likelihood trace at every step
Piv	estimate of initial probability matrix

PI	estimate of transition probability matrices
U1	matrix containing the predicted sequence of latent states by the local decoding method
call	command used to call the function

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia, <http://www.stat.unipg.it/bartolucci>

References

Pennington, F., Pandolfi, S. Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.

Bartolucci, F., Farcomeni, A. and Pennington, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
## Not run:
# Example based on multivariate longitudinal continuous data

data(data_long_cont)
TT <- 5
res <- long2matrices(data_long_cont$id, X = cbind(data_long_cont$X1, data_long_cont$X2),
  Y = cbind(data_long_cont$Y1, data_long_cont$Y2, data_long_cont$Y3))
Y <- res$YY
X1 <- res$XX[,1,]
X2 <- res$XX[,2:TT,]

# estimate the model
est <- est_lm_cov_latent_cont(Y, X1, X2, k = 3, output = TRUE)
summary(est)

# average transition probability matrix
PI <- round(apply(est$PI[,,,2:TT], c(1,2), mean), 4)
PI

## End(Not run)
```

est_lm_cov_manifest	<i>Estimate LM model with covariates in the measurement model</i>
---------------------	---

Description

Main function for estimating LM model with covariates in the measurement model based on a global logit parameterization.

The function is no longer maintained. Please look at [lmest](#) function.

Usage

```
est_lm_cov_manifest(S, X, yv = rep(1,nrow(S)), k, q = NULL, mod = c("LM", "FM"),
  tol = 10^-8, maxit = 1000, start = 0, mu = NULL, al = NULL,
  be = NULL, si = NULL, rho = NULL, la = NULL, PI = NULL,
  output = FALSE, out_se = FALSE)
```

Arguments

S	array of available configurations (n x TT) with categories starting from 0
X	array (n x TT x nc) of covariates with eventually includes lagged response (nc = number of covariates)
yv	vector of frequencies of the available configurations
k	number of latent states
q	number of support points for the AR(1) process
mod	model ("LM" = Latent Markov with stationary transition, "FM" = finite mixture)
tol	tolerance for the convergence (optional) and tolerance of conditional probability if tol>1 then return
maxit	maximum number of iterations of the algorithm
start	type of starting values (0 = deterministic, 1 = random, 2 = initial values in input)
mu	starting value for mu (optional)
al	starting value for al (optional)
be	starting value for be (optional)
si	starting value for si when mod="FM" (optional)
rho	starting value for rho when mod="FM" (optional)
la	starting value for la (optional)
PI	starting value for PI (optional)
output	to return additional output (PRED0, PRED1)
out_se	TRUE for computing information matrix and standard errors

Value

mu	vector of cutpoints
al	support points for the latent states
be	estimate of the vector of regression parameters
si	sigma of the AR(1) process (mod = "FM")
rho	parameter vector for AR(1) process (mod = "FM")
la	vector of initial probabilities
PI	transition matrix
lk	maximum log-likelihood
np	number of parameters

aic	value of AIC index
bic	value of BIC index
PRED0	prediction of latent state
PRED1	prediction of the overall latent effect
sebe	standard errors for the regression parameters be
selrho	standard errors for logit type transformation of rho
J1	information matrix
call	command used to call the function

Author(s)

Francesco Bartolucci, Silvia Pandolfi - University of Perugia (IT)

References

Pennoni, F., Pandolfi, S. Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.

Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Bartolucci, F., Bacci, S. and Pennoni, F. (2014) Longitudinal analysis of the self-reported health status by mixture latent autoregressive models, *Journal of the Royal Statistical Society - series C*, **63**, pp. 267-288

Examples

```
## Not run:
# Example based on self-rated health status (SRHS) data

# load SRHS data
data(data_SRHS_long)
dataSRHS <- data_SRHS_long
head(dataSRHS)

res <- long2matrices(dataSRHS$id, X = cbind(dataSRHS$gender-1,
  dataSRHS$race == 2 | dataSRHS$race == 3, dataSRHS$education == 4,
  dataSRHS$education == 5, dataSRHS$age-50, (dataSRHS$age-50)^2/100),
Y = dataSRHS$srhs)

X <- res$XX
S <- 5-res$YY

# *** fit stationary LM model
res0 <- vector("list", 10)
tol <- 10^-6;
for(k in 1:10){
  res0[[k]] <- est_lm_cov_manifest(S, X, k, 1, mod = "LM", tol)
}
tmp_file <- tempfile("example_SRHS_", fileext = ".RData")
```

```

save(res0, file = tmp_file)

# *** fit the mixture latent auto-regressive model
tol <- 0.005
res <- vector("list",4)
k <- 1
q <- 51
res[[k]] <- est_lm_cov_manifest(S, X, k, q, mod = "FM", tol, output = TRUE)
for(k in 2:4) res[[k]] <- est_lm_cov_manifest(S, X, k, q = 61, mod = "FM", tol, output = TRUE)

## End(Not run)

```

est_lm_mixed	<i>Estimate mixed LM model</i>
--------------	--------------------------------

Description

Main function for estimating the mixed LM model with discrete random effect in the latent model.

The function is no longer maintained. Please look at [lmestMixed](#) function

Usage

```
est_lm_mixed(S, yv = rep(1,nrow(S)), k1, k2, start = 0, tol = 10^-8, maxit = 1000,
             out_se = FALSE)
```

Arguments

S	array of available response configurations (n x TT x r) with categories starting from 0
yv	vector of frequencies of the available configurations
k1	number of latent classes
k2	number of latent states
start	type of starting values (0 = deterministic, 1 = random)
tol	tolerance level for convergence
maxit	maximum number of iterations of the algorithm
out_se	to compute standard errors

Value

la	estimate of the mass probability vector (distribution of the random effects)
Piv	estimate of initial probabilities
Pi	estimate of transition probability matrices
Psi	estimate of conditional response probabilities
lk	maximum log-likelihood

W	posterior probabilities of the random effect
np	number of free parameters
bic	value of BIC for model selection
call	command used to call the function

Author(s)

Francesco Bartolucci, Silvia Pandolfi - University of Perugia (IT)

References

Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
## Not run:
# Example based of criminal data

# load data
data(data_criminal_sim)
out <- long2wide(data_criminal_sim, "id", "time", "sex",
  c("y1", "y2", "y3", "y4", "y5", "y6", "y7", "y8", "y9", "y10"), aggr = T, full = 999)

XX <- out$XX
YY <- out$YY
freq <- out$freq
n1 <- sum(freq[XX[,1] == 1])
n2 <- sum(freq[XX[,1] == 2])
n <- sum(freq)

# fit mixed LM model only for females
YY <- YY[XX[,1] == 2,,]
freq <- freq[XX[,1] == 2]
k1 <- 2
k2 <- 2
res <- est_lm_mixed(YY, freq, k1, k2, tol = 10^-8)
summary(res)

## End(Not run)
```

est_mc_basic

Estimate basic Markov chain (MC) model

Description

Main function for estimating the basic MC model.

The function is no longer maintained. Please look at [lmestMc](#) function.

Usage

```
est_mc_basic(S, yv, mod = 0, tol = 10^-8, maxit = 1000, out_se = FALSE)
```

Arguments

S	matrix (n x TT) of available configurations of the response variable with categories starting from 0
yv	vector of frequencies of the available configurations
mod	model on the transition probabilities (0 for time-heter., 1 for time-homog., from 2 to (TT-1) partial homog. of that order)
tol	tolerance level for convergence
maxit	maximum number of iterations of the algorithm
out_se	to compute the information matrix and standard errors

Value

lk	maximum log-likelihood
piv	estimate of initial probability vector
Pi	estimate of transition probability matrices
np	number of free parameters
aic	value of AIC for model selection
bic	value of BIC for model selection
Fy	estimated marginal distribution of the response variable for each time occasion
sepiv	standard errors for the initial probabilities
sePi	standard errors for the transition probabilities
call	command used to call the function

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

References

Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
# Example of drug consumption data

# load data
data(data_drug)
data_drug <- as.matrix(data_drug)
S <- data_drug[,1:5]-1
yv <- data_drug[,6]
```

```
# fit of the Basic MC model
out <- est_mc_basic(S, yv, mod = 1, out_se = TRUE)
summary(out)
```

est_mc_cov

Estimate Markov chain (MC) model with covariates

Description

Main function for estimating the MC model with covariates.

The function is no longer maintained. Please look at [lmestMc](#) function.

Usage

```
est_mc_cov(S, X1 = NULL, X2 = NULL, yv = rep(1,nrow(S)), start = 0, tol = 10^-8,
  maxit = 1000, out_se = FALSE, output = FALSE, fort = TRUE)
```

Arguments

S	matrix of available configurations of the response variable (n x TT) with categories starting from 0
X1	matrix of covariates affecting the initial probabilities (n x nc1)
X2	array of covariates affecting the transition probabilities (n x TT-1 x nc2)
yv	vector of frequencies of the available configurations
start	type of starting values (0 = deterministic, 1 = random)
tol	tolerance level for checking convergence of the algorithm
maxit	maximum number of iterations of the algorithm
out_se	to compute the information matrix and standard errors
output	to return additional output (PI,Piv)
fort	to use fortran routine when possible (FALSE for not use fortran)

Value

lk	maximum log-likelihood
Be	estimated array of the parameters affecting the logit for the initial probabilities
Ga	estimated array of the parameters affecting the logit for the transition probabilities
np	number of free parameters
aic	value of AIC for model selection
bic	value of BIC for model selection
seBe	standard errors for Be

seGa	standard errors for Ga
Piv	estimate of initial probability matrix
PI	estimate of transition probability matrices
call	command used to call the function

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia, <http://www.stat.unipg.it/bartolucci>

References

Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
## Not run:

# Example based on criminal data

# load criminal data
data(data_criminal_sim)

#We consider the response variable referring of crime of type 5

out <- long2wide(data_criminal_sim, "id", "time", "sex",
"y5", aggr = T, full = 999)
XX <- out$XX-1
YY <- out$YY
freq <- out$freq
TT <- 6

X1 <- as.matrix(XX[,1])
X2 <- as.matrix(XX[,2:TT])
# estimate the model
res <- est_mc_cov(S = YY, yv = freq, X1 = X1, X2 = X2, output = TRUE)
summary(res)

# Initial probability for female
Piv0 <- round(colMeans(res$Piv[X1 == 0,]), 4)

# Initial probability for male
Piv1 <- round(colMeans(res$Piv[X1 == 1,]), 4)

## End(Not run)
```

LMbasic-class

Class 'LMbasic'

Description

An S3 class object created by `lmest` function for basic Latent Markov (LM) model.

Value

lk	maximum log-likelihood at convergence of the EM algorithm
piv	estimate of initial probability vector
Pi	estimate of transition probability matrices ($k \times k \times TT$)
Psi	estimate of conditional response probabilities ($mb \times k \times r$)
np	number of free parameters
k	number of latent states
aic	value of the Akaike Information Criterion for model selection
bic	value of the Bayesian Information Criterion for model selection
lkv	log-likelihood trace at every step
n	sample size (sum of the weights when weights are provided)
TT	number of time occasions
modBasic	model on the transition probabilities: default 0 for time-heterogeneous transition matrices, 1 for time-homogeneous transition matrices, 2 for partial time homogeneity based on two transition matrices one from 2 to (TT-1) and the other for TT.
sepiv	standard errors for the initial probabilities
sePi	standard errors for the transition probabilities
sePsi	standard errors for the conditional response probabilities
Lk	vector containing the values of the log-likelihood of the LM model with each k (latent states)
Bic	vector containing the values of the BIC for each k
Aic	vector containing the values of the AIC for each k
V	array containing the estimated posterior probabilities of the latent states for each response configuration and time occasion
U1	matrix containing the predicted sequence of latent states by the local decoding method
S	array containing the available response configurations
yv	vector of frequencies of the available configurations
Pmarg	matrix containing the marginal distribution of the latent states
ns	number of distinct response configurations
call	command used to call the function
data	data.frame given in input

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

See Also

[lmest](#)

LMbasiccont-class	Class 'LMbasiccont'
-------------------	---------------------

Description

An S3 class object created by [lmestCont](#) function for the latent Markov (LM) model for continuous responses in long format.

Value

lk	maximum log-likelihood
piv	estimate of initial probability vector
Pi	estimate of transition probability matrices (k x k x TT)
Mu	estimate of conditional means of the response variables (r x k)
Si	estimate of var-cov matrix common to all states (r x r)
np	number of free parameters
k	optimal number of latent states
aic	value of the Akaike Information Criterion for model selection
bic	value of the Bayesian Information Criterion for model selection
lkv	log-likelihood trace at every step
n	number of observations in the data
TT	number of time occasions
modBasic	model on the transition probabilities: default 0 for time-heterogeneous transition matrices, 1 for time-homogeneous transition matrices, 2 for partial time homogeneity based on two transition matrices one from 2 to (TT-1) and the other for TT
sepiv	standard errors for the initial probabilities
sePi	standard errors for the transition probabilities
seMu	standard errors for the conditional means
seSi	standard errors for the var-cov matrix
sc	score vector
J	information matrix
Lk	vector containing the values of the log-likelihood of the LM model with each k (latent states)

Bic	vector containing the values of the BIC of the LM model with each k (latent states)
Aic	vector containing the values of the AIC of the LM model with each k (latent states)
V	array containing the posterior distribution of the latent states for each units and time occasion
U1	matrix containing the predicted sequence of latent states by the local decoding method
Pmarg	matrix containing the marginal distribution of the latent states
call	command used to call the function
data	data frame given in input

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

See Also

[lmestCont](#)

lmest

Estimate Latent Markov models for categorical responses

Description

Main function for estimating Latent Markov (LM) models for categorical responses.

Usage

```
lmest(responsesFormula = NULL, latentFormula = NULL,
      data, index, k = 1:4, start = 0,
      modSel = c("BIC", "AIC"), modBasic = 0,
      modManifest = c("LM", "FM"),
      paramLatent = c("multilogit", "difflogit"),
      weights = NULL, tol = 10^-8, maxit = 1000,
      out_se = FALSE, q = NULL, output = FALSE,
      parInit = list(piv = NULL, Pi = NULL, Psi = NULL,
                    Be = NULL, Ga = NULL, mu = NULL,
                    al = NULL, be = NULL, si = NULL,
                    rho = NULL, la = NULL, PI = NULL,
                    fixPsi = FALSE),
      fort = TRUE, seed = NULL, ntry = 0)
```

Arguments

<code>responsesFormula</code>	a symbolic description of the model to fit. A detailed description is given in the ‘Details’ section
<code>latentFormula</code>	a symbolic description of the model to fit. A detailed description is given in the ‘Details’ section
<code>data</code>	a <code>data.frame</code> in long format
<code>index</code>	a character vector with two elements, the first indicating the name of the unit identifier, and the second the time occasions
<code>k</code>	an integer vector specifying the number of latent states (default: 1:4)
<code>start</code>	type of starting values (0 = deterministic, 1 = random, 2 = initial values in input)
<code>modSel</code>	a string indicating the model selection criteria: "BIC" for Bayesian Information Criterion and "AIC" for Akaike Information Criterion
<code>modBasic</code>	model on the transition probabilities (0 for time-heterogeneity, 1 for time-homogeneity, from 2 to (TT-1) partial time-homogeneity of a certain order)
<code>modManifest</code>	model for manifest distribution when covariates are included in the measurement model ("LM" = Latent Markov with stationary transition, "FM" = finite mixture model where a mixture of AR(1) processes is estimated with common variance and specific correlation coefficients).
<code>paramLatent</code>	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
<code>weights</code>	an optional vector of weights for the available responses
<code>tol</code>	tolerance level for convergence
<code>maxit</code>	maximum number of iterations of the algorithm
<code>out_se</code>	to compute the information matrix and standard errors
<code>q</code>	number of support points for the AR(1) process (if <code>modManifest</code> = "FM")
<code>output</code>	to return additional output: Posterior probabilities V , decoded states $U1$, response configurations S , vector of frequencies yv , marginal probabilities $Pmarg$ for the basic LM model and for the LM with covariates on the latent model (LMbasic-class and LMlatent-class) and V , $PRED1$, S , yv , $Pmarg$ for the LM model with covariates in the measurement model (LMmanifest-class)
<code>parInit</code>	list of initial model parameters when "start = 2". For the list of parameters look at LMbasic-class , LMlatent-class and LMmanifest-class
<code>fort</code>	to use fortran routines when possible
<code>seed</code>	an integer value with the random number generator state
<code>ntry</code>	to set the number of random initializations

Details

`lmest` is a general function for estimating LM models for categorical responses. The function requires data in long format and two additional columns indicating the unit identifier and the time occasions.

Covariates are allowed to affect manifest distribution (measurement model) or the initial and transition probabilities (latent model). Two different formulas are employed to specify the different LM models, `responsesFormula` and `latentFormula`:

- `responsesFormula` is used to specify the measurement model:
 - `responsesFormula = y1 + y2 ~ NULL`
the LM model without covariates and two responses (`y1` and `y2`) is specified;
 - `responsesFormula = NULL`
all the columns in the data except the "id" and "time" columns are used as responses to estimate the LM model without covariates;
 - `responsesFormula = y1 ~ x1 + x2`
the univariate LM model with response (`y1`) and two covariates (`x1` and `x2`) in the measurement model is specified;
- `latentFormula` is used to specify the LM model with covariates in the latent model:
 - `responsesFormula = y1 + y2 ~ NULL`
`latentFormula = ~ x1 + x2 | x3 + x4`
the LM model with two responses (`y1` and `y2`) and two covariates affecting the initial probabilities (`x1` and `x2`) and other two affecting the transition probabilities (`x3` and `x4`) is specified;
 - `responsesFormula = y1 + y2 ~ NULL`
`latentFormula = ~ 1 | x1 + x2`
(or `latentFormula = ~ NULL | x1 + x2`)
the covariates affect only the transition probabilities and an intercept is specified for the initial probabilities;
 - `responsesFormula = y1 + y2 ~ NULL`
`latentFormula = ~ x1 + x2`
the LM model with two covariates (`x1` and `x2`) affecting both the initial and transition probabilities is specified;
 - `responsesFormula = y1 + y2 ~ NULL`
`latentFormula = ~ NULL | NULL`
(or `latentFormula = ~ 1 | 1`)
the LM model with only an intercept on the initial and transition probabilities is specified.

The function also allows us to deal with missing responses, including drop-out and non-monotonic missingness, under the missing-at-random assumption. Missing values for the covariates are not allowed.

The LM model with individual covariates in the measurement model is estimated only for complete univariate responses. In such a case, two possible formulations are allowed: `modManifest="LM"` is used to estimate the model illustrated in Bartolucci et al. (2017), where the latent process is of first order with initial probabilities equal to those of the stationary distribution of the chain; `modManifest="FM"` is used to estimate a model relying on the assumption that the distribution of the latent process is a mixture of AR(1) processes with common variance and specific correlation coefficients. This model is illustrated in Bartolucci et al. (2014).

For continuous outcomes see the function [lmestCont](#).

Value

Returns an object of class 'LMbasic' for the model without covariates (see [LMbasic-class](#)), or an object of class 'LMmanifest' for the model with covariates on the manifest model (see [LMmanifest-class](#)), or an object of class 'LMlatent' for the model with covariates on the latent model (see [LMlatent-class](#)).

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

References

Pennoni, F., Pandolfi, S. and Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.

Bartolucci F., Pandolfi S., and Pennoni F. (2017) LMest: An R Package for Latent Markov Models for Longitudinal Categorical Data, *Journal of Statistical Software*, **81**(4), 1-38.

Bartolucci, F., Bacci, S., and Pennoni, F. (2014). Longitudinal analysis of the self-reported health status by mixture latent autoregressive models, *Journal of the Royal Statistical Society - series C*, **63**, pp. 267-288.

Bartolucci, F., Farcomeni, A., and Pennoni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
### Basic LM model

data("data_SRHS_long")
SRHS <- data_SRHS_long[1:2400,]

# Categories rescaled to vary from 0 ("poor") to 4 ("excellent")

SRHS$srhs <- 5 - SRHS$srhs

out <- lmest(responsesFormula = srhs ~ NULL,
             index = c("id", "t"),
             data = SRHS,
             k = 3,
             start = 1,
             modBasic = 1,
             seed = 123)

out
summary(out)

## Not run:

## Basic LM model with model selection using BIC
```

```

out1 <- lmest(responsesFormula = srhs ~ NULL,
              index = c("id","t"),
              data = SRHS,
              k = 1:5,
              tol = 1e-8,
              modBasic = 1,
              seed = 123, ntry = 2)

out1
out1$Bic

# Basic LM model with model selection using AIC

out2 <- lmest(responsesFormula = srhs ~ NULL,
              index = c("id","t"),
              data = SRHS,
              k = 1:5,
              tol = 1e-8,
              modBasic = 1,
              modSel = "AIC",
              seed = 123, ntry = 2)

out2
out2$Aic

# Criminal data

data(data_criminal_sim)
data_criminal_sim = data.frame(data_criminal_sim)

responsesFormula <- lmestFormula(data = data_criminal_sim, response = "y")$responsesFormula

out3 <- lmest(responsesFormula = responsesFormula,
              index = c("id","time"),
              data = data_criminal_sim,
              k = 1:7,
              modBasic = 1,
              tol = 10^-4)

out3

# Example of drug consumption data

data("data_drug")
long <- data_drug[,-6]-1
long <- data.frame(id = 1:nrow(long), long)
long <- reshape(long, direction = "long",
                idvar = "id",
                varying = list(2:ncol(long)))

out4 <- lmest(index = c("id","time"),
              k = 3,
              data = long,
              weights = data_drug[,6],
              modBasic = 1)

```

```

out4
summary(out4)

### LM model with covariates in the latent model
# Covariates: gender, race, educational level (2 columns), age and age^2

out5 <- lmest(responsesFormula = srhs ~ NULL,
              latentFormula = ~
                I(gender - 1) +
                I( 0 + (race == 2) + (race == 3)) +
                I(0 + (education == 4)) +
                I(0 + (education == 5)) +
                I(age - 50) + I((age-50)^2/100),
              index = c("id","t"),
              data = SRHS,
              k = 2,
              paramLatent = "multilogit",
              start = 0)

out5
summary(out5)

### LM model with the above covariates in the measurement model (stationary model)

out6 <- lmest(responsesFormula = srhs ~ -1 +
              I(gender - 1) +
              I( 0 + (race == 2) + (race == 3)) +
              I(0 + (education == 4)) +
              I(0 + (education == 5)) + I(age - 50) +
              I((age-50)^2/100),
              index = c("id","t"),
              data = SRHS,
              k = 2,
              modManifest = "LM",
              out_se = TRUE,
              tol = 1e-8,
              start = 1,
              seed = 123)

out6
summary(out6)

#### LM model with covariates in the measurement model (mixture latent auto-regressive model)

out7 <- lmest(responsesFormula = srhs ~ -1 +
              I(gender - 1) +
              I( 0 + (race == 2) + (race == 3)) +
              I(0 + (education == 4)) +
              I(0 + (education == 5)) + I(age - 50) +
              I((age-50)^2/100),
              index = c("id","t"),
              data = SRHS,
              k = 2,

```

```

modManifest = "FM", q = 61,
out_se = TRUE,
tol = 1e-8)

out7
summary(out7)

## End(Not run)

```

lmestCont

Estimate Latent Markov models for continuous responses

Description

Main function for estimating Latent Markov (LM) models for continuous outcomes under the assumption of (multivariate) Gaussian distribution of the response variables given the latent process.

Usage

```

lmestCont(responsesFormula = NULL, latentFormula = NULL,
data, index, k = 1:4, start = 0,
modSel = c("BIC", "AIC"), modBasic = 0,
paramLatent = c("multilogit", "difflogit"),
weights = NULL, tol = 10^-10,
maxit = 5000, out_se = FALSE, output = FALSE,
parInit = list(piv = NULL, Pi = NULL,
Mu = NULL, Si = NULL,
Be = NULL, Ga = NULL),
fort = TRUE, seed = NULL, ntry = 0, miss.imp = FALSE)

```

Arguments

responsesFormula	a symbolic description of the model to be fitted. A detailed description is given in the ‘Details’ section
latentFormula	a symbolic description of the model to be fitted. A detailed description is given in the ‘Details’ section
data	a data.frame in long format
index	a character vector with two elements, the first indicating the name of the unit identifier, and the second the time occasions
k	an integer vector specifying the number of latent states (default: 1:4)
start	type of starting values (0 = deterministic, 1 = random, 2 = initial values in input)
modSel	a string indicating the model selection criteria: "BIC" for Bayesian Information Criterion and "AIC" for Akaike Information Criterion
modBasic	model on the transition probabilities (0 for time-heter., 1 for time-homog., from 2 to (TT-1) partial homog. of that order)

paramLatent	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
weights	vector of weights
tol	tolerance level for convergence
maxit	maximum number of iterations of the algorithm
out_se	to compute the information matrix and standard errors (By default is set to FALSE)
output	to return additional output (V, U1, Pmarg) (LMbasiccont-class , LMlatentcont-class , LMmanifestcont-class)
parInit	list of initial model parameters when "start = 2". For the list of parameters look at LMbasiccont-class , LMlatentcont-class , and LMmanifestcont-class
fort	to use fortran routines when possible (By default is set to TRUE)
seed	an integer value with the random number generator state
ntry	to set the number of random initializations
miss.imp	how to deal with missing values (TRUE for imputation through the imp.mix function, FALSE for missing at random assumption)

Details

The function `lmestCont` is a general function for estimating LM models for continuous responses. The function requires data in long format and two additional columns indicating the unit identifier and the time occasions.

Covariates are allowed on the initial and transition probabilities (latent model) and in the measurement model. Two different formulas are employed to specify the different LM models, `responsesFormula` and `latentFormula`:

- `responsesFormula` is used to specify the measurement model:
 - `responsesFormula = y1 + y2 ~ NULL`
the LM model without covariates and two responses (`y1` and `y2`) is specified.
 - `responsesFormula = NULL`
all the columns in the data except the "id" and "time" columns are used as responses to estimate the LM model without covariates;
 - `responsesFormula = y1 + y2 ~ x1 + x2`
the LM model with two responses (`y1` and `y2`) and two covariates in the measurement model is specified;
- `latentFormula` is used to specify the LM model with covariates in the latent model:
 - `responsesFormula = y1 + y2 ~ NULL`
`latentFormula = ~ x1 + x2 | x3 + x4`
the LM model with two responses (`y1` and `y2`) and two covariates affecting the initial probabilities (`x1` and `x2`) and other two affecting the transition probabilities (`x3` and `x4`) is specified;
 - `responsesFormula = y1 + y2 ~ NULL`
`latentFormula = ~ 1 | x1 + x2`
(or `latentFormula = ~ NULL | x1 + x2`)
the covariates affect only the transition probabilities and an intercept is specified for the initial probabilities;


```
      tol = 10^-5)

out
summary(out)

# Basic LM model with model selection using BIC

out1 <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 1:5,
                  ntry = 2,
                  modBasic = 1,
                  tol = 10^-5)

out1
out1$Bic

# Basic LM model with model selection using AIC

out2 <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 1:5,
                  modBasic = 1,
                  ntry = 2,
                  modSel = "AIC",
                  tol = 10^-5)

out2
out2$Aic

# LM model with covariates in the measurement model

out3 <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ X1 + X2,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 3,
                  output = TRUE)

out3
summary(out3)

# LM model with covariates in the latent model

out4 <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                  latentFormula = ~ X1 + X2,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 3,
                  output = TRUE)

out4
```

```
summary(out4)

# LM model with two covariates affecting the initial probabilities and one
# affecting the transition probabilities

out5 <- lmeStCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                  latentFormula = ~ X1 + X2 | X1,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 3,
                  output = TRUE)

out5
summary(out5)

## End(Not run)
```

lmeStData	<i>Data for lmeSt functions</i>
-----------	---------------------------------

Description

An object of class `lmeStData` containing data in long format, some necessary information on the data structure and objects for the estimation functions.

Usage

```
lmeStData(data, id = NULL, time = NULL,
          idAsFactor = TRUE, timeAsFactor = TRUE,
          responsesFormula = NULL, latentFormula = NULL,
          na.rm = FALSE, check.names = FALSE)
```

Arguments

<code>data</code>	a matrix or data frame in long format of observation
<code>id</code>	a numeric vector or a string indicating the column with the unit identifier. If <code>NULL</code> , the first column is considered
<code>time</code>	a numeric vector or a string indicating the column with the time occasions. If <code>NULL</code> , the second column is considered, and if the <code>id</code> is not <code>NULL</code> , the function will automatically add the column with the time occasions
<code>idAsFactor</code>	a logical value indicating whether or not the column with the ids is converted to a factor. (By default is set to <code>TRUE</code>)
<code>timeAsFactor</code>	a logical value indicating whether or not the column with the time occasions is converted in a factor. (By default is set to <code>TRUE</code>)
<code>responsesFormula</code>	A detailed description is given in lmeSt , lmeStCont

latentFormula	A detailed description is given in lmeSt , lmeStCont
na.rm	a logical value indicating whether or not the observation with at least a missing value is removed (By default is set to FALSE)
check.names	a logical value indicating whether or not the names of the variables are syntactically valid, and adjusted if necessary. (By default is set to FALSE)

Value

An object of class 'lmeStData' with the following objects:

data	a data.frame object to use in the estimation functions
id	a integer vector with the unit identifier
time	a integer vector with the time occasions
n	the number of observation
TT	an integer value indicating number of time occasions
d	an interger value indicating the number of variables (columns except id and time)
Y	the response variables
Xmanifest	the variables affecting the measurement model if specified in responsesFormula
Xinitial	the variables affecting the initial probabilities of the latent model if specified in latentFormula
Xtrans	the variables affecting the transition probabilities of the latent model if specified in latentFormula

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Penzoni, Alessio Farcomeni, Alessio Serafini

Examples

```
data(data_long_cont)
str(data_long_cont)

## Data with continous resposes

dt <- lmeStData(data = data_long_cont, id = "id", time="time")
str(dt)

## Summary of each variable and for each time

summary(dt)

## Summary of each variable

summary(dt, type = "cross")

## Summary of each variable by time
```

```

summary(dt, type = "year")

plot(dt)
plot(dt, typePlot = "sh")

#####

## Not run:

data("data_criminal_sim")

dt1 <- lmestData(data = data_criminal_sim, id = "id", time = "time")
str(dt1)

summary(dt1, varType = rep("d",ncol(dt1$Y)))

dt2 <- lmestData(data = data_criminal_sim, id = "id", time = "time",
                 responsesFormula = y1 + y2 ~ y3, latentFormula = ~ y7 + y8 | y9 + y10)
str(dt2)

## Summary for responses, covariates on the manifest distribution,
## covariates on intial and transition probabilities

summary(dt2, dataSummary = "responses",varType = rep("d",ncol(dt2$Y)))
summary(dt2, dataSummary = "manifest",varType = rep("d",ncol(dt2$Xmanifest)))
summary(dt2, dataSummary = "initial",varType = rep("d",ncol(dt2$Xinitial)))
summary(dt2, dataSummary = "transition",varType = rep("d",ncol(dt2$Xtrans)))

## End(Not run)

```

lmestDecoding

Perform local and global decoding

Description

Function that performs local and global decoding (Viterbi algorithm) from the output of `lmest`, `lmestCont`, and `lmestMixed`.

Usage

```

lmestDecoding(est, sequence = NULL, fort = TRUE, ...)
## S3 method for class 'LMbasic'
lmestDecoding(est, sequence = NULL, fort = TRUE, ...)
## S3 method for class 'LMmanifest'
lmestDecoding(est, sequence = NULL, fort = TRUE, ...)
## S3 method for class 'LMlatent'
lmestDecoding(est, sequence = NULL, fort = TRUE,...)

```

```
## S3 method for class 'LMbasiccont'
lmestDecoding(est, sequence = NULL, fort = TRUE,...)
## S3 method for class 'LMmixed'
lmestDecoding(est, sequence = NULL, fort = TRUE,...)
```

Arguments

<code>est</code>	an object obtained from a call to <code>lmest</code> , <code>lmestCont</code> , and <code>lmestMixed</code>
<code>sequence</code>	an integer vector indicating the units for the decoding. If NULL the whole observations are considered. (By default is set to NULL)
<code>fort</code>	to use fortran routines when possible
<code>...</code>	further arguments

Value

<code>U1</code>	matrix of local decoded states corresponding to each row of Y
<code>Ug</code>	matrix of global decoded states corresponding to each row of Y

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

References

Viterbi A. (1967) Error Bounds for Convolutional Codes and an Asymptotically Optimum Decoding Algorithm. *IEEE Transactions on Information Theory*, **13**, 260-269.

Juan B., Rabiner L. (1991) Hidden Markov Models for Speech Recognition. *Technometrics*, **33**, 251-272.

Examples

```
# Decoding for basic LM model

data("data_drug")
long <- data_drug[,-6]-1
long <- data.frame(id = 1:nrow(long),long)
long <- reshape(long,direction = "long",
                idvar = "id",
                varying = list(2:ncol(long)))

est <- lmest(index = c("id","time"),
             k = 3,
             data = long,
             weights = data_drug[,6],
             modBasic = 1)

# Decoding for a single sequence

out1 <- lmestDecoding(est, sequence = 1)
```

```

out2 <- lmestDecoding(est, sequence = 1:4)

# Decoding for all sequences

out3 <- lmestDecoding(est)

## Not run:
# Decoding for LM model with covariates on the initial and transition probabilities

data("data_SRHS_long")

SRHS <- data_SRHS_long[1:2400,]

# Categories rescaled to vary from 0 ("poor") to 4 ("excellent")

SRHS$srhs <- 5 - SRHS$srhs

est2 <- lmest(responsesFormula = srhs ~ NULL,
              latentFormula = ~
                I(gender - 1) +
                I( 0 + (race == 2) + (race == 3)) +
                I(0 + (education == 4)) +
                I(0 + (education == 5)) +
                I(age - 50) + I((age-50)^2/100),
              index = c("id","t"),
              data = SRHS,
              k = 2,
              paramLatent = "difflogit",
              output = TRUE)

# Decoding for a single sequence

out3 <- lmestDecoding(est2, sequence = 1)

# Decoding for the first three sequences

out4 <- lmestDecoding(est2, sequence = 1:3)

# Decoding for all sequences

out5 <- lmestDecoding(est2)

## End(Not run)

```

lmestFormula

Formulas for LMest functions

Description

Bulding formulas for [lmest](#), [lmestCont](#), [lmestMixed](#), and [lmestMc](#).

Usage

```
lmestFormula(data,
              response, manifest = NULL,
              LatentInitial = NULL, LatentTransition = NULL,
              AddInterceptManifest = FALSE,
              AddInterceptInitial = TRUE,
              AddInterceptTransition = TRUE, responseStart = TRUE,
              manifestStart = TRUE, LatentInitialStart = TRUE,
              LatentTransitionStart = TRUE)
```

Arguments

<code>data</code>	a data.frame or a matrix of data
<code>response</code>	a numeric or character vector indicating the column indices or the names for the response variables
<code>manifest</code>	a numeric or character vector indicating the column indices or the names for the covariates affecting the measurement model
<code>LatentInitial</code>	a numeric or character vector indicating the column indices or the names for the covariates affecting the initial probabilities
<code>LatentTransition</code>	a numeric or character vector indicating the column indices or the names for the covariates affecting the transition probabilities
<code>AddInterceptManifest</code>	a logical value indicating whether the intercept is added to the covariates affecting the measurement model
<code>AddInterceptInitial</code>	a logical value indicating whether the intercept is added to covariates affecting the initial probabilities
<code>AddInterceptTransition</code>	a logical value indicating whether the intercept is added to covariates affecting the transition probabilities
<code>responseStart</code>	a logical value indicating whether the response variables names start with response argument
<code>manifestStart</code>	a logical value indicating whether the covariates names start with manifest argument
<code>LatentInitialStart</code>	a logical value indicating whether the covariates names start with LatentInitial argument
<code>LatentTransitionStart</code>	a logical value indicating whether the covariates names start with LatentTransition argument

Details

Generates formulas for `responsesFormula` and `latentFormula` to use in `lmest`, `lmestCont`, `lmestMixed`, and `lmestMc`.

Value

Returns a list with responsesFormula and latentFormula objects.

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

Examples

```
data(data_SRHS_long)
names(data_SRHS_long)

# Formula with response srhs and covariates for both initail and transition:
# gender,race,educational,age.

## LM model with covariates on the latent model
# and with intercepts on the initial and transition probabilities

fm <- lmestFormula(data = data_SRHS_long,
                   response = "srhs",
                   LatentInitial = 3:6, LatentTransition = 3:6)

fm

## LM model with covariates on the latent model
# and without intercepts on the initial and transition probabilities

fm <- lmestFormula(data = data_SRHS_long,
                   response = "srhs",
                   LatentInitial = 3:6, LatentTransition = 3:6,
                   AddInterceptInitial = FALSE,AddInterceptTransition = FALSE)

fm

#####

data(data_criminal_sim)
str(data_criminal_sim)

# Formula with only the responses from y1 to y10

fm <- lmestFormula(data = data_criminal_sim,response = "y")$responsesFormula
fm

# Formula with only the responses from y1 to y10 and intercept for manifest

fm <- lmestFormula(data = data_criminal_sim,
                   response = "y",AddInterceptManifest = TRUE)$responsesFormula
fm

## LM model for continous responses

data(data_long_cont)
```

```

names(data_long_cont)

# Formula with response Y1, Y2, no covariate for manifest,
# X1 covariates for initail and X2 covariate for transition

fm <- lmestFormula(data = data_long_cont,
                  response = c("Y"),
                  LatentInitial = "X",
                  LatentTransition = "X2")

fm

## Wrong model specification since two variable start with X.
# Check the starts arguments.

# For the right model:

fm <- lmestFormula(data = data_long_cont,
                  response = c("Y"),
                  LatentInitial = "X1", LatentTransition = "X2")

fm

## or

fm <- lmestFormula(data = data_long_cont,
                  response = c("Y"),
                  LatentInitial = 6, LatentTransition = "X2",
                  LatentInitialStart = FALSE)

fm

## Not run:

data(data_criminal_sim)
data_criminal_sim <- data.frame(data_criminal_sim)

# Mixed LM model for females

responsesFormula <- lmestFormula(data = data_criminal_sim,
                                response = "y")$responsesFormula

out <- lmest(responsesFormula = responsesFormula,
            index = c("id", "time"),
            data = data_criminal_sim,
            k = 2)

## End(Not run)

```

Description

Main function for estimating Markov Chain (MC) models for categorical responses with or without covariates.

Usage

```
lmestMc(responsesFormula = NULL,
        data, index, start = 0,
        modBasic = NULL, weights = NULL,
        tol = 10^-8, maxit = 1000,
        out_se = FALSE, output = FALSE, fort = TRUE, seed = NULL)
```

Arguments

responsesFormula	a symbolic description of the model to fit. A detailed description is given in the 'Details' section
data	a data.frame in long format
index	a character vector with two elements, the first indicating the name of the unit identifier, and the second the time occasions
start	type of starting values (0 = deterministic, 1 = random, 2 = initial values in input)
modBasic	model on the transition probabilities (0 for time-heter., 1 for time-homog., from 2 to (TT-1) partial homog. of that order)
weights	an optional vector of weights for the available responses
tol	tolerance level for convergence
maxit	maximum number of iterations of the algorithm
out_se	to compute the information matrix and standard errors (FALSE is the default option)
output	to return additional output (transition matrix PI, initial probabilities Piv) (McCov-class)
fort	to use fortran routines when possible (By default is set to TRUE)
seed	An integer value with the random number generator state.

Details

The function `lmestMc` estimates the basic MC model and the univariate MC model with covariates for categorical responses. The function requires data in long format and two additional columns indicating the unit identifier and the time occasions.

`responsesFormula` is used to specify the basic MC models and the model with covariates:

- `responsesFormula = y1 ~ NULL`
the MC model without covariates and one response (`y1`) is specified;
- `responsesFormula = NULL`
all the columns in the data except the "id" and "time" columns are used to estimate MC without covariates;

- `responsesFormula = y1 ~ x1 + x2 | x3 + x4`
the MC model with one response (y1), two covariates affecting the initial probabilities (x1 and x2) and other two different covariates affecting the transition probabilities (x3 and x4) is specified;
- `responsesFormula = y1 ~ x1 + x2`
the MC model with one response (y1) and two covariates (x1 and x2) affecting both the initial and transition probabilities is specified.

Missing responses are not allowed.

Value

Returns an object of class 'MCbasic' for the basic model without covariates (see [MCbasic-class](#)), or an object of class 'Mccov' for the model with covariates (see [Mccov-class](#)).

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

References

- Pennoni, F., Pandolfi, S. and Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.
- Bartolucci F., Pandolfi S. and Pennoni, F. (2017). LMest: An R Package for Latent Markov Models for Longitudinal Categorical Data, *Journal of Statistical Software*, **81**(4), 1-38.
- Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013). *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
## Not run:
# Basic Markov Chain model

data("RLMSlong")

# Categories rescaled from 0 "absolutely unsatisfied" to 4 "absolutely satisfied"

RLMSlong$value <- 5 - RLMSlong$value

out <- lmestMc(responsesFormula = value ~ NULL,
               index = c("id", "time"),
               modBasic = 1,
               data = RLMSlong)

out
summary(out)

# Example of drug consumption data
```

```

data("data_drug")
long <- data_drug[,-6]
long <- data.frame(id = 1:nrow(long),long)
long <- reshape(long,direction = "long",
                idvar = "id",
                varying = list(2:ncol(long)))

out1 <- lmestMc(index = c("id","time"), data = long,
               weights = data_drug[,6], modBasic = 1, out_se = TRUE)

out1

### MC model with covariates
### Covariates: gender, race, educational level (2 columns), age and age^2

data("data_SRHS_long")
SRHS <- data_SRHS_long[1:2400,]

# Categories of the responses rescaled from 1 "poor" to 5 "excellent"

SRHS$srhs <- 5 - SRHS$srhs

out2 <- lmestMc(responsesFormula = srhs ~
                I( 0 + (race==2) + (race == 3)) +
                I(0 + (education == 4)) +
                I(0 + (education == 5)) +
                I(age - 50) +
                I((age-50)^2/100),
                index = c("id","t"),
                data = SRHS)

out2
summary(out2)

# Criminal data

data(data_criminal_sim)
data_criminal_sim = data.frame(data_criminal_sim)

out3 <- lmestMc(responsesFormula = y5~sex,
                index = c("id","time"),
                data = data_criminal_sim,
                output = TRUE)

out3

## End(Not run)

```

Description

Main function for estimating the mixed latent Markov (LM) models for categorical responses with discrete random effects in the latent model.

Usage

```
lmestMixed(responsesFormula = NULL,
            data, index, k1, k2, start = 0,
            weights = NULL, tol = 10^-8, maxit = 1000,
            out_se = FALSE, seed = NULL)
```

Arguments

responsesFormula	a symbolic description of the model to fit. A detailed description is given in the 'Details' section
data	a data.frame in long format
index	a character vector with two elements, the first indicating the name of the unit identifier, and the second the time occasions
k1	number of latent classes
k2	number of latent states
start	type of starting values (0 = deterministic, 1 = random, 2 = initial values in input)
weights	an optional vector of weights for the available responses
tol	tolerance level for convergence
maxit	maximum number of iterations of the algorithm
out_se	to compute the information matrix and standard errors (FALSE is the default option)
seed	an integer value with the random number generator state

Details

The function `lmestMixed` estimates the mixed LM for categorical data. The function requires data in long format and two additional columns indicating the unit identifier and the time occasions.

`responsesFormula` is used to specify the responses of the mixed LM model:

- `responsesFormula = y1 + y2 ~ NULL`
the mixed LM model with two categorical responses (`y1` and `y2`) is specified;
- `responsesFormula = NULL`
all the columns in the data except the "id" and "time" columns are used as responses to estimate the mixed LM.

Missing responses are not allowed.

Value

Returns an object of class 'LMmixed' (see [LMmixed-class](#)).

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

References

Bartolucci F., Pandolfi S., Pennoni F. (2017) LMest: An R Package for Latent Markov Models for Longitudinal Categorical Data, *Journal of Statistical Software*, **81**(4), 1-38.

Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
## Not run:

# Example based on criminal data

data(data_criminal_sim)
data_criminal_sim <- data.frame(data_criminal_sim)

# Estimate mixed LM model for females

responsesFormula <- lmestFormula(data = data_criminal_sim,
                                response = "y")$responsesFormula

# fit mixed LM model only for females
out <- lmestMixed(responsesFormula = responsesFormula,
                  index = c("id", "time"),
                  k1 = 2,
                  k2 = 2,
                  data = data_criminal_sim[data_criminal_sim$sex == 2,])

out
summary(out)

## End(Not run)
```

lmestSearch

Search for the global maximum of the log-likelihood

Description

Function that searches for the global maximum of the log-likelihood of different models and selects the optimal number of states.

Usage

```
lmestSearch(responsesFormula = NULL, latentFormula = NULL,
            data, index, k,
            version = c("categorical", "continuous"),
            weights = NULL, nrep = 2, tol1 = 10^-5,
            tol2 = 10^-10, out_se = FALSE, miss.imp = FALSE, seed = NULL, ...)
```

Arguments

responsesFormula	a symbolic description of the model to fit. A detailed description is given in the ‘Details’ section of lmest
latentFormula	a symbolic description of the model to fit. A detailed description is given in the ‘Details’ section of lmest
data	a data.frame in long format
index	a character vector with two elements, the first indicating the name of the unit identifier, and the second the time occasions
k	a vector of integer values for the number of latent states
weights	an optional vector of weights for the available responses
version	type of responses for the LM model: "categorical" and "continuous"
nrep	number of repetitions of each random initialization
tol1	tolerance level for checking convergence of the algorithm in the random initializations
tol2	tolerance level for checking convergence of the algorithm in the last deterministic initialization
out_se	to compute the information matrix and standard errors (FALSE is the default option)
miss.imp	Only for continuous responses: how to deal with missing values (TRUE for imputation through the imp.mix function, FALSE for missing at random assumption)
seed	an integer value with the random number generator
...	additional arguments to be passed to functions lmest or lmestCont

Details

The function combines deterministic and random initializations strategy to reach the global maximum of the model log-likelihood. It uses one deterministic initialization (`start=0`) and a number of random initializations (`start=1`) proportional to the number of latent states. The tolerance level is set equal to 10^{-5} . Starting from the best solution obtained in this way, a final run is performed (`start=2`) with a default tolerance level equal to 10^{-10} .

Missing responses are allowed according to the model to be estimated.

Value

Returns an object of class 'LMsearch' with the following components:

<code>out.single</code>	Output of every LM model estimated for each number of latent states given in input
<code>Aic</code>	Values the Akaike Information Criterion for each number of latent states given in input
<code>Bic</code>	Values of the Bayesian Information Criterion for each number of latent states given in input
<code>lkv</code>	Values of log-likelihood for each number of latent states given in input.

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

References

Pennoni, F., Pandolfi, S. and Bartolucci, F. (2025). LMest: An R Package for Estimating Generalized Latent Markov Models, *The R Journal*, **16**(4) 74-101.

Bartolucci F., Pandolfi S. and Pennoni F. (2017) LMest: An R Package for Latent Markov Models for Longitudinal Categorical Data, *Journal of Statistical Software*, **81**(4), 1-38.

Bartolucci, F., Farcomeni, A. and Pennoni, F. (2013) *Latent Markov Models for Longitudinal Data*, Chapman and Hall/CRC press.

Examples

```
### Example with data on drug use in wide format

data("data_drug")
long <- data_drug[,-6]

# add labels referred to the identifier

long <- data.frame(id = 1:nrow(long),long)

# reshape data from the wide to the long format

long <- reshape(long,direction = "long",
                idvar = "id",
                varying = list(2:ncol(long)))

out <- lmestSearch(data = long,
                  index = c("id","time"),
                  version = "categorical",
                  k = 1:3,
                  weights = data_drug[,6],
                  modBasic = 1,
                  seed = 123)
```

```

out
summary(out$out.single[[3]])

## Not run:

### Example with data on self rated health

# LM model with covariates in the measurement model

data("data_SRHS_long")
SRHS <- data_SRHS_long[1:1000,]

# Categories rescaled to vary from 1 ("poor") to 5 ("excellent")

SRHS$srhs <- 5 - SRHS$srhs

out1 <- lmestSearch(data = SRHS,
                    index = c("id","t"),
                    version = "categorical",
                    responsesFormula = srhs ~ -1 +
                    I(gender - 1) +
                    I( 0 + (race == 2) + (race == 3)) +
                    I(0 + (education == 4)) +
                    I(0 + (education == 5)) + I(age - 50) +
                    I((age-50)^2/100),
                    k = 1:2,
                    out_se = TRUE,
                    seed = 123)

summary(out1)
summary(out1$out.single[[2]])

## End(Not run)

```

LMlatent-class	Class 'LMlatent'
----------------	------------------

Description

An S3 class object created by [lmest](#) for Latent Markov (LM) model with covariates in the latent model.

Value

lk	maximum log-likelihood
Be	estimated array of the parameters affecting the logit for the initial probabilities
Ga	estimated array of the parameters affecting the logit for the transition probabilities
Piv	estimate of initial probability matrix. The first state is used as reference category when param = "multilogit"

PI	estimate of transition probability matrices. State u is used as reference category when paramLatent = "multilogit"
Psi	estimate of conditional response probabilities (mb x k x r)
np	number of free parameters
k	optimal number of latent states
aic	value of the Akaike Information Criterion for model selection
bic	value of the Bayesian Information Criterion for model selection
lkv	log-likelihood trace at every step of the EM algorithm
n	number of observations in the data
TT	number of time occasions
paramLatent	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
sePsi	standard errors for the conditional response matrix
seBe	standard errors for Be
seGa	standard errors for Ga
Lk	vector containing the values of the log-likelihood of the LM model with each k (latent states)
Bic	vector containing the values of the BIC for each k
Aic	vector containing the values of the AIC for each k
V	array containing the posterior distribution of the latent states for each response configuration and time occasion
Ul	matrix containing the predicted sequence of latent states by the local decoding method
S	array containing the available response configurations
yv	vector of frequencies of the available configurations
Pmarg	matrix containing the marginal distribution of the latent states
call	command used to call the function
data	Data frame given in input

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

See Also

[lmest](#)

LMlatentcont-class Class 'LMlatentcont'

Description

An S3 class object created by [lmestCont](#) for the Latent Markov (LM) model for continuous responses in long format with covariates in the latent model.

Value

lk	maximum log-likelihood
Be	estimated array of the parameters affecting the logit for the initial probabilities
Ga	estimated array of the parameters affecting the logit for the transition probabilities
Mu	estimate of conditional means of the response variables
Si	estimate of var-cov matrix common to all states
np	number of free parameters
k	optimal number of latent states
aic	value of the Akaike Information Criterion for model selection
bic	value of the Bayesian Information Criterion for model selection
lkv	log-likelihood trace at every step
n	number of observations in the data
TT	number of time occasions
paramLatent	type of parametrization for the transition probabilities ("multilogit" = standard multinomial logit for every row of the transition matrix, "difflogit" = multinomial logit based on the difference between two sets of parameters)
seMu	standard errors for the conditional means
seSi	standard errors for the var-cov matrix
seBe	standard errors for Be
seGa	standard errors for Ga
sc	score vector
J	information matrix
PI	estimate of transition probability matrices
Piv	estimate of initial probability matrix
Lk	vector containing the values of the log-likelihood of the LM model with each k (latent states)
Bic	vector containing the values of the BIC of the LM model with each k (latent states)
Aic	vector containing the values of the AIC of the LM model with each k (latent states)

V	array containing the posterior distribution of the latent states for each units and time occasion
U1	matrix containing the predicted sequence of latent states by the local decoding method
Pmarg	matrix containing the marginal distribution of the latent states
call	command used to call the function
data	data frame given in input

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

See Also

[lmestCont](#)

LMmanifest-class	Class 'LMmanifest'
------------------	--------------------

Description

An S3 class object created by [lmest](#) for Latent Markov (LM) model with covariates in the measurement model.

Value

mu	vector of cut-points
al	support points for the latent states
be	estimate of the vector of regression parameters
si	sigma of the AR(1) process (mod = "FM")
rho	parameter vector for AR(1) process (mod = "FM")
la	vector of initial probabilities
PI	transition matrix
lk	maximum log-likelihood
np	number of parameters
k	optimal number of latent states
aic	value of the Akaike Information Criterion
bic	value of Bayesian Information Criterion
n	number of observations in the data
TT	number of time occasions

modManifest	for LM model with covariates on the manifest model: "LM" = Latent Markov with stationary transition, "FM" = finite mixture model where a mixture of AR(1) processes is estimated with common variance and specific correlation coefficients
sebe	standard errors for the regression parameters β
selrho	standard errors for logit type transformation of ρ
J1	information matrix
V	array containing the posterior distribution of the latent states for each units and time occasion
PRED1	prediction of the overall latent effect
S	array containing the available response configurations
yv	vector of frequencies of the available configurations
Pmarg	matrix containing the marginal distribution of the latent states
Lk	vector containing the values of the log-likelihood of the LM model with each k (latent states)
Bic	vector containing the values of the BIC for each k
Aic	vector containing the values of the AIC for each k
call	command used to call the function
data	data frame given in input

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

See Also

[lmest](#)

LMmanifestcont-class *Class* 'LMmanifestcont'

Description

An S3 class object created by [lmestCont](#) for Latent Markov (LM) model for continuous responses in long format with covariates in the measurement model.

Value

Al	support points for the latent states
Be	estimate of the vector of regression parameters
Si	estimate of var-cov matrix common to all states
piv	vector of initial probabilities

Pi	transition matrix
lk	maximum log-likelihood
np	number of parameters
k	optimal number of latent states
aic	value of the Akaike Information Criterion
bic	value of Bayesian Information Criterion
n	number of observations in the data
TT	number of time occasions
modBasic	model on the transition probabilities (0 for time-heter., 1 for time-homog., from 2 to (TT-1) partial homog. of that order)
lkv	log-likelihood trace at every step
seAl	standard errors for the support points Al
seBe	standard errors regression parameters Be
sepiv	standard errors for the initial probabilities
sePi	standard errors for the transition probabilities
seSi	standard errors for the var-cov matrix
Lk	vector containing the values of the log-likelihood of the LM model for each k (latent states)
Np	vector containing the number of parameters for each k (latent states)
Bic	vector containing the values of the BIC for each k
Aic	vector containing the values of the AIC for each k
J	information matrix
sc	score vector
V	array containing the posterior distribution of the latent states for each units and time occasion
U1	matrix containing the predicted sequence of latent states by the local decoding method
Pmarg	matrix containing the marginal distribution of the latent states
call	command used to call the function
data	data frame given in input

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni

See Also

[lmestCont](#)

LMmixed-class

Class 'LMmixed'

Description

An S3 class object created by [lmestMixed](#) for the mixed latent Markov (LM) models for categorical data in long format.

Value

la	estimate of the mass probability vector (distribution of the random effects)
Piv	estimate of initial probabilities
Pi	estimate of transition probability matrices
Psi	estimate of conditional response probabilities
lk	maximum log-likelihood
W	posterior probabilities of the random effect
np	number of free parameters
k1	number of support points (latent classes) of the latent variable defining the un-observed clusters
k2	number of support points (latent states) of the latent variable defining the first-order Markov process
bic	value of the Akaike Information Criterion for model selection
aic	value of the Akaike Information Criterion for model selection
n	number of observations in the data
TT	number of time occasions
sela	standard errors for la
sePiv	estimate of initial probability matrix
sePi	standard errors for the transition probabilities
sePsi	standard errors for the conditional response matrix
call	command used to call the function
data	the input data

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Penzoni, Alessio Farcomeni, Alessio Serafini

See Also

[lmestMixed](#)

long2matrices

From data in the long format to data in array format

Description

Function that transforms data in the long format to data in array format.

Usage

```
long2matrices(id, time = NULL, X = NULL, Y)
```

Arguments

id	vector of subjects id
time	vector of time occasions
X	matrix of covariates in long format
Y	matrix of responses in long format

Value

XX	array of covariates (n x TT x nc)
YY	array of responses (n x TT x r)

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
# Example based on SRHS data

# load SRHS data
data(data_SRHS_long)
dataSRHS <- data_SRHS_long[1:1600,]
head(dataSRHS)
X <- cbind(dataSRHS$gender-1, dataSRHS$race == 2 | dataSRHS$race == 3,
dataSRHS$education == 4, dataSRHS$education == 5, dataSRHS$age-50,
(dataSRHS$age-50)^2/100)
Y <- dataSRHS$srhs
res <- long2matrices(dataSRHS$id, X = X, Y = Y)
```

long2wide

*From data in the long format to data in the wide format***Description**

Function that transforms data in the long format to data in the wide format.

Usage

```
long2wide(data, nameid, namet, colx, coly, aggr = T, full = 999)
```

Arguments

data	matrix of data
nameid	name of the id column
namet	name of the t column
colx	vector of the names of the columns of the covariates
coly	vector of the names of the columns of the responses
aggr	if wide aggregated format is required
full	number to use for missing data

Value

listid	list of id for every unit
listt	list of the time occasions
data_wide	data in wide format
XX	array of the covariates
YY	array of the responses
freq	vector of the corresponding frequencies

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
# Example based on criminal data
# load criminal data
data(data_criminal_sim)
# consider only the first 1000 records to shorten time
out <- long2wide(data_criminal_sim[1:1000,], "id", "time", "sex",
  c("y1", "y2", "y3", "y4", "y5", "y6", "y7", "y8", "y9", "y10"), aggr = TRUE, full = 999)
```

matrices2long	<i>From data in array format to data in long format</i>
---------------	---

Description

Function to convert data with array format in data with long format.

Usage

```
matrices2long(Y, X1 = NULL, X2 = NULL)
```

Arguments

Y	array of responses (n x TT x r)
X1	array of covariates (n x TT x nc1)
X2	array of covariates (n x TT x nc2)

Details

Y, X1 and X2 must have the same number of observations.

Value

Returns a data.frame with data in long format. The first column indicates the name of the unit identifier, and the second column indicates the time occasions.

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

Examples

```
### Example with data on self rated health

data(data_SRHS_long)
SRHS <- data_SRHS_long[1:1600,]

# Covariates

X <- cbind(SRHS$gender-1,
           SRHS$race == 2 | SRHS$race == 3,
           SRHS$education == 4,
           SRHS$education == 5,
           SRHS$age-50,
           (SRHS$age-50)^2/100)

# Responses

Y <- SRHS$srhs
```

```
res <- long2matrices(SRHS$id, X = X, Y = Y)

long <- matrices2long(Y = res$YY, X1 = res$XX)
```

MCbasic-class	Class 'MCbasic'
---------------	-----------------

Description

An S3 class object created by [lmestMc](#) function for the Markov chain (MC) model without covariates.

Value

lk	maximum log-likelihood
piv	estimate of initial probability vector
Pi	estimate of transition probability matrices
np	number of free parameters
aic	value of the Akaike Information Criterion for model selection
bic	value of the Bayesian Information Criterion for model selection
Fy	estimated marginal distribution of the response variable at each time occasion
n	number of observations in the data
TT	number of time occasions
modBasic	model on the transition probabilities: default 0 for time-heterogeneous transition matrices, 1 for time-homogeneous transition matrices, 2 for partial time homogeneity based on two transition matrices one from 2 to (TT-1) and the other for TT
sepiv	standard errors for the initial probabilities
sePi	standard errors for the transition probabilities
call	command used to call the function
data	data frame given in input

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

See Also

[lmestMc](#)

MCcov-class

Class 'MCcov'

Description

An S3 class object created by [lmestMc](#) function for Markov chain (MC) model for categorical responses in long format with covariates.

Value

lk	maximum log-likelihood
Be	estimated array of the parameters affecting the logit for the initial probabilities
Ga	estimated array of the parameters affecting the logit for the transition probabilities
np	number of free parameters
aic	value of the Akaike Information Criterion (AIC) for model selection
bic	value of the Bayesian Information Criterion (BIC) for model selection
n	number of observations in the data
TT	number of time occasions
seBe	standard errors for Be
seGa	standard errors for Ga
Piv	estimate of initial probability matrix
PI	estimate of transition probability matrices
call	command used to call the function
data	data frame given in input

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

See Also

[lmestMc](#)

mc_multinom

*Estimate MC model with constraints***Description**

Function that estimates Markov chain model with suitable constraints on the transition matrix.

Usage

```
mc_multinom(formula, data, baseline = c("initial", "central"),
            model_int = c("all", "const", "dist1", "dist2", "dist3", "two",
                          "symm", "rsymm", "diff"),
            model_cov = c("all", "const", "dist1", "dist2", "dist3", "two",
                          "symm", "rsymm", "diff"),
            formula_init = NULL, reltol = 10^-10, output = FALSE)
```

Arguments

formula	A model formula specifying the response variable and the covariates affecting the transition probabilities. The response variable must be numeric, coded consecutively from 1 to k, where k is the number of observed states. See the ‘Details’ section for the specification of the covariates
data	A balanced data frame in long format. The first two required variables are id, identifying subjects, and t, identifying time occasions. Subject identifiers must be consecutive integers from 1 to the number of subjects; for each subject the time occasions must be the consecutive integers from 1 to the number of occasions available for that subject, which must be at least two; the rows must be ordered by subject and, within each subject, by time occasion. Missing values are not allowed in the variables entering formula and formula_init
baseline	Character string specifying the reference category in the multinomial logit parameterization for the transition probabilities. With "initial", the transition towards the first state is used as the reference category for each row of the transition matrix. With "central", the self-transition is used as the reference category for each row of the transition matrix.
model_int	Character string specifying the constraint structure for the intercepts of the transition logits. See design_matrices for the available options and their interpretation.
model_cov	Character string specifying the constraint structure for the regression coefficients associated with the transition covariates. See design_matrices for the available options and their interpretation
formula_init	Optional formula specifying the covariates affecting the initial probabilities. If NULL, the covariates specified in formula are also used for the initial probabilities
reltol	Positive numeric value specifying the relative convergence tolerance used in the Newton–Raphson iterations for the initial and transition components of the log-likelihood

output	Logical value. If TRUE, subject-specific initial and transition probability arrays are returned in addition to the parameter estimates
--------	--

Details

The covariates are included in the model through `model.matrix`, so that factors are automatically coded by means of dummy variables and transformations of the covariates may be specified directly in the formula, as in `I(age - 50)` or `I((age - 50)^2/100)`. The model always includes an intercept and only one response variable is allowed. Covariates affecting the initial probabilities are specified through the separate argument `formula_init`; when this is `NULL`, the covariates in `formula` are used for both the initial and the transition probabilities, whereas `formula_init = y ~ 1` gives initial probabilities that do not depend on covariates.

Value

An object of class "mc_multinom" containing the following components:

la	Estimated regression coefficients for the initial probabilities
psi	Estimated reduced vector of regression coefficients for the constrained transition logits
eta	Expanded vector of transition-logit parameters obtained by applying the design-matrix constraints to <code>psi</code>
lk	Total log-likelihood, equal to the sum of the initial-probability and transition-probability log-likelihoods
lk1	Log-likelihood contribution of the initial probabilities
lk2	Log-likelihood contribution of the transition probabilities
np	Number of free model parameters
aic	Akaike Information Criterion
bic	Bayesian Information Criterion
sela	Standard errors of the estimated coefficients <code>la</code>
sepsi	Standard errors of the estimated coefficients <code>psi</code>
call	Matched call used to fit the model
Piv	Matrix of subject-specific initial probabilities, with dimensions $n \times k$. Returned only when <code>output = TRUE</code>
PI	Array of subject-specific transition probabilities, with dimensions $k \times k \times n \times TT$, where <code>TT</code> is the maximum number of time occasions. Returned only when <code>output = TRUE</code>

Author(s)

Francesco Bartolucci and Silvia Pandolfi, University of Perugia (IT), Luca Brusa and Fulvia Pennoni, University of Milano-Bicocca (IT)

References

Bartolucci, F., Pandolfi, S., and Pennoni, F. (2026). Parsimonious parametrizations of transition matrices of Markov chain and hidden Markov models, *Annals of Operations Research*, 363, 233–266.

Examples

```
## Not run:
data("data_SRHS_long")
srhs <- data_SRHS_long

# Covariates
srhs$gender <- factor(
  srhs$gender,
  levels = c(1, 2),
  labels = c("male", "female")
)

srhs$race <- factor(
  srhs$race,
  levels = c(1, 2, 3),
  labels = c("white", "black", "others")
)

srhs$education <- factor(
  srhs$education,
  levels = 1:5,
  labels = c(
    "high school",
    "general educational diploma",
    "high school graduate",
    "some college",
    "college and above"
  )
)

srhs$age_c <- srhs$age - mean(srhs$age)

# 1 = poor, ..., 5 = excellent

srhs$srhs1 <- 6L - as.integer(srhs$srhs)

# Consecutive numeric identifiers and ordering by subject and time

srhs$id <- as.integer(factor(srhs$id))
srhs <- srhs[order(srhs$id, srhs$t), ]

# Select a small reproducible balanced sample for a fast example

set.seed(2026)

n_example <- 2000L
example_ids <- sample(unique(srhs$id), n_example)

srhs_example <- srhs[srhs$id %in% example_ids, , drop = FALSE]

srhs_example$id <- match(srhs_example$id, example_ids)
srhs_example <- srhs_example[order(srhs_example$id, srhs_example$t), ]
```

```

# Example 1: gender and age affect both initial and transition probabilities

mod_cov <- mc_multinom(
  srhs1 ~ gender + age_c,
  data = srhs_example,
  baseline = "central",
  model_int = "dist1",
  model_cov = "dist1",
  output = TRUE)

print(mod_cov)
summary(mod_cov)

# Average initial and transition probabilities

colMeans(mod_cov$Piv)
round(apply(mod_cov$PI[, , 2:max(srhs_example$t)], c(1, 2), mean),3)

# Example 2: covariates affect transitions only

mod_trans <- mc_multinom(
  srhs1 ~ gender + age_c,
  data = srhs_example,
  baseline = "central",
  model_int = "dist1",
  model_cov = "dist1",
  formula_init = srhs1 ~ 1)

print(mod_trans)
summary(mod_trans)

## End(Not run)

```

NLSYlong

National Longitudinal Survey of Youth data

Description

Longitudinal dataset in long format deriving from the National Longitudinal Survey of Youth with information about 581 individuals followed from 1990 to 1994.

Usage

```
data(NLSYlong)
```

Format

A data frame with 1743 observations on the following 12 variables.

momage mother's age at birth.

gender 0 if male, 1 if female.

childage child's age at first interview.

hispanic 1 if child is Hispanic, 0 if not.

black 1 if child is black, 0 if not.

momwork 1 if mother works, 0 if not.

married 1 if parents are married, 0 if not.

time occasion of observation.

anti a measure of antisocial behavior measured on a scale from 0 to 6.

self a measure of self-esteem measured on a scale from 6 to 24.

pov a time varying variable assuming value 1 if family is in poverty, 0 if not.

id subject id.

Source

<https://www.nlsinfo.org/content/cohorts/nlsy79>

References

The wide format of this dataset is downloadable from the package 'panelr'.

Examples

```
data(NLSYlong)
```

plot

Plots for Generalized Latent Markov Models

Description

Plots for outputs of LMest objects: LMbasic, LMbasiccont, LMlatent, LMlatentcont, and LMsearch

Usage

```
## S3 method for class 'LMbasic'
plot(x,
      what = c("modSel", "CondProb", "transitions", "marginal"),
      verbose=interactive(),...)
## S3 method for class 'LMlatent'
plot(x,
      what = c("modSel", "CondProb", "transitions", "marginal"),
```

```

                                verbose=interactive(),...)
## S3 method for class 'LMbasiccont'
plot(x,
      what = c("modSel", "density", "transitions", "marginal"),
      components, verbose=interactive(),...)
## S3 method for class 'LMlatentcont'
plot(x,
      what = c("modSel", "density", "transitions", "marginal"),
      components, verbose=interactive(),...)
## S3 method for class 'LMsearch'
plot(x,...)

```

Arguments

<code>x</code>	an object of class <code>LMbasic</code> , <code>LMlatent</code> , <code>LMbasiccont</code> , <code>LMlatentcont</code> or <code>LMsearch</code>
<code>what</code>	a string indicating the type of plot. A detailed description is provided in the ‘Details’ section.
<code>components</code>	An integer or a vector of integers specifying the components (latent states) to be selected for the "density" plot.
<code>verbose</code>	A logical controlling if a text progress bar is displayed during the fitting procedure. By default is TRUE if the session is interactive, and FALSE otherwise.
<code>...</code>	Unused argument.

Details

The type of plots are the following:

<code>"modSel"</code>	plot of values of the Bayesian Information Criterion and of the Akaike Information Criterion for model selection
<code>"CondProb"</code>	plot of the estimated conditional response probabilities
<code>"density"</code>	plot of the overall estimated density for continuous responses, with weights given by the estimated marginal distribution of the latent variable. For multivariate continuous responses a contour plot is provided. If the argument <code>components</code> is specified, the density plot for the selected components results
<code>"transitions"</code>	path diagram of the estimated transition probabilities
<code>"marginal"</code>	plot of the estimated marginal distribution of the latent variable

If argument `what` is not specified, a menu of choices is proposed in an interactive session.

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

Examples

```
## Not run:
### Plot of basic LM model

data("data_SRHS_long")
SRHS <- data_SRHS_long[1:2400,]

# Categories rescaled to vary from 0 ("poor") to 4 ("excellent")

SRHS$srhs <- 5 - SRHS$srhs

out <- lmest(responsesFormula = srhs ~ NULL,
             index = c("id", "t"),
             data = SRHS,
             k = 1:3,
             start = 1,
             modBasic = 1,
             seed = 123)

out
summary(out)
plot(out)

### Plot of basic LM model for continuous responses

data(data_long_cont)

out1 <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 1:5,
                  modBasic=1,
                  tol=10^-5)

plot(out1, what="modSel")

plot(out1, what="density")
plot(out1, what="density", components=c(1,3))

## End(Not run)
```

print

Print the output

Description

Given the output, it is written in a readable form

Usage

```
## S3 method for class 'LMbasic'
print(x, ...)
## S3 method for class 'LMbasiccont'
print(x, ...)
## S3 method for class 'LMlatent'
print(x, ...)
## S3 method for class 'LMlatentcont'
print(x, ...)
## S3 method for class 'LMmanifest'
print(x, ...)
## S3 method for class 'LMmixed'
print(x, ...)
## S3 method for class 'MCbasic'
print(x, ...)
## S3 method for class 'MCcov'
print(x, ...)
## S3 method for class 'LMsearch'
print(x, modSel = "BIC",...)
## S3 method for class 'mc_multinom'
print(x, ...)
## S3 method for class 'LM_cat_multinom'
print(x, ...)
```

Arguments

x	output from <code>lmest</code> , <code>lmestCont</code> , <code>lmestMixed</code> , <code>lmestMc</code> , and <code>mc_multinom</code>
modSel	a string indicating the model selection criteria: "BIC" (default) for Bayesian Information Criterion and "AIC" for Akaike Information Criterion
...	further arguments passed to or from other methods

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Luca Brusa, Alessio Farcomeni, Alessio Serafini

PSIDlong

Dataset about income dynamics

Description

Longitudinal dataset deriving from the Panel Study of Income Dynamics (PSID) from 1987 to 1993.

Usage

```
data(PSIDlong)
```

Format

A data frame with 1446 observations on the following variables.

`id` subject id.

time occasion of observation.

`Y1Fertility` indicating whether a woman had given birth to a child in a certain year 1 for "yes", 0 for "no".

`Y2Employment` indicating whether she was employed 1 for "yes", 0 for "no".

`X1Race` dummy variable equal to 1 for a "black" woman, 0 for "other".

`X2Age` age in 1986, rescaled by its maximum value.

`X3Age2` squared age.

`X4Education` number of years of schooling.

`X5Child1_2` number of children in the family aged between 1 and 2 years, referred to the previous year.

`X6Child3_5` number of children in the family aged between 3 and 5 years, referred to the previous year.

`X7Child6_13` number of children in the family aged between 6 and 13 years, referred to the previous year.

`X8Child14` number of children in the family aged over 14 years, referred to the previous year.

`X9Income` income of the husband (in dollars, referred to the previous year, divided by 1,000).

Source

<https://psidonline.isr.umich.edu>

References

This dataset is downloadable through the package ‘psidR’.

Examples

```
data(PSIDlong)
```

RLMSdat

Dataset about job satisfaction

Description

Longitudinal dataset deriving from the Russia Longitudinal Monitoring Survey (RLMS) about job satisfaction measured by an ordinal variable at seven different occasions with five categories, 1 for “absolutely satisfied”, 2 for “mostly satisfied”, 3 for “neutral”, 4 for “not very satisfied”, and 5 for “absolutely unsatisfied”.

Usage

```
data(RLMSdat)
```

Format

A data frame with 1718 observations on the following 7 variables.

IKSJQ reported job satisfaction at the 1st occasion

IKSJR reported job satisfaction at the 2nd occasion

IKSJS reported job satisfaction at the 3rd occasion

IKSJT reported job satisfaction at the 4th occasion

IKSJU reported job satisfaction at the 5th occasion

IKSJV reported job satisfaction at the 6th occasion

IKSJW reported job satisfaction at the 7th occasion

Source

<http://www.cpc.unc.edu/projects/rlms-hse>, <https://www.hse.ru/org/hse/rlms>

References

Russia Longitudinal Monitoring survey, RLMS-HSE, conducted by Higher School of Economics and ZAO "Demoscope" together with Carolina Population Center, University of North Carolina at Chapel Hill and the Institute of Sociology RAS

Examples

```
data(RLMSdat)
```

RLMSlong

Dataset about job satisfaction

Description

Longitudinal dataset in long format deriving from the Russia Longitudinal Monitoring Survey (RLMS, from Round XVII to Round XXIII, collected from 2008 to 2014) about job satisfaction measured by an ordinal variable at seven different occasions with five categories, 1 for “absolutely satisfied”, 2 for “mostly satisfied”, 3 for “neutral”, 4 for “not very satisfied”, and 5 for “absolutely unsatisfied”.

Usage

```
data(RLMSlong)
```

Format

A data frame with 1718 observations on the following 7 variables.

time occasion of observation.

id subject id.

rlms see [RLMSdat](#).

value reported job satisfaction at different time occasions coded as 1 for “absolutely satisfied”, 2 for “mostly satisfied”, 3 for “neutral”, 4 for “not very satisfied”, 5 for “absolutely unsatisfied”.

Source

<https://rlms-hse.cpc.unc.edu>, <https://www.hse.ru/org/hse/rlms>

References

Russia Longitudinal Monitoring survey, RLMS-HSE, conducted by Higher School of Economics and ZAO "Demoscope" together with Carolina Population Center, University of North Carolina at Chapel Hill and the Institute of Sociology RAS

Examples

```
data(RLMSlong)
```

se	<i>Standard errors</i>
----	------------------------

Description

Function to compute standard errors for the parameter estimates.

Usage

```
se(est, ...)
## S3 method for class 'LMbasic'
se(est, ...)
## S3 method for class 'LMbasiccont'
se(est, ...)
## S3 method for class 'LMlatent'
se(est, ...)
## S3 method for class 'LMlatentcont'
se(est, ...)
```

Arguments

est an object obtained from a call to [lmest](#) and [lmestCont](#)
 ... further arguments

Value

Standard errors for estimates in est object.

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

Examples

```
## Not run:

# LM model for categorical responses without covariates

data("data_SRHS_long")
SRHS <- data_SRHS_long[1:2400,]

# Categories rescaled to vary from 0 ("poor") to 4 ("excellent")

SRHS$srhs <- 5 - SRHS$srhs

out <- lmest(responsesFormula = srhs ~ NULL,
             index = c("id", "t"),
             data = SRHS,
             k = 3,
             modBasic = 1,
             out_se = FALSE)

out.se <- se(out)

out1 <- lmest(responsesFormula = srhs ~ NULL,
              index = c("id", "t"),
              data = SRHS,
              k = 3,
              modBasic = 1,
              out_se = TRUE)

out1.se <- se(out1)

# LM model for categorical responses with covariates on the latent model

out2 <- lmest(responsesFormula = srhs ~ NULL,
              latentFormula = ~
                I(gender - 1) +
                I(0 + (race == 2) + (race == 3)) +
                I(0 + (education == 4)) +
                I(0 + (education == 5)) +
                I(age - 50) + I((age-50)^2/100),
              index = c("id", "t"),
              data = SRHS,
              k = 2,
              paramLatent = "multilogit",
              start = 0)
```

```

out2.se <- se(out2)

# LM model for continous responses without covariates

data(data_long_cont)

out3 <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 3,
                  modBasic = 1,
                  tol = 10^-5)

out3.se <- se(out3)

# LM model for continous responses with covariates

out4 <- lmestCont(responsesFormula = Y1 + Y2 + Y3 ~ NULL,
                  latentFormula = ~ X1 + X2 | X1 + X2,
                  index = c("id", "time"),
                  data = data_long_cont,
                  k = 3,
                  output = TRUE)

out4.se <- se(out4)

## End(Not run)

```

search.model.LM

Search for the global maximum of the log-likelihood

Description

Function that searches for the global maximum of the log-likelihood of different models given a vector of possible number of states to try for.

The function is no longer maintained. Please look at [lmestSearch](#) function.

Usage

```
search.model.LM(version = c("basic", "latent", "manifest", "basic.cont", "latent.cont"),
                 kv, ..., nrep = 2, tol1 = 10^-5, tol2 = 10^-10, out_se = FALSE)
```

Arguments

version	model to be estimated ("basic" = basic LM model (est_lm_basic function); "latent" = LM model with covariates in the distribution of the latent process (est_lm_cov_latent function); "manifest" = LM model with covariates in the measurement model)
---------	--

	(<code>est_lm_cov_maifest</code> function), " <code>basic.cont</code> " = basic LM model for continuous outcomes (<code>est_lm_basic_cont</code> function); " <code>latent.cont</code> " = LM model for continuous outcomes with covariates in the distribution of the latent process (<code>est_lm_cov_latent_cont</code> function))
<code>kv</code>	vector of possible number of latent states
<code>...</code>	additional arguments to be passed based on the model to be estimated (see details)
<code>nrep</code>	number of repetitions of each random initialization
<code>tol1</code>	tolerance level for checking convergence of the algorithm in the random initializations
<code>tol2</code>	tolerance level for checking convergence of the algorithm in the last deterministic initialization
<code>out_se</code>	TRUE for computing information matrix and standard errors

Details

The function combines deterministic and random initializations strategy to reach the global maximum of the model log-likelihood. It uses one deterministic initialization (`start=0`) and a number of random initializations (`start=1`) proportional to the number of latent states. The tolerance level is set equal to 10^{-5} . Starting from the best solution obtained in this way, a final run is performed (`start=2`) with a default tolerance level equal to 10^{-10} .

Arguments in `...` depend on the model to be estimated. They match the arguments to be passed to functions `est_lm_basic`, `est_lm_cov_latent`, `est_lm_cov_manifest`, `est_lm_basic_cont`, or `est_lm_cov_latent_cont`.

Value

<code>out.single</code>	output of each single model (as from <code>est_lm_basic</code> , <code>est_lm_cov_latent</code> or <code>est_lm_cov_manifest</code>) for each <code>k</code> in <code>kv</code>
<code>aicv</code>	value of AIC index for each <code>k</code> in <code>kv</code>
<code>bicv</code>	value of BIC index for each <code>k</code> in <code>kv</code>
<code>lkv</code>	value of log-likelihood for each <code>k</code> in <code>kv</code>

Author(s)

Francesco Bartolucci, Silvia Pandolfi, University of Perugia (IT), <http://www.stat.unipg.it/bartolucci>

Examples

```
## Not run:

# example for est_lm_basic
data(data_drug)
data_drug <- as.matrix(data_drug)
S <- data_drug[,1:5]-1
yv <- data_drug[,6]
n <- sum(yv)
```

```
# Search Basic LM model

res <- search.model.LM("basic", kv = 1:4, S, yv, mod = 1)
summary(res)

## End(Not run)
```

summary

*Summary of LM fits***Description**

Summary methods

Usage

```
## S3 method for class 'LMbasic'
summary(object, ...)
## S3 method for class 'LMbasiccont'
summary(object, ...)
## S3 method for class 'LMlatent'
summary(object, ...)
## S3 method for class 'LMlatentcont'
summary(object, ...)
## S3 method for class 'LMmanifest'
summary(object, ...)
## S3 method for class 'LMmixed'
summary(object, ...)
## S3 method for class 'MCbasic'
summary(object, ...)
## S3 method for class 'MCcov'
summary(object, ...)
## S3 method for class 'LMsearch'
summary(object,...)
## S3 method for class 'mc_multinom'
summary(object,...)
```

Arguments

object	output from <code>lmest</code> , <code>lmestCont</code> , <code>lmestMixed</code> , <code>mc_multinom</code> , and <code>lmestMc</code>
...	further arguments passed to or from other methods

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Luca Brusa, Alessio Farcomeni, Alessio Serafini

summary.lmestData *Summary and plot of lmestData*

Description

Methods for lmestData object providing basic descriptive statistics (summary) and plots.

Usage

```
## S3 method for class 'lmestData'
summary(object, type = c("all", "cross", "year"),
        dataSummary = c("all", "responses", "manifest", "initial", "transition"),
        varType = rep("c", x$d), digits = getOption("digits"),
        maxsum = 10, maxobs = 20, ...)
## S3 method for class 'lmestData'
plot(x, typePlot = c("s", "sh"),
     dataPlots = c("all", "responses", "manifest", "initial", "transition"),
     ...)
## S3 method for class 'lmestData'
print(x, ...)
```

Arguments

object	an object of class lmestData
x	an object of class lmestData
type	type of summary to print. all prints a summary for each variable, and a summary for each variables by time. cross prints a summary for each variable. year prints a summary for each variable by time. The summary is adapted according to varType (By default is set to all)
dataSummary	a string indicating whether summary is returned: all for the entire data, responses for the responses, manifest for covariates on the manifest distribution, initial for the covariate affecting the initial probabilities, and transition for the covariates affecting the transition probabilities. (By default is set to all)
varType	a string vector of length equal to the number of variables, "c" for continuous and "d" for discrete, indicating which variables are continuous and which are discrete
digits	the number of significant digits
maxsum	an integer value indicating the maximum number of levels to print
maxobs	an integer value indicating the maximum number of observation in which the summary statistics are reported for each observation
typePlot	a string indicating the type of plot. "s" plots a scatterplot matrix. "sh" plots a scatterplot matrix with the histogram for each variable in the diagonal

dataPlots a string indicating whether the plot is returned: all for the entire data, responses
for the responses, manifest for covariates on the manifest distribution, initial
for the covariate affecting the initial probabilities, transition for the covariates
affecting the transition probabilities. (By default is set to all)

... further arguments

Author(s)

Francesco Bartolucci, Silvia Pandolfi, Fulvia Pennoni, Alessio Farcomeni, Alessio Serafini

Index

* datasets

- data_criminal_sim, [12](#)
- data_drug, [13](#)
- data_employment_sim, [14](#)
- data_heart_sim, [15](#)
- data_long_cont, [16](#)
- data_market_sim, [16](#)
- data_SRHS_long, [17](#)
- NLSYlong, [94](#)
- PSIDlong, [98](#)
- RLMSdat, [99](#)
- RLMSlong, [100](#)

bootstrap, [5](#), [7–9](#), [11](#)

bootstrap_lm_basic, [7](#)

bootstrap_lm_basic_cont, [8](#)

bootstrap_lm_cov_latent, [9](#)

bootstrap_lm_cov_latent_cont, [11](#)

data_criminal_sim, [12](#)

data_drug, [13](#)

data_employment_sim, [14](#)

data_heart_sim, [15](#)

data_long_cont, [16](#)

data_market_sim, [16](#)

data_SRHS_long, [17](#)

decoding, [18](#)

design_matrices, [20](#), [37](#), [39](#), [91](#)

draw, [21](#)

draw.LMbasic, [26](#)

draw.LMbasiccont, [27](#)

draw.LMlatent, [28](#)

draw.LMlatentcont, [30](#)

draw.LMmixed, [31](#)

draw_lm_basic, [26](#)

draw_lm_basic_cont, [27](#)

draw_lm_cov_latent, [28](#)

draw_lm_cov_latent_cont, [29](#)

draw_lm_mixed, [31](#)

est_lm_basic, [32](#)

est_lm_basic_cont, [34](#)

est_LM_cat_multinom, [36](#)

est_lm_cov_latent, [40](#)

est_lm_cov_latent_cont, [42](#)

est_lm_cov_manifest, [44](#)

est_lm_mixed, [47](#)

est_mc_basic, [48](#)

est_mc_cov, [50](#)

LMbasic-class, [52](#)

LMbasiccont-class, [53](#)

LMest (LMest-package), [3](#)

lmest, [3–5](#), [32](#), [40](#), [44](#), [52](#), [53](#), [54](#), [62](#), [64](#), [65](#), [67–69](#), [77](#), [79](#), [80](#), [82](#), [83](#), [98](#), [101](#), [105](#)

LMest-package, [3](#)

lmestCont, [3–5](#), [23](#), [34](#), [42](#), [53](#), [54](#), [56](#), [60](#), [64](#), [65](#), [67–69](#), [77](#), [81–84](#), [98](#), [101](#), [105](#)

lmestData, [64](#)

lmestDecoding, [4](#), [18](#), [66](#)

lmestFormula, [62](#), [68](#)

lmestMc, [3](#), [4](#), [48](#), [50](#), [68](#), [69](#), [71](#), [89](#), [90](#), [98](#), [105](#)

lmestMixed, [3](#), [4](#), [47](#), [67–69](#), [74](#), [85](#), [98](#), [105](#)

lmestSearch, [4](#), [76](#), [103](#)

LMlatent-class, [79](#)

LMlatentcont-class, [81](#)

LMmanifest-class, [82](#)

LMmanifestcont-class, [83](#)

LMmixed-class, [85](#)

long2matrices, [86](#)

long2wide, [87](#)

matrices2long, [88](#)

mc_multinom, [20](#), [21](#), [91](#), [98](#), [105](#)

MCbasic-class, [89](#)

MCCov-class, [90](#)

model.matrix, [92](#)

NLSYlong, [94](#)

plot, [95](#)

plot.lmestData(summary.lmestData), [106](#)

print, [4](#), [97](#)

print.lmestData(summary.lmestData), [106](#)

PSIDlong, [98](#)

RLMSdat, [99](#), [101](#)

RLMSlong, [100](#)

se, [4](#), [101](#)

search.model.LM, [103](#)

summary, [4](#), [105](#)

summary.lmestData, [106](#)