

Package ‘fMRIttools’

September 28, 2026

Type Package

Title Routines for Common fMRI Processing Tasks

Version 0.8.3

Maintainer Amanda Mejia <mandy.mejia@gmail.com>

Description Supports fMRI (functional magnetic resonance imaging) analysis tasks including reading in 'CIFTI', 'GIFTI' and 'NIFTI' data, temporal filtering, nuisance regression, and aCompCor (anatomical Components Correction) (Muschelli et al. (2014) <[doi:10.1016/j.neuroimage.2014.03.028](https://doi.org/10.1016/j.neuroimage.2014.03.028)>).

Depends R (>= 3.5.0)

License GPL-3

Encoding UTF-8

Imports stats, matrixStats

Suggests ciftiTools, corpcor, expm, gifti, knitr, rmarkdown, robustbase, pesel, RNifti, oro.nifti, gsignal, testthat (>= 3.0.0), covr, fda, quantreg, graphics, grDevices, RColorBrewer, viridis, ggcorrplot, ggplot2, scales

URL <https://github.com/mandymejia/fMRIttools>

BugReports <https://github.com/mandymejia/fMRIttools/issues>

Config/roxygen2/version 8.1.0

NeedsCompilation no

Author Amanda Mejia [aut, cre] (ORCID: <<https://orcid.org/0000-0002-4312-8974>>),
Damon Pham [aut] (ORCID: <<https://orcid.org/0000-0001-7563-4727>>),
Mark Fiecas [ctb]

Repository CRAN

Date/Publication 2026-09-28 14:30:02 UTC

Contents

all_binary	3
all_integers	4
as.matrix_ifni	4
bandstop_filter	5
carpetplot	6
carpetplot_stack	7
colCenter	8
color_palette	8
CompCor	9
CompCor_HCP	11
coordlist_to_vol	13
crop_vol	14
dct_bases	14
dct_convert	15
despike_3D	16
dice_coef	16
dilate_mask_vol	17
dual_reg	18
dual_reg_parac	20
erode_mask_vol	21
expand_RPs	22
flags2spikes	23
fMRITools	23
fsl_bptf	24
hat_matrix	25
infer_format_ifni	25
infer_format_ifni_vec	26
is_1	26
is_constant	27
is_integer	27
is_posNum	28
mask_BOLD	28
mat2UT	29
match_exactly	29
match_input	30
match_nets	31
mean_squares	32
Mode	32
norm_BOLD	33
nuisance_regression	34
pad_vol	35
PCA	36
pct_sig	37
plot_FC	37
plot_FC_gg	38
read_nifti	39

scale_design_mat	40
scale_med	41
scale_timeseries	41
sign_flip	42
skew_pos	43
sum_neighbors_vol	43
temporal_filter	44
unmask_mat	45
unvec_mat	45
unvec_vol	46
UT2mat	47
validate_design_mat	48
var_decomp	48
vox_locations	49

Index	50
--------------	-----------

all_binary	<i>All binary?</i>
------------	--------------------

Description

Check if a data vector or matrix is all zeroes and ones. Option to also accept logical values.

Usage

```
all_binary(x, logical_ok = TRUE)
```

Arguments

- | | |
|------------|---|
| x | The data vector or matrix |
| logical_ok | Is a logical vector or matrix also acceptable? Default: TRUE. |

Value

Logical. Is x binary data?

all_integers	<i>All integers?</i>
--------------	----------------------

Description

Check if a data vector or matrix is all integers.

Usage

```
all_integers(x)
```

Arguments

x	The data vector or matrix
---	---------------------------

Value

Logical. Is x all integers?

as.matrix_ifti	<i>Convert CIFTI, NIFTI, or GIFTI input to $T \times V$ matrix</i>
----------------	---

Description

Convert CIFTI, NIFTI, or GIFTI input to a $T \times V$ matrix by reading it in with the corresponding package and then separating the data from the metadata. Also works with the intermediate R objects created from reading these files: "xifti" objects from ciftiTools, "gifti" objects from gifti, "nifti" or "niftiExtension" objects from oro.nifti, and "niftiImage" objects from RNifti.

For CIFTI files, only intents supported by ciftiTools are supported: dscalar, dtseries, and dlabel. For NIFTI file or NIFTI-intermediate R objects, the data will be vectorized/masked.

Usage

```
as.matrix_ifti(
  x,
  meta = FALSE,
  sortSub = FALSE,
  TbyV = TRUE,
  verbose = FALSE,
  ...
)
```

Arguments

x	The object to coerce to a matrix
meta	Return metadata too? Default: FALSE.
sortSub	For CIFTI format input only. Sort subcortex by labels? Default: FALSE (sort by array index).
TbyV	Return the data matrix in $T \times V$ form? Default: TRUE. If FALSE, return in $V \times T$ form instead. Using this argument may be faster than transposing after the function call.
verbose	Print updates? Default: FALSE.
...	If x is a file path, additional arguments to the function used to read in x can be specified here. For example, if x is a path to a CIFTI file, ... might specify which idx and brainstructures to read in.

Value

If !meta, x as a matrix. If meta, a list of length two: the first entry is x as a matrix, and the second entry is the metadata of x.

bandstop_filter	<i>Bandstop filter</i>
-----------------	------------------------

Description

Filter out frequencies within a given range using a Chebyshev Type II stopband. Essentially a convenience wrapper for the [cheby2](#) function.

Usage

```
bandstop_filter(X, TR, f1, f2, Rs = 20)
```

Arguments

X	A numeric matrix, with each column being a timeseries to apply the stopband filter. For fMRI data, X should be T timepoints by V brain locations.
TR	The time step between adjacent rows of x, in seconds
f1, f2	The frequency limits for the filter, in Hz. $f1 < f2$
Rs	The amount of attenuation of the stopband ripple, in dB

Value

The filtered data

Examples

```
if (requireNamespace("gsignal", quietly=TRUE)) {
  n_voxels = 1e4
  n_timepoints = 100
  X = cbind(arma.sim(n=100, list(ar=.6)), arma.sim(n=100, list(ar=.6)))
  Y = bandstop_filter(X, .72, .31, .43)
}
```

carpetplot

Carpetplot

Description

Plot a matrix with `graphics::image`. For fMRI data, this is the "carpetplot" or grayplot coined by (Power, 2017). The `graphics` and `grDevices` packages are required.

Usage

```
carpetplot(
  x,
  qcut = 0.1,
  fname = NULL,
  center = TRUE,
  scale = FALSE,
  colors = "gray255",
  sortSub = TRUE,
  ...
)
```

Arguments

- | | |
|----------------------------|---|
| <code>x</code> | The $T \times V$ numeric data matrix, or a "xifti" object. In the plot, the T index will increase from left to right, and the V will increase from top to bottom. |
| <code>qcut</code> | Sets blackpoint at the <code>qcut</code> quantile, and the whitepoint at the $1 - \text{qcut}$ quantile. Default: <code>.1</code> . This is equivalent to setting the color range between the 10% and 90% quantiles. The quantiles are computed across the entire data matrix after any centering or scaling. |
| <code>fname</code> | Must be between 0 and <code>.49</code> . If <code>0</code> or <code>NULL</code> (default), do not clamp the data values. |
| <code>center, scale</code> | A <code>.pdf</code> (highly recommended) or <code>.png</code> file path to write the carpetplot to. If <code>NULL</code> (default), return the plot directly instead of writing a file. |
| <code>center, scale</code> | Center and scale the data? If <code>x</code> is fMRI data which has not otherwise been centered or scaled, it is recommended to center but not scale it (default). |
| <code>colors</code> | Colors will be assigned from the lowest to the highest data value, after any clamping of the data values by <code>qcut</code> . |

"gray255" (default) will use a grayscale color ramp from black to white. Otherwise, this should be a character vector of color names to use.

Colors will be assigned from the lowest to the highest data value, after any clamping of the data values by `qcut`.

sortSub	If x is a "xifti" object with subcortical data, should the voxels be sorted by structure alphabetically? Default: TRUE.
...	Additional arguments to pdf or png, such as width and height.

Value

The image or NULL, invisibly if a file was written.

References

- Power, J. D. A simple but useful way to assess fMRI scan qualities. NeuroImage 154, 150-158 (2017).

carpetplot_stack	<i>Stacked carpetplot</i>
------------------	---------------------------

Description

Stacks carpetplots on top of one another by rbinding the matrices.

Usage

```
carpetplot_stack(
  x_list,
  center = TRUE,
  scale = FALSE,
  qcut = 0.1,
  match_scale = TRUE,
  nsep = 0,
  ...
)
```

Arguments

x_list	List of data matrices
center, scale	Center and scale the data? If x is fMRI data which has not otherwise been centered or scaled, it is recommended to center but not scale it (default).
qcut	Sets blackpoint at the qcut quantile, and the whitepoint at the 1-qcut quantile. Default: .1. This is equivalent to setting the color range between the 10% and 90% quantiles. The quantiles are computed across the entire data matrix after any centering or scaling.
match_scale	Must be between 0 and .49. If 0 or NULL (default), do not clamp the data values.
nsep	Match the scales of the carpetplots? Default: TRUE.
nsep	Equivalent number of data locations for size of gap between carpetplots. Default: zero (no gap).
...	Additional arguments to carpetplot

Value

NULL, invisibly

colCenter	<i>Center matrix columns</i>
-----------	------------------------------

Description

Efficiently center columns of a matrix. (Faster than `base::scale`.)

Usage

```
colCenter(X)
```

Arguments

X The data matrix. Its columns will be centered.

Value

The centered data

color_palette	<i>Color palette</i>
---------------	----------------------

Description

Color palettes for fMRI data analysis tasks

Usage

```
color_palette(pal = "Beach")
```

Arguments

pal "Beach" (default; blue to white to red), "Sand" (white to red), or "Water" (white to blue).

Value

A data.frame with two columns: "col" has the hex code of color, and "val" has the placement of colors between zero and one.

CompCor

*Anatomical CompCor***Description**

The aCompCor algorithm for denoising fMRI data using noise ROIs data

Usage

```
CompCor(
  X,
  ROI_data = "infer",
  ROI_noise = NULL,
  noise_nPC = 5,
  noise_erosion = NULL,
  center = TRUE,
  scale = TRUE,
  nuisance = NULL
)
```

Arguments

- X** Wide numeric data matrix (*T* observations by *V* variables, $T \ll V$). For example, if *X* represents an fMRI run, *T* should be the number of timepoints and *V* should be the number of brainordinate vertices/voxels.
- Or, a 4D array or NIFTI or file path to a NIFTI (*I* by *J* by *K* by *T* observations), in which case ROI_data must be provided. (The vectorized data will be *T* timepoints by *V_{in-mask}* voxels)
- Or, a ciftiTools "xifti" object or a file path to a CIFTI (The vectorized data will be *T* timepoints by *V_{left+right+subgrayordinates}*).
- ROI_data** Indicates the data ROI. Allowed arguments depend on *X*:
- If *X* is a matrix, this must be a length *V* logical vector, where the data ROI is indicated by TRUE values. If "infer" (default), all columns of *X* will be included in the data ROI (rep(TRUE, *V*)).
- If *X* is an array or NIFTI, this must be either a vector of values to expect for out-of-mask voxels in *X*, or a (file path to a) 3D NIFTI. In the latter case, each of the volume dimensions should match the first three dimensions of *X*. Voxels in the data ROI should be indicated by TRUE and all other voxels by FALSE. If "infer" (default), will be set to c(0, NA, NaN) (include all voxels which are not constant 0, NA, or NaN).
- If *X* is a "xifti" this must be the brainstructures argument to ciftiTools::read_cifti. If "infer" (default), brainstructures will be set to "all" (use both left and right cortex vertices, and subcortical voxels).
- If NULL, the data ROI will be empty. This is useful for obtaining just the noise ROI, if the data and noise are located in separate files.

ROI_noise	Indicates the noise ROIs for aCompCor. Should be a list where each entry corresponds to a distinct noise ROI. The names of the list should be the ROI names, e.g. "white_matter" and "csf". The expected formats of the list entries depends on X: For all types of X, ROI_noise entries can be a matrix of noise ROI data. The matrix should have T rows, with each column being a data location's timeseries. If X is a matrix, entries can also indicate a noise ROI within X. These entries must be a length V logical vector with TRUE values indicating locations in X within that noise ROI. Since the ROIs must not overlap, the masks must be mutually exclusive with each other, and with ROI_data. If X is an array or NIFTI, entries can also indicate a noise ROI within X. These entries must be a logical array or (file path to) a 3D NIFTI with the same spatial dimensions as X, and with TRUE values indicating voxels inside the noise ROI. Since the ROIs must not overlap, the masks must be mutually exclusive with each other, and with ROI_data. (If X is a "xifti", entries must be data matrices, since no grayordinate locations in X are appropriate noise ROIs).
noise_nPC	The number of principal components to compute for each noise ROI. Alternatively, values between 0 and 1, in which case they will represent the minimum proportion of variance explained by the PCs used for each noise ROI. The smallest number of PCs will be used to achieve this proportion of variance explained. Should be a list or numeric vector with the same length as ROI_noise. It will be matched to each ROI based on the name of each entry, or if the names are missing, the order of entries. If it is an unnamed vector, its elements will be recycled. Default: 5 (compute the top 5 PCs for each noise ROI).
noise_erosion	The number of voxel layers to erode the noise ROIs by. Should be a list or numeric vector with the same length as ROI_noise. It will be matched to each ROI based on the name of each entry, or if the names are missing, the order of entries. If it is an unnamed vector, its elements will be recycled. Default: NULL, which will use a value of 0 (do not erode the noise ROIs). Note that noise erosion can only be performed if the noise ROIs are volumetric.
center, scale	Center the columns of the noise ROI data by their medians, and scale by their MADs? Default: TRUE for both. Note that this argument affects the noise ROI data and not the data that is being cleaned with aCompCor. Centering and scaling of the data being cleaned can be done after this function call.
nuisance	Nuisance signals to regress from each data column in addition to the noise ROI PCs. Should be a T by N numeric matrix where N represents the number of nuisance signals. To not perform any nuisance regression set this argument to NULL, $\emptyset$, or FALSE. Default: NULL.

Details

First, the principal components (PCs) of each noise region of interest (ROI) are calculated. For each ROI, voxels are centered and scaled (can be disabled with the arguments center and scale), and then the PCs are calculated via the singular value decomposition.

Next, aCompCor is performed to remove the shared variation between the noise ROI PCs and each location in the data. This is accomplished by a nuisance regression using a design matrix with the

noise ROI PCs, any additional regressors specified by nuisance, and an intercept term. (To detrend the data and perform aCompCor in the same regression, nuisance can be set to DCT bases obtained with the function [dct_bases](#).)

Value

A list with entries "data", "noise", and potentially "ROI_data".

The entry "data" will be a $V \times T$ matrix where each row corresponds to a data location (if it was originally an array, the locations will be voxels in spatial order). Each row will be a time series with each noise PC regressed from it. This entry will be NULL if there was no data.

The entry "noise" is a list of noise PC scores, their corresponding variance, and their ROI mask, for each noise ROI.

If the data ROI is not all TRUE, the entry "ROI_data" will have the ROI mask for the data.

References

- Behzadi, Y., Restom, K., Liao, J. & Liu, T. T. A component based noise correction method (CompCor) for BOLD and perfusion based fMRI. *NeuroImage* 37, 90-101 (2007).
- Muschelli, J. et al. Reduction of motion-related artifacts in resting state fMRI using aCompCor. *NeuroImage* 96, 22-35 (2014).

See Also

CompCor_HCP

CompCor_HCP

Anatomical CompCor for HCP NIFTI and CIFTI data

Description

Wrapper to [CompCor](#) for HCP-format data. Can be used to clean the surface-based CIFTI data with aCompCor using the noise PCs and ROIs calculated from the NIFTI fMRI data and NIFTI mask. Can also be used to just obtain the noise PCs and ROIs without performing aCompCor, if the CIFTI data is not provided.

Usage

```
CompCor_HCP(
  nii,
  nii_labels,
  ROI_noise = c("wm_cort", "csf"),
  noise_nPC = 5,
  noise_erosion = NULL,
  idx = NULL,
  cii = NULL,
  brainstructures = c("left", "right"),
```

```

center = TRUE,
scale = TRUE,
DCT = 0,
nuisance_too = NULL,
verbose = FALSE
)

```

Arguments

<code>nii</code>	<i>I</i> by <i>J</i> by <i>K</i> by <i>T</i> NIFTI object or array (or file path to the NIFTI) which contains whole-brain data, including the noise ROIs. In the HCP, the corresponding file is e.g. <code>"../Results/rfMRI_REST1_LR/rfMRI_REST1_LR.nii.gz"</code>
<code>nii_labels</code>	<i>I</i> by <i>J</i> by <i>K</i> NIFTI object or array (or file path to the NIFTI) which contains the corresponding labels to each voxel in <code>nii</code> . Values should be according to this table: https://surfer.nmr.mgh.harvard.edu/fswiki/FsTutorial/AnatomicalROI/FreeSurferColorLUT . In the HCP, the corresponding file is <code>"ROIs/Atlas_wmparc.2.nii.gz"</code> .
<code>ROI_noise</code>	A list of numeric vectors. Each entry should represent labels in <code>nii_labels</code> belonging to a single noise ROI, named by that entry's name. Or, this can be a character vector of at least one of the following: <code>"wm_cort"</code> (cortical white matter), <code>"wm_cblm"</code> (cerebellar white matter), <code>"csf"</code> (cerebrospinal fluid). In the latter case, these labels will be used: <code>"wm_cort" c(3000:4035, 5001, 5002)</code> <code>"wm_cblm" c(7, 46)</code> <code>"csf" c(4, 5, 14, 15, 24, 31, 43, 44, 63, 250, 251, 252, 253, 254, 255))</code> These default ROIs are based on this forum post: https://www.mail-archive.com/hcp-users@humanconnectome.org/msg00931.html Default: <code>c("wm_cort", "csf")</code>
<code>noise_nPC</code>	The number of principal components to compute for each noise ROI. Alternatively, values between 0 and 1, in which case they will represent the minimum proportion of variance explained by the PCs used for each noise ROI. The smallest number of PCs will be used to achieve this proportion of variance explained. Should be a list or numeric vector with the same length as <code>ROI_noise</code> . It will be matched to each ROI based on the name of each entry, or if the names are missing, the order of entries. If it is an unnamed vector, its elements will be recycled. Default: 5 (compute the top 5 PCs for each noise ROI).
<code>noise_erosion</code>	The number of voxel layers to erode the noise ROIs by. Should be a list or numeric vector with the same length as <code>ROI_noise</code> . It will be matched to each ROI based on the name of each entry, or if the names are missing, the order of entries. If it is an unnamed vector, its elements will be recycled. Default: <code>NULL</code> , which will use a value of 0 (do not erode the noise ROIs).
<code>idx</code>	A numeric vector indicating the timepoints to use, or <code>NULL</code> (default) to use all <code>idx</code> . (Indexing begins with 1, so the first timepoint has index 1 and the last has the same index as the length of the scan.)
<code>cii</code>	<code>"xifti"</code> (or file path to the CIFTI) from which the noise ROI components will be regressed. In the HCP, the corresponding file is e.g. <code>"../Results/rfMRI_REST1_LR/rfMRI_REST1_LR."</code> If not provided, only the noise components will be returned (no data will be cleaned).

brainstructures	Choose among "left", "right", and "subcortical". Default: c("left", "right") (cortical data only)
center, scale	Center the columns of the data by median, and scale the columns of the data by MAD? Default: TRUE for both. Affects both X and the noise data. center also applies to nuisance_too so if it is FALSE, nuisance_too must already be centered.
DCT	Add DCT bases to the nuisance regression? Use an integer to indicate the number of cosine bases. Use 0 (default) to forgo detrending. The data must be centered, either before input or with center.
nuisance_too	A matrix of nuisance signals to add to the nuisance regression. Should have T rows. NULL to not add additional nuisance regressors (default).
verbose	Should occasional updates be printed? Default: FALSE.

Value

The noise components, and if `cii` is provided, the cleaned surface-based data as a "xifti" object.

References

- Behzadi, Y., Restom, K., Liao, J. & Liu, T. T. A component based noise correction method (CompCor) for BOLD and perfusion based fMRI. *NeuroImage* 37, 90-101 (2007).
- Muschelli, J. et al. Reduction of motion-related artifacts in resting state fMRI using aCompCor. *NeuroImage* 96, 22-35 (2014).

See Also

CompCor

coordlist_to_vol	<i>Convert coordinate list to 3D array</i>
------------------	--

Description

Converts a sparse coordinate list to its non-sparse volumetric representation.

Usage

```
coordlist_to_vol(coords, fill = FALSE)
```

Arguments

coords	The sparse coordinate list. Should be a "data.frame" or matrix with voxels along the rows and three or four columns. The first three columns should be integers indicating the spatial coordinates of the voxel. If the fourth column is present, it will be the value used for that voxel. If it is absent, the value will be TRUE or 1 if fill is not one of those values, and FALSE or 0 if fill is. The data type will be the same as that of fill. The fourth column must be logical or numeric.
fill	Logical or numeric fill value for the volume. Default: FALSE.

Value

The volumetric data

crop_vol	<i>Crop a 3D array</i>
----------	------------------------

Description

Remove empty (zero-valued) edge slices from a 3D array.

Usage

```
crop_vol(x)
```

Arguments

x	The numeric 3D array to crop.
---	-------------------------------

Value

A list of length two: "data", the cropped array, and "padding", the number of slices removed from each edge of each dimension.

dct_bases	<i>Generate cosine bases for the DCT</i>
-----------	--

Description

https://en.wikipedia.org/wiki/Discrete_cosine_transform "DCT II"

Usage

```
dct_bases(T_, n)
```

Arguments

T_	Length of timeseries
n	Number of cosine bases

Value

Matrix with cosine bases along columns

dct_convert	<i>DCT and frequency conversion</i>
-------------	-------------------------------------

Description

Convert between number of DCT bases and Hz of highpass filter

Usage

```
dct_convert(T_, TR, n = NULL, f = NULL)

dct2Hz(T_, TR, n)

Hz2dct(T_, TR, f)
```

Arguments

T_	Length of timeseries (number of timepoints)
TR	TR of the fMRI scan, in seconds (the time between timepoints)
n	Number of cosine bases
f	Hz of highpass filter

Details

Provide either n or f to calculate the other.

If only the total length of the scan is known, you can set that to TR and use T_=1.

$$f = n / (2 * T_*TR)$$

Value

If n was provided, the highpass filter cutoff (Hz) is returned. Otherwise, if f was provided, the number of cosine bases is returned. The result should be rounded before passing to [dct_bases](#)

despike_3D	<i>3dDespike from AFNI</i>
------------	----------------------------

Description

Identify and interpolate outliers. See [the AFNI documentation for 3dDespike](#) for additional information.

Usage

```
despike_3D(Yt, c1 = 2.5, c2 = 4)
```

Arguments

Yt	The data vector.
c1	spike threshold. Default: 2.5.
c2	upper range of the acceptable deviation from the fit. Default: 4.

Examples

```
if (requireNamespace("fda", quietly=TRUE) && requireNamespace("quantreg", quietly=TRUE)) {
  y <- rnorm(99) + cos(seq(99)/15)*3
  y[20] <- 20
  despike_3D(y)
}
```

dice_coef	<i>Dice coefficient</i>
-----------	-------------------------

Description

Dice coefficient

Usage

```
dice_coef(X, Y = NULL)
```

Arguments

X, Y	Numeric vectors, or matrices with locations along the rows and networks along the columns. Dice coefficients will be calculated between each pair of networks between X and Y; if Y is not provided, X will be used for Y.
------	--

Value

The Dice coefficients in a $Q_x \times Q_y$ matrix, where Q_x is the number of columns in X, Q_y is the number of columns in Y, and element ij is the Dice coefficient between network i of X and network j of Y.

dilate_mask_vol	<i>Dilate 3D mask</i>
-----------------	-----------------------

Description

Dilate a volumetric mask by a certain number of voxel layers. For each layer, any out-of-mask voxel adjacent to at least one in-mask voxel is added to the mask.

Usage

```
dilate_mask_vol(vol, n_dilate = 1, out_of_mask_val = NA, new_val = 1)
```

Arguments

vol	The 3D array to dilate. The mask to dilate is defined by all values not in out_of_mask_val.
n_dilate	The number of layers to dilate the mask by. Default: 1.
out_of_mask_val	A voxel is not included in the mask if and only if its value is in this vector. Default: NA. If vol is simply a logical array with TRUE values for in-mask voxels, use out_of_mask_val=FALSE.
new_val	Value for voxels newly added to the mask. Default: 1. If vol is simply a logical array with TRUE values for in-mask voxels, use new_val=1.

Details

Diagonal voxels are not considered adjacent, i.e. the voxel at (0,0,0) is not adjacent to the voxels at (1,1,0) or (1,1,1), although it is adjacent to (1,0,0).

Value

The dilated vol. It is the same as vol, but dilated voxels are replaced with new_val.

dual_reg

*Dual Regression***Description**

Perform dual regression.

Usage

```
dual_reg(
  BOLD,
  GICA,
  drop_first = 0,
  nuisance = NULL,
  scrub = NULL,
  TR = NULL,
  hpf = 0.01,
  lpf = NULL,
  scale_by = c("mean", "sd", "FUN", "none"),
  scale_sm_FWHM = 4,
  scale_sm_xifti = NULL,
  scale_FUN = NULL,
  GSR = FALSE
)
```

Arguments

BOLD	Subject-level fMRI data matrix ($V \times T$). Rows will be centered.
GICA	Group-level independent components ($V \times Q$)
drop_first	(Optional) Number of volumes to drop from the start of each BOLD session. Default: 0.
nuisance	(Optional) Nuisance matrix to regress from the BOLD data. Nuisance regression is performed in a simultaneous regression with any spike regressors from scrub and DCT bases from hpf. Note that the nuisance matrix should be provided with timepoints matching the original BOLD irregardless of drop_first. Nuisance matrices will be truncated automatically if drop_first>0.
scrub	(Optional) Numeric vector of integers giving the indices of volumes to scrub from the BOLD data. (List the volumes to remove, not the ones to keep.) Scrubbing is performed within a nuisance regression by adding a spike regressor to the nuisance design matrix for each volume to scrub. Note that indices are counted beginning with the first index in the BOLD session irregardless of drop_first. The indices will be adjusted automatically if drop_first>0.

TR	The temporal resolution of the data, i.e. the time between volumes, in seconds. TR is required for detrending with hpf.
hpf, lpf	The frequencies at which to apply temporal filtering to the data during pre-processing, in Hertz. Set either to NULL to disable. Default: 0.01 Hz high-pass filter, and NULL for the lowpass filter (disabled). Highpass filtering is accomplished by nuisance regression of discrete cosine transform (DCT) bases. Lowpass filtering is accomplished by a non-linear filter: fsl_bptf . Note the TR argument is required for temporal filtering. If TR is not provided, an error is raised if hpf and lpf have been set.
scale_by	Scale the BOLD at each voxel based on either its "mean" (default), its "sd", or do not scale ("none"). Mean scaling cannot be used if the BOLD have already been de-measured.
scale_sm_FWHM	Full width at half maximum (FWHM) for smoothing the estimates of scale across brain locations (see scale_by), to reduce the variance of the estimates. Set to 0 to disable smoothing, or Inf for "global" smoothing (estimate and use one measure of scale across the entire brain). Otherwise, for "local" smoothing, this should be a positive number. Default: 4.
scale_sm_xifti	Required only for "local" smoothing of the scale estimates with CIFTI data (see scale_sm_FWHM). To smooth the scale estimates, provide a "xifti" object aligned with BOLD. If no "xifti" object is provided (default) smoothing must be skipped.
scale_FUN	If scale_by is "FUN", this function is used to compute the scaling measure from BOLD, after it has been centered (and so after dropping any volumes, and applying nuisance regression, scrubbing, and temporal filtering). Otherwise, ignored.
GSR	Center BOLD across columns (each image)? This is equivalent to performing global signal regression. Default: FALSE.

Details

Row centering is required and column centering is not recommended. Scaling and detrending depend on user preference.

Value

A list containing the subject-level independent components $\mathbf{S}$ ($Q \times V$), and subject-level mixing matrix $\mathbf{A}$ ($T \times Q$).

Examples

```
nT <- 30
nV <- 400
nQ <- 7
mU <- matrix(rnorm(nV*nQ), nrow=nV)
mS <- mU %*% diag(seq(nQ, 1)) %*% matrix(rnorm(nQ*nT), nrow=nQ)
BOLD <- mS + rnorm(nV*nT, sd=.05) + 10
GICA <- mU
dual_reg(BOLD=BOLD, GICA=mU, scale_sm_FWHM=Inf, TR=.72)
```

dual_reg_parcc

*Dual Regression for parcel data***Description**

Perform multiple regression for parcel data.

Usage

```
dual_reg_parcc(
  BOLD,
  parcc,
  parcc_vals,
  drop_first = 0,
  nuisance = NULL,
  scrub = NULL,
  TR = NULL,
  hpf = 0.01,
  lpf = NULL,
  scale_by = c("mean", "sd", "FUN", "none"),
  scale_sm_FWHM = 4,
  scale_sm_xiffti = NULL,
  scale_FUN = NULL,
  GSR = FALSE
)
```

Arguments

BOLD	fMRI numeric data matrix ($V \times T$)
parcc	The parcellation as an integer vector.
parcc_vals	The parcel values (keys) in desired order, e.g. <code>sort(unique(parcc))</code> .
drop_first	(Optional) Number of volumes to drop from the start of each BOLD session. Default: 0.
nuisance	(Optional) Nuisance matrix to regress from the BOLD data. Nuisance regression is performed in a simultaneous regression with any spike regressors from <code>scrub</code> and DCT bases from <code>hpf</code> . Note that the nuisance matrix should be provided with timepoints matching the original BOLD regardless of <code>drop_first</code> . Nuisance matrices will be truncated automatically if <code>drop_first > 0</code> .
scrub	(Optional) Numeric vector of integers giving the indices of volumes to scrub from the BOLD data. (List the volumes to remove, not the ones to keep.) Scrubbing is performed within a nuisance regression by adding a spike regressor to the nuisance design matrix for each volume to scrub. Note that indices are counted beginning with the first index in the BOLD session regardless of <code>drop_first</code> . The indices will be adjusted automatically if <code>drop_first > 0</code> .

TR	The temporal resolution of the data, i.e. the time between volumes, in seconds. TR is required for detrending with hpf.
hpf, lpf	The frequencies at which to apply temporal filtering to the data during pre-processing, in Hertz. Set either to NULL to disable. Default: 0.01 Hz high-pass filter, and NULL for the lowpass filter (disabled). Highpass filtering is accomplished by nuisance regression of discrete cosine transform (DCT) bases. Lowpass filtering is accomplished by a non-linear filter: fsl_bptf . Note the TR argument is required for temporal filtering. If TR is not provided, an error is raised if hpf and lpf have been set.
scale_by	Scale the BOLD at each voxel based on either its "mean" (default), its "sd", or do not scale ("none"). Mean scaling cannot be used if the BOLD have already been de-meant.
scale_sm_FWHM	Full width at half maximum (FWHM) for smoothing the estimates of scale across brain locations (see scale_by), to reduce the variance of the estimates. Set to 0 to disable smoothing, or Inf for "global" smoothing (estimate and use one measure of scale across the entire brain). Otherwise, for "local" smoothing, this should be a positive number. Default: 4.
scale_sm_xifti	Required only for "local" smoothing of the scale estimates with CIFTI data (see scale_sm_FWHM). To smooth the scale estimates, provide a "xifti" object aligned with BOLD. If no "xifti" object is provided (default) smoothing must be skipped.
scale_FUN	If scale_by is "FUN", this function is used to compute the scaling measure from BOLD, after it has been centered (and so after dropping any volumes, and applying nuisance regression, scrubbing, and temporal filtering). Otherwise, ignored.
GSR	Center BOLD across columns (each image)? This is equivalent to performing global signal regression. Default: FALSE.

Value

A list containing the subject-level independent components $\mathbf{S}$ ($Q \times V$), and subject-level mixing matrix $\mathbf{A}$ ($T \times Q$).

erode_mask_vol	<i>Erode 3D mask</i>
----------------	----------------------

Description

Erode a volumetric mask by a certain number of voxel layers. For each layer, any in-mask voxel adjacent to at least one out-of-mask voxel is removed from the mask.

Usage

```
erode_mask_vol(vol, n_erosion = 1, out_of_mask_val = NA)
```

Arguments

vol	The 3D array to erode. The mask to erode is defined by all values not in out_of_mask_val.
n_erosion	The number of layers to erode the mask by. Default: 1.
out_of_mask_val	A voxel is not included in the mask if and only if its value is in this vector. The first value of this vector will be used to replace eroded voxels. Default: NA. If vol is simply a logical array with TRUE values for in-mask voxels, use out_of_mask_val=FALSE.

Details

Diagonal voxels are not considered adjacent, i.e. the voxel at (0,0,0) is not adjacent to the voxels at (1,1,0) or (1,1,1), although it is adjacent to (1,0,0).

Value

The eroded vol. It is the same as vol, but eroded voxels are replaced with out_of_mask_val[1].

expand_RPs	<i>Expand realignment parameters (RPs)</i>
------------	--

Description

Compute the squares, differences, and square differences of each RP timeseries.

Usage

```
expand_RPs(RPs)
```

Arguments

RPs	A $T \times N$ numeric matrix, where T is the number of timepoints and N is the number of RPs (typically six) to expand.
-----	--

Value

A $T \times 4N$ numeric matrix, with the first N columns being the original RPs, the next N being the differences, the next N being the squares, and the last N being the squared differences.

flags2spikes	<i>Flags to nuisance spikes</i>
--------------	---------------------------------

Description

Convert flagged volumes to corresponding one-hot encoded vectors which can be used for nuisance regression.

Usage

```
flags2spikes(flags, n_time)
```

Arguments

flags	Numeric vector of integers indicating the indices of the flagged volumes. Or, a logical vector of length n_time where TRUE values indicate the flagged volumes.
n_time	The length of the vectors to obtain. For nuisance regression, this is the length of the BOLD data. The highest index in flags should not exceed n_time.

Value

A numeric matrix of ones and zeroes. The number of rows will be n_time and the number of columns will be the number of flags. Each column will have a 1 at the flag index, and 0 elsewhere.

fMRItools	<i>fMRItools: Routines for Common fMRI Processing Tasks</i>
-----------	---

Description

See `help(package="fMRItools")` for a list of functions.

Author(s)

Maintainer: Amanda Mejia <mandy.mejia@gmail.com> ([ORCID](#))

Authors:

- Amanda Mejia <mandy.mejia@gmail.com> ([ORCID](#))
- Damon Pham <damondpham@gmail.com> ([ORCID](#))

Other contributors:

- Mark Fiecas <mfiecas@umn.edu> [contributor]

See Also

Useful links:

- <https://github.com/mandymejia/fMRItools>
- Report bugs at <https://github.com/mandymejia/fMRItools/issues>

fsl_bptf	bptf function from FSL
----------	------------------------

Description

Copy of bptf highpass filter from FSL. The results are very similar but not identical.

Usage

```
fsl_bptf(orig_data, HP_sigma = 2000, LP_sigma = NULL)
```

Arguments

orig_data	$T \times V$ data matrix whose columns will be detrended
HP_sigma	The frequency parameter, sigma, for the highpass filter. Recommended HP_sigma: $1/(2*f*TR)$, where f is the cutoff filter in Hz and TR is the time resolution in seconds (See jiscmail link in function description). Default: 2000.
LP_sigma	The frequency parameter, sigma, for the lowpass filter. Recommended LP_sigma: $1/(18*f*TR)$.

Details

Sources: https://cpb-us-w2.wpmucdn.com/sites.udel.edu/dist/7/4542/files/2016/09/fsl_temporal_filt-15sywxn.m <https://github.com/rordenlab/niimath/blob/master/src/coreFLT.c#L1935> <https://www.jiscmail.ac.uk/cgi-bin/webadmin?A2=FSL;f6fd75a6.1709>

Value

The data with detrended columns

References

- Jenkinson, M., Beckmann, C. F., Behrens, T. E. J., Woolrich, M. W. & Smith, S. M. FSL. NeuroImage 62, 782-790 (2012).

Examples

```
fsl_bptf(matrix(rnorm(700), nrow=100))
```

hat_matrix	<i>Hat matrix</i>
------------	-------------------

Description

Get the hat matrix from a design matrix.

Usage

```
hat_matrix(design)
```

Arguments

design	The T by Q design matrix
--------	------------------------------

Details

Uses the QR decomposition.

Value

The T by T hat matrix

Examples

```
hat_matrix(cbind(seq(100), 1))
```

infer_format_ifti	<i>Infer fMRI data format</i>
-------------------	-------------------------------

Description

Infer fMRI data format

Usage

```
infer_format_ifti(BOLD, verbose = FALSE)
```

Arguments

BOLD	The fMRI data
verbose	Print the format? Default: FALSE.

Value

A length-two vector. The first element indicates the format: "CIFTI" file path, "xifti" object, "GIFTI" file path, "gifti" object, "NIFTI" file path, "nifti" object, "RDS" file path, or "data". The second element indicates the sub-format if relevant; i.e. the type of CIFTI or GIFTI file/object.

infer_format_ifti_vec	<i>Infer fMRI data format for several inputs</i>
-----------------------	--

Description

Vectorized version of `infer_format_ifti`. Expects all inputs to have the same format.

Usage

```
infer_format_ifti_vec(BOLD, verbose = FALSE)
```

Arguments

BOLD	The vector of fMRI data, expected to be of one format
verbose	Print the format? Default: FALSE.

Details

Raises an error if the elements of BOLD do not share the same format.

Value

A length-two vector. The first element indicates the format: "CIFTI" file path, "xifti" object, "GIFTI" file path, "gifti" object, "NIFTI" file path, "nifti" object, "RDS" file path, or "data". The second element indicates the sub-format if relevant; i.e. the type of CIFTI or GIFTI file/object.

is_1	<i>Is this object the expected data type, and length one?</i>
------	---

Description

Is this object the expected data type, and length one?

Usage

```
is_1(x, dtype = c("numeric", "logical", "character"))
```

Arguments

x	The value to check
dtype	The data type. Default: "numeric". Also can be "logical" or "character"

Value

TRUE if x is dtype and length one.

is_constant	<i>Is this numeric vector constant?</i>
-------------	---

Description

Is this numeric vector constant?

Usage

```
is_constant(x, TOL = 1e-08)
```

Arguments

x	The numeric vector
TOL	minimum range of x to be considered non-constant. Default: 1e-8

Value

Is x constant?

is_integer	<i>Is this an integer?</i>
------------	----------------------------

Description

Is this an integer?

Usage

```
is_integer(x, nneg = FALSE)
```

Arguments

x	The putative integer
nneg	Require $x \geq 0$ (non-negative) too?

Value

Logical indicating whether x is an integer

is_posNum	<i>Is this object a positive number? (Or non-negative)</i>
-----------	--

Description

Is this object a positive number? (Or non-negative)

Usage

```
is_posNum(x, zero_ok = FALSE)
```

Arguments

x	The value to check
zero_ok	Is a value of zero ok?

Value

Logical indicating if x is a single positive or non-negative number

mask_BOLD	<i>Create a mask based on vertices that are invalid</i>
-----------	---

Description

Create a mask based on vertices that are invalid

Usage

```
mask_BOLD(BOLD, meanTol = -Inf, varTol = 1e-06, verbose = TRUE)
```

Arguments

BOLD	A $V \times T$ numeric matrix. Each row is a location.
meanTol, varTol	Tolerance for mean and variance of each data location. Locations which do not meet these thresholds are masked out of the analysis. Defaults: -Inf for meanTol (ignore), and 1e-6 for varTol.
verbose	Print messages counting how many locations are removed?

Value

A logical vector indicating valid vertices

mat2UT

*Matrix to Upper Triangular Vector***Description**

Returns the vectorized upper triangle of a square matrix

Usage

```
mat2UT(x, diag = FALSE)
```

Arguments

x	A square matrix
diag	Get the diagonal values too? Default: FALSE

Value

The vectorized upper triangle of x.

match_exactly

*Do these character vectors match exactly?***Description**

Checks if a user-defined character vector matches an expected character vector. That is, they share the same lengths and entries in the same order. For vectors of the same lengths, the result is `all(a == b)`.

Usage

```
match_exactly(
  user,
  expected,
  fail_action = c("message", "warning", "stop", "nothing")
)
```

Arguments

user	Character vector of user input.
expected	Character vector of expected/allowed values.
fail_action	If any value in user could not be matched, or repeated matches occurred, what should happen? Possible values are "message" (default), "warning", "stop", and "nothing".

Details

Attributes are ignored.

Value

Logical. Do user and expected match?

match_input	<i>Match user inputs to expected values</i>
-------------	---

Description

Match each user input to an expected/allowed value. Raise a warning if either several user inputs match the same expected value, or at least one could not be matched to any expected value. ciftiTools uses this function to match keyword arguments for a function call. Another use is to match brainstructure labels ("left", "right", or "subcortical").

Usage

```
match_input(
  user,
  expected,
  fail_action = c("stop", "warning", "message", "nothing"),
  user_value_label = NULL
)
```

Arguments

user	Character vector of user input. These will be matched to expected using match.arg .
expected	Character vector of expected/allowed values.
fail_action	If any value in user could not be matched, or repeated matches occurred, what should happen? Possible values are "stop" (default; raises an error), "warning", and "nothing".
user_value_label	How to refer to the user input in a stop or warning message. If NULL, no label is used.

Value

The matched user inputs.

match_nets

*Find best matches for each network based on Dice overlap***Description**

For each network (map or parcel) in A, it finds the network in B with which it has the highest Dice coefficient. (Some networks in B will have zero matches, and some will have more than one.)

Usage

```
match_nets(A, B = "Yeo_7", B_zero_drop = TRUE, brainstructures = "existing")
```

Arguments

- A** The networks to find matches for. Can be a CIFTI file path, a "xifti" object, a numeric matrix (locations by networks, and can be continuous or binary), or a locations-length vector giving the network index each location belongs to.
- B** The networks to match to. Can be a CIFTI file path, a "xifti" object, a numeric matrix (locations by networks, and can be continuous or binary), a locations-length vector giving the network index each location belongs to, or the name of a parcellation included in ciftiTools. Default: "Yeo_7".
- B_zero_drop** If B is a parcellation (i.e. a vector of network indices), and the lowest parcel index is 0, drop that level? Sometimes the zero-valued parcel is used for the medial wall or other invalid locations. Default: TRUE. If FALSE, treat it as a candidate for matching just like all the other parcels.
- brainstructures** The brainstructures to use, if A and/or B are CIFTI data. Default: "existing" to use the brainstructures present in A (or in B if A is a matrix).

Details

If the resolutions of A and B differ, it will try to resample B to match the resolution of A.

Value

A numeric vector giving the indices of B networks that are the best matches for each network in A. `order(match_nets(A, B))` would give an indexing of A that rearranges its networks according to the order of networks in B.

mean_squares	<i>Compute mean squares from variance decomposition</i>
--------------	---

Description

Compute mean squares from variance decomposition

Usage

```
mean_squares(vd)
```

Arguments

vd	The variance decomposition
----	----------------------------

Value

The mean squares

Mode	<i>Mode of data vector</i>
------	----------------------------

Description

Get mode of a data vector. But use the median instead of the mode if all data values are unique.

Usage

```
Mode(x)
```

Arguments

x	The data vector
---	-----------------

Value

The mode

norm_BOLD	<i>Normalize BOLD data</i>
-----------	----------------------------

Description

Clean the data (scrubbing, detrending, nuisance regression, and temporal filtering in a simultaneous framework), then center it, then scale it, in that order.

Usage

```
norm_BOLD(
  BOLD,
  drop_first = 0,
  nuisance = NULL,
  scrub = NULL,
  TR = NULL,
  hpf = 0.01,
  lpf = NULL,
  center_rows = TRUE,
  center_cols = FALSE,
  scale_by = c("mean", "sd", "FUN", "none"),
  scale_sm_FWHM = 4,
  scale_sm_xifti = NULL,
  scale_sm_xifti_mask = NULL,
  scale_FUN = NULL,
  give_stats = FALSE
)
```

Arguments

BOLD	fMRI numeric data matrix ($V \times T$)
drop_first	(Optional) Number of volumes to drop from the start of each BOLD session. Default: 0.
nuisance	(Optional) Nuisance matrix to regress from the BOLD data. Nuisance regression is performed in a simultaneous regression with any spike regressors from scrub and DCT bases from hpf. Note that the nuisance matrix should be provided with timepoints matching the original BOLD regardless of drop_first. Nuisance matrices will be truncated automatically if drop_first>0.
scrub	(Optional) Numeric vector of integers giving the indices of volumes to scrub from the BOLD data. (List the volumes to remove, not the ones to keep.) Scrubbing is performed within a nuisance regression by adding a spike regressor to the nuisance design matrix for each volume to scrub. Note that indices are counted beginning with the first index in the BOLD session regardless of drop_first. The indices will be adjusted automatically if drop_first>0.

TR	The temporal resolution of the data, i.e. the time between volumes, in seconds. TR is required for detrending with hpf.
hpf, lpf	The frequencies at which to apply temporal filtering to the data during pre-processing, in Hertz. Set either to NULL to disable. Default: 0.01 Hz high-pass filter, and NULL for the lowpass filter (disabled). Highpass filtering is accomplished by nuisance regression of discrete cosine transform (DCT) bases. Lowpass filtering is accomplished by a non-linear filter: fsl_bptf . Note the TR argument is required for temporal filtering. If TR is not provided, an error is raised if hpf and lpf have been set.
center_rows, center_cols	Center BOLD data across rows (each data location's time series) or columns (each time point's image)? Default: TRUE for row centering, and FALSE for column centering.
scale_by	Scale the BOLD at each voxel based on either its "mean" (default), its "sd", or do not scale ("none"). Mean scaling cannot be used if the BOLD have already been de-meant.
scale_sm_FWHM	Full width at half maximum (FWHM) for smoothing the estimates of scale across brain locations (see scale_by), to reduce the variance of the estimates. Set to 0 to disable smoothing, or Inf for "global" smoothing (estimate and use one measure of scale across the entire brain). Otherwise, for "local" smoothing, this should be a positive number. Default: 4.
scale_sm_xifti	Required only for "local" smoothing of the scale estimates with CIFTI data (see scale_sm_FWHM). To smooth the scale estimates, provide a "xifti" object aligned with BOLD. If no "xifti" object is provided (default) smoothing must be skipped.
scale_sm_xifti_mask	For local smoothing of scale estimates, the data must be unmasked to be mapped back to the surface. So if the data are masked, provide the mask here.
scale_FUN	If scale_by is "FUN", this function is used to compute the scaling measure from BOLD, after it has been centered (and so after dropping any volumes, and applying nuisance regression, scrubbing, and temporal filtering). Otherwise, ignored.
give_stats	Return the intercept, residual SD estimates, and full design matrix from the nuisance regression? Default: FALSE

Value

Normalized BOLD data matrix ($V \times T$), or if give_stats, a list with three elements: the normed BOLD, the intercept estimate, and the residual SD estimate.

Description

Performs nuisance regression. Important note: the data and design matrix must both be centered, or an intercept must be included in the design matrix.

Usage

```
nuisance_regression(Y, design)
```

Arguments

`Y` The $T \times V$ or $V \times T$ data.
`design` The $T \times Q$ matrix of nuisance regressors.

Value

The data after nuisance regression.

Examples

```
Y <- matrix(rnorm(700), nrow=100)
design <- cbind(seq(100), 1)
nuisance_regression(Y, design)
```

pad_vol

Pad 3D Array

Description

Pad a 3D array by a certain amount in each direction, along each dimension. This operation is like the opposite of cropping.

Usage

```
pad_vol(x, padding, fill = NA)

uncrop_vol(x, padding, fill = NA)
```

Arguments

`x` A 3D array, e.g. `unvec_vol(xifti$data$subcort, xifti$meta$subcort$mask)`.
`padding` A 3×2 matrix indicating the number of slices to add at the beginning (first column) and end (second column) of each of dimension, e.g. `xifti$meta$subcort$mask_padding`.
`fill` Value to pad with. Default: NA.

Value

The padded array

Examples

```
x <- array(seq(24), dim=c(2,3,4))
y <- pad_vol(x, array(1, dim=c(3,2)), 0)
stopifnot(all(dim(y) == dim(x)+2))
stopifnot(sum(y) == sum(x))
z <- crop_vol(y)$data
stopifnot(identical(dim(x), dim(z)))
stopifnot(max(abs(z - x))==0)
```

PCA

*PCA for tall matrix***Description**

Efficient PCA for a tall matrix (many more rows than columns). Uses the SVD of the covariance matrix. The dimensionality of the result can be preset with `Q` or estimated with PESEL.

Usage

```
PCA(X, center = TRUE, Q = NULL, Q_max = 100, Vdim = 0)
```

Arguments

<code>X</code>	The tall numeric matrix for which to compute the PCA. For fMRI data, <code>X</code> should be <code>V</code> brain locations by <code>T</code> timepoints.
<code>center</code>	Center the columns of <code>X</code> ? Default: <code>TRUE</code> . Set to <code>FALSE</code> if already centered. Centered data is required to compute PCA.
<code>Q</code>	Number of latent dimensions to estimate. If <code>NULL</code> (default), estimated using PESEL (Sobczyk et al. 2020).
<code>Q_max</code>	Maximal number of principal components for automatic dimensionality selection with PESEL. Default: 100.
<code>Vdim</code>	Number of principal directions to obtain. Default: 0. Can also be "Q" to set equal to the value of <code>Q</code> . Note that setting this value less than <code>Q</code> does not speed up computation time, but does save on memory. Note that the directions will be with respect to <code>X</code> , not its covariance matrix.

Value

The SVD decomposition

Examples

```
U <- matrix(rnorm(900), nrow=300, ncol=3)
V <- matrix(rnorm(15), nrow=3, ncol=5)
PCA(U %*% V)
```

pct_sig	<i>Convert data values to percent signal.</i>
---------	---

Description

Convert data values to percent signal.

Usage

```
pct_sig(X, center = median, by = c("column", "all"))
```

Arguments

X	a T by N numeric matrix. The columns will be normalized to percent signal.
center	A function that computes the center of a numeric vector. Default: median. Other common options include mean and mode.
by	Should the center be measured individually for each "column" (default), or should the center be the same across "all" columns?

Value

X with its columns normalized to percent signal. (A value of 85 will represent a -15% signal change.)

plot_FC	<i>Plot FC</i>
---------	----------------

Description

Plot a functional connectivity matrix.

Usage

```
plot_FC(
  FC,
  zlim = c(-1, 1),
  diag_val = NULL,
  title = "FC matrix",
  cols = color_palette("Beach"),
  cleg_ticks_by = diff(zlim)/2,
  cleg_digits = NULL,
  labels = NULL,
  lines = NULL,
  lines_col = "black",
  lines_lwd = 1,
  cex = 0.8
)
```

Arguments

FC	The functional connectivity matrix, a square numeric matrix with values between -1 and 1.
zlim	The minimum and maximum range of the color scale. Default: <code>c(-1, 1)</code> . If in descending order, the color scale will be reversed.
diag_val	Set to NA for white, 1, or NULL (default) to not modify the diagonal values in FC.
title	(Optional) Plot title.
cols	Character vector of colors for the color scale. Default: <code>color_palette("Beach")</code> .
cleg_ticks_by	Spacing between ticks on the color legend. Default: <code>range(zlim)/2</code> .
cleg_digits	How many decimal digits for the color legend. Default: NULL to set automatically.
labels	A character vector of length <code>length(lines)+1</code> , giving row/column labels for the submatrices divided by lines. If NULL (default), do not add labels.
lines	Add lines to divide the FC matrix into submatrices? Default: NULL (do not draw lines). Set to "all" to delineate each individual row and column.
lines_col, lines_lwd	Color and line width of the lines. Default: black lines of width 1.
cex	Text size. Default: 0.8.

plot_FC_gg

Plot FC with ggplot2

Description

Plot a FC matrix.

Usage

```
plot_FC_gg(
  mat,
  colFUN = NULL,
  title = "FC Matrix",
  legTitle = "",
  group_divs = NULL,
  group_cols = RColorBrewer::brewer.pal(8, "Set2"),
  labs = NULL,
  uppertri_means = TRUE,
  divColor = "black",
  lim = 0.5,
  diagVal = 1,
  labs_margin_y = NULL,
  labs_margin_x = 0
)
```

Arguments

mat	The FC matrix
colFUN	A <code>scale_fill</code> function. If <code>NULL</code> , use a red-blue diverging palette if there are negative values in <code>mat</code> , and <code>viridis</code> ' <code>inferno</code> sequential palette otherwise.
title	The plot title. Default: "FC Matrix".
legTitle	The legend title. Default: "".
group_divs, group_cols	Split the FC matrix into groups of contiguous rows/columns? Use <code>group_divs</code> to indicate the index of the first element in each group. For example, if the groups are 1-8, 9-15, and 16 to 25, set <code>group_divs=c(1, 9, 16)</code> . Groups will be indicated by a color bar along the left and top sides of the plot. Use <code>group_cols</code> to change the colors. By default, <code>group_divs</code> is <code>NULL</code> (no groups).
labs	Labels to place along the y-axis? If <code>is.null(group_divs)</code> , this should be a character vector labeling each row of <code>mat</code> , or a dot dot dot. If <code>!is.null(group_divs)</code> , this may alternatively be a character vector labeling each group.
uppertri_means	Use the upper triangle of the FC matrix to show the mean of each group indicated by <code>group_divs</code> ? Default: <code>TRUE</code> . Has no effect if <code>group_divs</code> is <code>NULL</code> .
divColor	Color of group dividers and outline of the FC matrix. Default: "black".
lim	Length-two numeric vector indicating the limits for the color bar. Values beyond <code>lim</code> will be clipped. If <code>NULL</code> , the limits will be set based on the largest magnitude value in <code>mat</code> (no clipping). If length-one, the left limit will be 0 if there are no negative values, or <code>-lim</code> if there are. Default: <code>.5</code> .
diagVal	On-diagonal values will be set to this value. (<code>uppertri_means</code> are calculated before <code>diagVal</code> is used.)
labs_margin_y, labs_margin_x	Margin value for labels. For the y-axis, a value of <code>NULL</code> (default) will set the margin value adaptively depending on the size of the FC matrix such that the labels are almost flush with the y-axis. The default for the x-axis is <code>0</code> , which also results in labels almost flush with the x-axis.

Value

The plot

read_nifti

Wrapper to functions for reading NIFTIs

Description

Tries `RNifti::readNifti`, then `oro.nifti::readNIFTI`. If neither package is available an error is raised.

Usage

```
read_nifti(nifti_fname)
```

Arguments

nifti_fname The file name of the NIFTI.

Details

For `oro.nifti::readNIFTI` the argument `reorient=FALSE` will be used.

Value

The NIFTI

scale_design_mat	<i>Scale a design matrix</i>
------------------	------------------------------

Description

Scale the columns of a matrix by dividing each column by its highest-magnitude value, and then subtracting its mean.

Usage

```
scale_design_mat(x, doRows = FALSE)
```

Arguments

x A $T \times K$ numeric matrix. In the context of a design matrix for a GLM analysis of task fMRI, T is the number of time points and K is the number of task covariates.

doRows Scale the rows instead? Default: FALSE.

Value

The scaled design matrix

Examples

```
scale_design_mat(cbind(seq(7), 1, rnorm(7)))
```

scale_med	<i>Robust scaling</i>
-----------	-----------------------

Description

Centers and scales the columns of a matrix robustly

Usage

```
scale_med(mat, TOL = 1e-08, drop_const = TRUE, doRows = FALSE)
```

Arguments

mat	A numeric matrix. Its columns will be centered and scaled.
TOL	Columns with MAD below this value will be considered constant. Default: 1e-8
drop_const	Drop constant columns? Default: TRUE. If FALSE, set to NA instead.
doRows	Center and scale the rows instead? Default: FALSE.

Details

Centers each column on its median, and scales each column by its median absolute deviation (MAD). If there are constant-valued columns, they are removed if drop_const or set to NA if !drop_const, and a warning is raised. If all columns are constant, an error is raised.

Value

The input matrix with its columns centered and scaled.

scale_timeseries	<i>Scale the BOLD timeseries</i>
------------------	----------------------------------

Description

Scale the BOLD timeseries

Usage

```
scale_timeseries(
  BOLD,
  scale = c("auto", "mean", "sd", "none"),
  transpose = TRUE
)
```

Arguments

BOLD	fMRI data as a locations by time ($V \times T$) numeric matrix.
scale	Option for scaling the BOLD response. <code>"auto"</code> (default) will use <code>"mean"</code> scaling except if demeaned data is detected (if any mean is less than one), in which case "sd" scaling will be used instead. <code>"mean"</code> scaling will scale the data to percent local signal change. <code>"sd"</code> scaling will scale the data by local standard deviation. <code>"none"</code> will only center the data, not scale it.
transpose	Transpose BOLD if there are more columns than rows? (Because we usually expect the number of voxels to exceed the number of time points.) Default: TRUE.

Value

Scale to units of percent local signal change and centers

sign_flip	<i>Sign match ICA results</i>
-----------	-------------------------------

Description

Flips all source signal estimates (S) to positive skew

Usage

sign_flip(x)

Arguments

x	The ICA results: a list with entries "S" and "M"
---	--

Value

x but with positive skew source signals

skew_pos

*Positive skew?***Description**

Does the vector have a positive skew?

Usage

```
skew_pos(x)
```

Arguments

x The numeric vector for which to calculate the skew. Can also be a matrix, in which case the skew of each column will be calculated.

Value

TRUE if the skew is positive or zero. FALSE if the skew is negative.

sum_neighbors_vol

*Sum of each voxel's neighbors***Description**

For each voxel in a 3D logical or numeric array, sum the values of the six neighboring voxels.

Usage

```
sum_neighbors_vol(arr, pad = 0)
```

Arguments

arr The 3D array.

pad In order to compute the sum, the array is temporarily padded along each edge with the value of pad. 0 (default) will mean that edge voxels reflect the sum of 3-5 neighbors whereas non-edge voxels reflect the sum of 6 neighbors. An alternative is to use a value of NA so that edge voxels are NA-valued because they did not have a complete set of six neighbors. Perhaps another option is to use `mean(arr)`.

Details

Diagonal voxels are not considered adjacent, i.e. the voxel at (0,0,0) is not adjacent to the voxels at (1,1,0) or (1,1,1), although it is adjacent to (1,0,0).

Value

An array with the same dimensions as `arr`. Each voxel value will be the sum across the immediate neighbors. If `arr` was a logical array, this value will be between 0 and 6.

temporal_filter	<i>Temporal filtering (bandpass, highpass, lowpass) with DCT or FFT</i>
-----------------	---

Description

Temporal filtering (bandpass, highpass, lowpass) with DCT or FFT

Usage

```
temporal_filter(
  X,
  TR,
  hpf = 0.008,
  lpf = NULL,
  method = c("DCT", "FFT"),
  verbose = FALSE
)

detrend(X, TR, hpf = 0.008, method = c("DCT", "FFT"))
```

Arguments

<code>X</code>	A numeric matrix, with each column being a timeseries to filter For fMRI data, <code>X</code> should be <code>T</code> timepoints by <code>V</code> brain locations. Alternatively, a single integer giving the number of timepoints in data. The return value will be the suitable set of DCT bases. Only works with <code>method == "DCT"</code> .
<code>TR</code>	The time step between adjacent rows of <code>X</code> , in seconds.
<code>hpf</code>	The frequency of the highpass filter, in Hertz. Default: <code>.008</code> .
<code>lpf</code>	The frequency of the lowpass filter, in Hertz. Default: <code>NULL</code> (skip lowpass filtering). If both are provided, <code>lpf > hpf</code> must be true.
<code>method</code>	"DCT" (default) or "FFT". FFT is not compatible with <code>lpf</code> yet.
<code>verbose</code>	Print messages? Default: <code>FALSE</code> .

Value

Filtered `X`, or if `X` was an integer, the set of DCT bases to use for nuisance regression (not including an intercept).

Examples

```
temporal_filter(matrix(rnorm(700), nrow=100), TR=.72)
```

unmask_mat	<i>Unmask matrix data</i>
------------	---------------------------

Description

Insert empty rows or columns to a matrix. For example, medial wall vertices can be added back to the cortex data matrix.

Usage

```
unmask_mat(x, mask, mask_dim = 1, fill = NA)
```

Arguments

x	The data matrix to unmask.
mask	The logical mask: the number of TRUE values should match the size of the (mask_dim)th dimension in dat.
mask_dim	Rows, 1 (default), or columns, 2.
fill	The fill value for the inserted rows/columns. Default: NA.

Value

The unmasked matrix.

unvec_mat	<i>Transform vector data to image</i>
-----------	---------------------------------------

Description

From a $v \times p$ matrix of vectorized data and an $m \times n$ image mask with v in-mask locations, create a list of $p \times m \times n$ data arrays in which the mask locations are filled in with the vectorized data values.

Consider using `abind::abind` to merge the result into a single array.

Usage

```
unvec_mat(x, mask, fill_value = NA)
```

Arguments

x	$v \times p$ matrix, where v is the number of voxels within a mask and p is the number of vectors to transform into matrix images.
mask	$m \times n$ logical matrix in which v entries are TRUE and the rest are FALSE.
fill_value	Out-of-mask value in the output image. Default: NA.

Value

A list of masked values from x

Examples

```
x <- unvec_mat(
  cbind(seq(3), seq(2,4), seq(3,5)),
  matrix(c(rep(TRUE, 3), FALSE), ncol=2),
  0
)
y <- array(c(1,2,3,0,2,3,4,0,3,4,5,0), dim=c(2,2,3))
stopifnot(identical(x[[1]], y[, ,1]))
stopifnot(identical(x[[2]], y[, ,2]))
stopifnot(identical(x[[3]], y[, ,3]))
```

unvec_vol	<i>Convert vectorized data back to volume</i>
-----------	---

Description

Un-applies a mask to vectorized data to yield its volumetric representation. The mask and data should have compatible dimensions: the number of rows in dat should equal the number of locations within the mask.

Usage

```
unvec_vol(dat, mask, fill = NA)
```

Arguments

- dat Data matrix with locations along the rows and measurements along the columns. If only one set of measurements were made, this may be a vector.
- mask Volumetric binary mask. TRUE indicates voxels inside the mask.
- fill The value for locations outside the mask. Default: NA.

Value

The 3D or 4D unflattened volume array

UT2mat

*Upper Triangular Vector to Matrix***Description**

Creates a square matrix from a vector which gives the values for the upper triangle. By default, the vector is expected to include the diagonal values, and the values in the upper triangle are copied to the lower triangle so that the result is symmetric.

Usage

```
UT2mat(x, diag = "x", LT = "x")
```

Arguments

x	A vector of values for the upper triangular elements of the desired square matrix.
diag	The values to put on the diagonal, or "x" (default) if x includes the diagonal values.
LT	The values to put on the lower triangle, or "x" (default) to use the upper triangular values such that the result is symmetric. (LT should not contain the diagonal values, which are provided with diag or x).

Value

A square matrix.

Examples

```
UT2mat(seq(10)) # defaults: diag="x", LT="x"
#      [,1] [,2] [,3] [,4]
# [1,]    1    2    4    7
# [2,]    2    3    5    8
# [3,]    4    5    6    9
# [4,]    7    8    9   10
UT2mat(seq(3), LT=8)
#      [,1] [,2]
# [1,]    1    2
# [2,]    8    3
UT2mat(seq(6), diag=0, LT=seq(7,12))
#      [,1] [,2] [,3] [,4]
# [1,]    0    1    2    4
# [2,]    7    0    3    5
# [3,]    8   10    0    6
# [4,]    9   11   12    0
UT2mat(rep(-1, 3), diag=c(4,5,6), LT=0)
#      [,1] [,2] [,3]
# [1,]    4   -1   -1
# [2,]    0    5   -1
# [3,]    0    0    6
```

validate_design_mat	<i>Validate design matrix</i>
---------------------	-------------------------------

Description

Coerces design to a numeric matrix, and optionally checks that the number of rows is as expected. Sets constant-valued columns to 1, and scales all other columns.

Usage

```
validate_design_mat(design, T_ = NULL)
```

Arguments

design	The design matrix
T_	the expected number of rows in design. Default: NULL (no expected value to validate).

Value

The (modified) design matrix

var_decomp	<i>Compute variance decomposition</i>
------------	---------------------------------------

Description

Calculate the various ANOVA sums of squares for repeated measures data. For each variable, subjects with any missing measurement are excluded.

Usage

```
var_decomp(x, verbose = FALSE)
```

Arguments

x	The data as a 3D array: measurements by subjects by variables. (Alternatively, a matrix that is measurements by subjects, if only one variable exists.)
verbose	If TRUE, display progress of algorithm. Default: FALSE.

Value

The variance decomposition.

vox_locations	<i>Get coordinates of each voxel in a mask</i>
---------------	--

Description

Made for obtaining voxel locations in 3D space from the subcortical metadata of CIFTI data: the volumetric mask, the transformation matrix and the spatial units.

Usage

```
vox_locations(mask, trans_mat, trans_units = NULL)
```

Arguments

- mask 3D logical mask
- trans_mat Transformation matrix from array indices to spatial coordinates.
- trans_units Units for the spatial coordinates (optional).

Value

A list: coords and trans_units.

Index

`all_binary`, 3
`all_integers`, 4
`as.matrix_ifni`, 4

`bandstop_filter`, 5

`carpetplot`, 6
`carpetplot_stack`, 7
`cheby2`, 5
`colCenter`, 8
`color_palette`, 8
`CompCor`, 9, 11
`CompCor_HCP`, 11
`coordlist_to_vol`, 13
`crop_vol`, 14

`dct2Hz (dct_convert)`, 15
`dct_bases`, 11, 14, 15
`dct_convert`, 15
`despike_3D`, 16
`detrend (temporal_filter)`, 44
`dice_coef`, 16
`dilate_mask_vol`, 17
`dual_reg`, 18
`dual_reg_par`, 20

`erode_mask_vol`, 21
`expand_RPs`, 22

`flags2spikes`, 23
`fMRITools`, 23
`fMRITools-package (fMRITools)`, 23
`fsl_bptf`, 19, 21, 24, 34

`hat_matrix`, 25
`Hz2dct (dct_convert)`, 15

`infer_format_ifni`, 25, 26
`infer_format_ifni_vec`, 26
`is_1`, 26
`is_constant`, 27

`is_integer`, 27
`is_posNum`, 28

`mask_BOLD`, 28
`mat2UT`, 29
`match.arg`, 30
`match_exactly`, 29
`match_input`, 30
`match_nets`, 31
`mean_squares`, 32
`Mode`, 32

`norm_BOLD`, 33
`nuisance_regression`, 34

`pad_vol`, 35
`PCA`, 36
`pct_sig`, 37
`plot_FC`, 37
`plot_FC_gg`, 38

`read_nifti`, 39

`scale_design_mat`, 40
`scale_med`, 41
`scale_timeseries`, 41
`sign_flip`, 42
`skew_pos`, 43
`sum_neighbors_vol`, 43

`temporal_filter`, 44

`uncrop_vol (pad_vol)`, 35
`unmask_mat`, 45
`unvec_mat`, 45
`unvec_vol`, 46
`UT2mat`, 47

`validate_design_mat`, 48
`var_decomp`, 48
`vox_locations`, 49